# STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION OFFICE OF OIL AND GAS

## AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE IN TRIPLICATE, one copy mailed to the Department, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Farm name:_	H.D. Cle	eaveng	er		Operato	or Well	No.:_	2-13	23 (0	0671)	i.	
LOCATION:	Elevation:	1340'			Quadr							
200/1110(1)	District:	Pleasan	t		Count	hv	Ba	rbou	r			
	Latitude:									Coo		
										Sec.		
	Longitude: _		Feet W	lest of .	00	_Deg.	03	Min.	-10	Sec.		
Well Type: 0	OIL 0	GAS X										
Company CoalQuest Development Coal Operator or Owner 100 Tygart Drive, Grafton, WV 26354											_	
				Coal O	perator							
Agent Permit Issue	Charles E	02/05/20	orth c	or Own	-							
				Α	FFIDAV	/IT						
STATE OF W												
Kevin S. Wri	ght	and	Matthew A.	Yearsle	y		bein	a first	dulv sv	vorn accord	ing to law d	epose
and say that th												
well operator,												ed on
the 2nd	day ofJ	urie	, 20 <u>20</u> , a	and the	well wa	s plugg	ed and	filled	in the fo	illowing mar	nner:	
TYPE	FR	ОМ	ТО		PIPE REMOVED				LE	FT		
Expandable Cen	nent 44	53'	1270'									
Thixotrop c Cement w/ Green	Dya 12	70'	600'					E-E				
Expandable Cen	nent 60	00'	Surface	<b>;</b>								
4 1/2" Casing	15	96'	4521'			15	96'			292	25'	
8 5/8" Casing			1022'		Milled 25'				99			
13 3/8" Casin			9'		01				9			
16" Conducto	r Sur	face	5'	1		(	)*			5		
Description said well was	of monument: completed on			me, well #, /		ate cement 2020 .	ed,	аг	d that t	he work of p	olugging and	filling
	deponents sa			evin S	5. Wr				۲-		NOTADY DUD	IC OFFICIAL SEAL (
			Mai	thew A	. Years	ley		_	- 1	1	THOMAS State of V	JC OFFICIAL SEAL J SULLIVAN West Virginia
Sworn and	subscribe bef	fore me thi	s 29+2 day	/ of	Jor	0	_, 20_7	2	1	52	Septemb	pission Expires per 15, 2022 Clarksburg, WV 26301
My commission	on expires:	29/15	أحد		_	L	Notary I	Public				
Affidavit revie	wed by the Of	fice of Oil a	and Gas: 🗾	Enn.	M.	2.0	Ly.	rld	_ Title:	012,	+ 6N5	INSPECTOR

# Plugging Report for MSHA

Well Nur	mber:2	1323 (067	1)	Mine: Arch	Coal - Sentine	I Mine	_	Surface	
									Top of 8 5/8", 13 3/8" and 16" Conductor Casing at Surface
Permit N		47-001-0							Bottom of 16" Conductor Casing at 5'
	an Out Starte		6/2/2020						Bottom of 13 3/8" Conductor Casing at 9'
	II Bore Plugge		6/19/2020	- 00F					
	ttanning Coal	Seam:	800 ft.	To <u>805</u>	ft.			Expa	
Plugs: From	n	То		Type of Ce				ndab	
445	3'	1596			Expandable Gas Blocker			Expandable Gement	
159	6'	1270			Expandable ment			ent	
127	0'	600'			Thixotropic / Green Dye				
600	)'	Surfac	155 sks of I		Expandable nent				
G W		10 FEW 1875		Ce					
Casing	Remaining	in Well I	Bore		<u>_Th</u>	ix Top:	600'		
Sucker Rods	Тор	Botton	n Left	Pulled				fixote W/ C	
2 3/8" tubing 4 1/2" casing	1596'	4521'	2925'	1596'				otropio i	
7" casing 7" fiberglass								Dye	
8 5/8" casing 13 3/8" casing	Surface Surface	1022' 9'	997'	Milled 25'					
16" Conducto		5'	5'	0			800' - 805'		Milled 25' (790' - 815')
					Lower Kittan	ning Coal		umm.	
Cement: Expandable		43	=	sacks				nixotropia	
Thixotropic Econofill	-	19		sacks sacks				orde	
Mud Flush Other	-	100	10	gal				Gement v	Bottom of 8 5/8" Casing at 1022'
Est. Top Thix Did Cement C	-	Ye	•	ft				tite Mi	bottom of o old odding at 1022
	ic.	re	5	_	This	D = 44 = ····	40701	Gree	N.
Comments:	treme	Moderate	Normal		Inix	Bottom:	1270		
Lost Circulation			<mark>oderate</mark> eme Mo	Normal derate <i>Normal</i>	į.				
Debris in Well		Wood	Steel	Other:					
									Top of 4 1/2" Casing at 1596'
								D.	
								Expandable Cement	
								S-eide	
Surface Elev	ration (Surve	yed)	1340'					eme	
Bottom of Co Dif	al Structure ( ference	(Map)	535' 805'						
		į.							
					To	tal Depth:	4453'		
Note: All depth	ıs shown wei	e measure	d from 10' abo	ve the surface.		Jopan			

Bottom of 4 1/2" Casing at 4521'

FORM WR-38 (Affidavit of Plugging)

#### **WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION** OIL AND GAS WELLS DIVISION

## AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

COALQUEST DEVELOPMENT, LLC.

Coal Operator or Owner

100 TYGART DRIVE GRAFTON, WV 26354

Address

COALQUEST DEVELOPMENT, LLC.

Coal Operator or Owner

100 TYGART DRIVE GRAFTON, WV 26354

Address

CHARLES E. CLEAVENGER, ET AL

Lease or Property Owner 185 MARYS LANE PHILIPPI, WV 26416

Address

**WOLF RUN MINING LLC** 

Name of Well Operator

100 TYGART DRIVE GRAFTON, WV 26354

**Complete Address** 

PHILIPPI (545)

Well Location

**PLEASANT District** 

**BARBOUR** 

County

2-1323 Well No.

H.D. CLEAVENGER

Farm

STATE INSPECTOR SUPERVISING PLUGGING

**AFFIDAVIT** 

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

MATTHEW A. YEARSLEY and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Wolf Run Mining, LLC well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 2<sup>nd</sup> day of June, 2020 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In			
Formation	M						
	rough 4 ½" casing from surface to 4453'. 53'. Cemented bottom hole with 180 sacks	4 ½" Casing	1596'	2925'			
of Expandable Cement	with a gas blocker additive from 4453' to of 4 ½" casing from surface to 1596'. Left	8 5/8" Casing	Milled 25'	997'			
2925' of 4 1/2" casing fro	om 1596' to 4521'. Cleaned a 7 7/8" hole ragged bottom hole cement plug at 1596'.	13 3/8" Casing	0	9'			
Set intermediate plug fi Expandable Cement. S through the Lower Kitta 8 5/8" casing from surfa to extreme cement bon perforations or rips wer Petition. All casing dep All electronic logs and a surface.  Cemented hole from 'From 1270' to 600' with Green Dye. From 600' Cement. Cement did ci cement were used to c	from 1596' to 1270' with 100 sacks of section milled 8 5/8" from 790' to 815' sanning Coal Seam (800' – 805'). Left 790' of ace to 790' and 207' from 815' to 1022' due d on 8 5/8" casing. No additional re required per the Sentinel Mine 101C this were taken from previous well records. In the section of the sacks of Thixotropic Cement with to surface with 155 sacks of Expandable reculate at surface. A total of 630 sacks of ement the well to surface. Left 5' of 16"	16" Conductor 0					
conductor pipe in the w	reli at surface.	D					
Coal Seams	0001 0051	Description of Monument					
Kittanning Coal Seam	800' – 805'	77" of 7" casing w/ company name, well number,					
		permit number and date cemented stated on 7" casing. Well marker will be attached to cement					
		plug at ground level.	4				

... and that the work of plugging and filling said well was completed on the 19th day of June, 2020

And further deponents saith not.

Matthew A. Yearsley

Matthew A. Yearsley

Kevin S. Wright

Kevin S. Wright

Sworn to and subscribed before me this the day of Jone, 2020

Notary Public

My commission expires:

NOTARY PUBLIC OFFICIAL SEAL THOMAS J SULLIVAN State of West Virginia My Commission Expires September 15, 2022 52 Canterbury Dr Clarksburg, WV 26301

Permit No. 47-001-00671

Well No. 2-1323

Latitude: 39° 13' 15" N Longitude: 80° 05' 16"W