


AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

COALQUEST DEVELOPMENT, LLC.
Coal Operator or Owner
100 TYGART DRIVE GRAFTON, WV 26354
Address
COALQUEST DEVELOPMENT, LLC.
Coal Operator or Owner
100 TYGART DRIVE GRAFTON, WV 26354
Address
BECKWITH LUMBER CO., INC.
Lease or Property Owner
P.O BOX 39, SLATY FORK, WV 26291
Address

WOLF RUN MINING, LLC
Name of Well Operator
100 TYGART DRIVE GRAFTON, WV 26354
Complete Address
PHILIPPI (545)
Well Location
PLEASANT
District
BARBOUR
County
BAR-910
Well No.
SADIE C. LAKE
Farm

STATE INSPECTOR SUPERVISING PLUGGING




AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:
MATTHEW A. YEARSLEY and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Wolf Run Mining, LLC well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 20th day of April, 2021 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Cleaned a 3 3/4" hole through the existing 4 1/2" casing from surface to 4600'. Tagged plug at 4600'. Cemented the bottom hole with 140 sacks of Expandable Cement with gas blocker additive from 4600' to 2300'. Tagged top of bottom hole plug at 2300'. Removed 2300' of 4 1/2" casing from the surface to 2300'. Left 2361' of 4 1/2" casing in the hole from 2300' to 4661'. Cleaned a 7 7/8" hole from the surface to 2300'. Cemented intermediate plug using 245 sacks of Expandable Cement from 2300' to 1374'. Tagged top of intermediate plug at 1374'. Section milled 26' window in 8 5/8" casing from 958' to 984' which also removed the 8 5/8" casing through the Lower Kittanning Coal Seam (969' - 974'). Left 958' of 8 5/8" casing in the hole from the surface to 958' and 285' from 984' to 1269'. Due to extreme cement bond on the 8 5/8" casing, no additional perforations or rips were required per the Sentinel Mine 101C petition. Left 241' of 11 3/4" casing in the hole from 241' to surface. Casing depths for bottom of casing were taken from previous well records. All depths shown above were taken from 10' above the surface.	4 1/2" Casing	2300'	2361'	
		8 5/8" Casing	Milled 26'	1243'
		11 3/4" Casing	241'	0'
Cemented the hole from 1374' to surface as follows: From 1374' to 769' with 175 sacks of Thixotropic Cement with Green Dye. From 769' to surface with 150 sacks of Expandable Cement. Cement did circulate at surface. A total of 710 sacks of cement were used to fill the well 4600' to surface.				
Coal Seams		Description of Monument		
<u>Kittanning Coal Seam</u>	<u>969' - 974'</u>	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.		

... and that the work of plugging and filling said well was completed on the 7th day of May, 2021

And further deponents saith not.



Sworn to and subscribed before me this 14th day of May, 2021

Matthew A. Yearsley

Matthew A. Yearsley

Kevin S. Wright

Kevin S. Wright



Notary Public

My commission expires: 09/15/22

Permit No. 47-001-00910
Well No. BAR-910
Latitude: 39° 13' 29" N
Longitude: -80° 06' 08" W

06/04/2021