

COMPLETION DATE	5-Jun-03								
WN 5999	1ST STG	2ND STG	3RD STG	4TH STG	5TH STG				
	Middle Huron	Upper Huron	Weir	Lower Big Lime	Upper Big Lime				
PERFS	4880' - 5178'	4242' - 4316'	3776' - 3784'	3496' - 3502'	3294' - 3312'				
NO.	17	18	17	13	15				
Treated Water	110	120	120	100	100				
ACID	0	250	250	2500	2500				
%	NA	15	15	28	28				
PERF BALLS	0	0	0	0	0				
SAND	25,000	20/40	25,000	20/40	25,000	20/40	0	0	0
CONC.	1 TO 4		1 TO 4		1 TO 4		0	0	0
N2 QUAL	70 Q		70Q		70 Q		200 SCF/BBL	200 SCF/BBL	200 SCF/BBL
N2 VOL	250,000 SCF		210,000 SCF		160,000 SCF		30,000	30,000	30,000
BPM	20		20		20		12	12	12
FRAC BALL	NA		3.25		3.375		3.5	3.75	3.75
FG	0.5		0.5		0.45		NA	NA	NA
N2 FACTOR	850		755		580		NA	NA	NA
BAFFLES	3 1/16"	4348'							
	3 5/16"	3893'							
	3 7/16"	3570'							
	3 9/16"	3360'							