



New Location   
 Drill Deeper   
 Abandonment

5.24 S  
 4.50 W

Company W. VA. PIPE PROJECT  
 Address P.O. Box 2452, TULSA, OKLA.  
 Farm J. A. WETHERELL  
 Tract \_\_\_\_\_ Acres 75 Lease No. \_\_\_\_\_  
 Well (Farm) No. 1 Serial No. F-7766  
 Elevation (Spirit Level) 1125  
 Quadrangle MADISON  
 County BOONE District WASHINGTON  
 Engineer PAUL E. JOACHIM  
 Engineer's Registration No. 669  
 File No. 46-35 Drawing No. \_\_\_\_\_  
 Date JUNE 11, 1949 Scale 1" = 400'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

**WELL LOCATION MAP**  
 FILE NO. B00-172-A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 - Denotes one inch spaces on border line of original tracing.



607 ✓

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

Ab 172-A

WELL RECORD

Permit No. \_\_\_\_\_

Oil or Gas Well Gas  
(KIND)

Company West Virginia Pipe Project  
Address Box 2452, Tulsa, Oklahoma  
Farm J. A. Weatherall Acres 75  
Location (waters) \_\_\_\_\_  
Well No. 11251 1 Elev. 1125'  
District Washington County Boone  
The surface of tract is owned in fee by \_\_\_\_\_  
Address \_\_\_\_\_  
Mineral rights are owned by \_\_\_\_\_  
Address \_\_\_\_\_

Drilling commenced March 23, 1926  
Drilling completed June 13, 1926  
Date Shot \_\_\_\_\_ From \_\_\_\_\_ To \_\_\_\_\_  
With \_\_\_\_\_

Open Flow \_\_\_\_\_ /10ths Water in \_\_\_\_\_ Inch  
\_\_\_\_\_ /10ths Merc. in \_\_\_\_\_ Inch  
Volume \_\_\_\_\_ Cu. Ft.  
Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
Fresh water \_\_\_\_\_ feet \_\_\_\_\_ feet  
Salt water \_\_\_\_\_ feet \_\_\_\_\_ feet


Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16		32	Kind of Packer
13			Bottom Hole &
10		557	anchors 6-5/8 x
8 1/4		1030	Size of 8-1/4" & 2 x 6-5/8"
6 5/8		1445	Depth set 1445,
5 3/16	6-5/8" Steel Shoe		1479 & 1435'
3	on bottom of casing		Perf. top
2	with 8' of perforated		Perf. bottom
Liners Used	casing between		Perf. top
	packer and bottom		Perf. bottom
	hole shoe.		

CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_

COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Soil			0	45			
Sand & Slate			45	585			
Salt Sand			585	1030			
Lime			1030	1100			
Maxon			1100	1220			
Red Rock			1220	1295			
Lime			1295	1300			
Slate			1300	1312			
Black Lime			1312	1431			
Big Lime			1431	1603			
Big Injun			1603	1653			
Shells			1653	2086			
Brown Shale			2086	2110			
Berea			2110	2131			
Total Depth				2200			

(Filled back to 1653' - Sand and rock)



JAN 20 1950

