



NOTE: This plat revises the plat dated April 30, 1960.

New Location  REVISED NOTE:  
 Drill Deeper   
 Abandonment

Wayne F. Gaskins owns 1/2 Oil & Gas Rights.  
 H.G. Evans owns 1/2 Oil & Gas Rights.

Company	INCO - 3	
Address	40 FRANKLIN MICHELS WEST UNION, W. VA.	
Farm	WAYNE F. GASKINS	
Tract	Acres 5 1/4	Lease No.
Well (Farm) No.	1	Serial No.
Elevation (Spirit Level)	1069'	
Quadrangle	CENTERPOINT SW	
County	DODDRIDGE	District WEST UNION
Engineer	JOHN W. HAMILTON	
Engineer's Registration No.	2274	
File No.	Drawing No.	
Date	JULY 14, 1960 Scale 1" = 5 POLES	

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. DoD-373- Revised

+ Denotes location of well on United States Topographic Maps, scale 1" to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.



STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION 4

Quadrangle CENTERPOINT

Permit No. DOD-373-REV.

WELL RECORD

Oil or Gas Well GAS - OIL  
(KIND)

Company INCO 3, INC.  
Address WEST UNION, W. VA.  
Farm WAYNE F. GASKINS Acres 5 1/4  
Location (waters) \_\_\_\_\_  
Well No. 1 Elev. 1121'  
District WEST UNION County DODDRIDGE  
The surface of tract is owned in fee by WAYNE F. GASKINS  
Address WEST UNION, W. VA.  
Mineral rights are owned by WAYNE F. GASKINS  
Address WEST UNION, W. VA.  
Drilling commenced JULY 2, 1960  
Drilling completed SEPT. 5, 1960  
Date Shot From \_\_\_\_\_ To \_\_\_\_\_  
With \_\_\_\_\_

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
18 3/8	18	18' 18"	
10			Size of
8 3/4	405		
6 3/8	1243		Depth set
5 3/16	2047	2047 1/2"	
3		2047	Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

Open Flow /10ths Water in \_\_\_\_\_ Inch  
/10ths Merc. in \_\_\_\_\_ Inch  
Volume 130,000 130,000 Cu. Ft.  
Rock Pressure 110 110 lbs. hrs.  
Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
WELL ACIDIZED \_\_\_\_\_  
WELL FRACTURED 9-6-60 9-6-60

CASING CEMENTED 5 1/2 5/8 SIZE 2047 No. Ft. 8-20-60 Date  
20 bags 20 bags Portland Cement - 500#  
Garaton Service Aquagel  
COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES

RESULT AFTER TREATMENT 1,000,000 1,000,000  
ROCK PRESSURE AFTER TREATMENT 600 600# 24 Hours  
Fresh Water \_\_\_\_\_ Feet Salt Water \_\_\_\_\_ Feet

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
RED CLAY	RED	SOFT	= 0	6			
SAND	BROWN	MED.	6	36			
RED ROCK	RED	SOFT	36	51			
CLAY	WHITE	SOFT	51	68			
LIME	GRAY	HARD	68	72			
RED ROCK & LIME	RED		72	92			
SLATE & SHELL			92	150			
RED ROCK & LIME	RED		150	167			
SLATE & SHELL			167	188	WATER	188'	
RED ROCK & LIME	RED		188	210			
SLATE & SHELL			210	336			
LIME	DARK	HARD	336	448	WATER	425'	
RED LIME	RED	HARD	448	460	WATER	430'	3 BARRELS IN 36 HOURS.
LIME	GRAY	HARD	469	475			
SAND			475	515			
SLATE & SHELL			515	543			
LIME	GRAY	HARD	543	556			
LIME	REDM	HARD	556	650			
SLATE & SHELL			650	706			
RED LIME	RED		706	722			
SLATE & SHELL			722	740			
LIME	GRAY		740	796			
SLATE & SHELL			796	807			

Formation	Color	Hard or Soft	Top 4	Bottom	Oil, Gas or Water	Depth Found	Remarks
LIME	GRAY	HARD & GRITTY	807	830			
SLATE & SHELL			830	832			
SAND STRAY			832	875			
RED LIME	RED		875	922			
LIME	GRAY	HARD	922	936			
RED ROCK	RED	SOFT	936	945			
LIME	GRAY	HARD	945	1019			
RED ROCK	RED	SOFT	1019	1031			
LIME	GRAY	HARD	1031	1110			
RED ROCK	RED	SOFT	1110	1131			
LIME	DARK	HARD	1131	1165			
RED ROCK	RED	SOFT	1165	1200			
LIME	GRAY	HARD	1200	1235			
SHALE	BLACK	SOFT	1235	1248			
LIME	GRAY	MED. HARD	1248	1270			
SAND DUNKARD	BROWN		1270	1300			
SLATE & SHELL			1300	1360			
LIME	GRAY		1360	1389			
GAS SAND		MED. HARD	1389	1416			
SLATE	BLACK		1416	1426			
BROKEN SALT SAND			1426	1480			
SLATE & SHELL	BROWN		1480	1519			
BROKEN SALT SAND			1519	1537			
SALT SAND		HARD	1537	1660			
SLATE	BLACK		1660	1670			
SALT SAND		MED HARD	1670	1702	WATER	1697-1702	300' 1HR 6 1/2"
LIME	DARK	HARD	1702	1707			
SLATE & SHELL	DARK		1707	1760			
LIME	DARK	GRITTY	1760	1785			
SALT SAND			1785	1833			
SLATE	DARK		1833	1819			
MAXON SAND STRAY			1819	1885			
BROKEN SAND			1885	1930	LIME		
LIME	GRAY	GRITTY	1930	1965			
BROKEN SAND			1965	1997			
SLATE	BLACK		1997	2000			
LIME			2000	2024			
BLUE MON. SAND			2024	2072			
BIG LIME	DARK		2072	2141			
INJUN SAND			2141	2253	GAS	2142-2156	6/10 WATER 8" OPENING
DARK SLATE	DARK		2253	2254			
SAND PAID			2254	2269	GAS INC.	2171-2193	12/10 WATER 8" OPENING
LIME	DARK	GRITTY	2269	2282			
SLATE	SOFT DARK	SOFT	2282		GAS SOME OIL	2245 2253	14/10 WATER 2" OPENING
WELL SHUT DOWN IN SALTE			2284				

Date 7-21, 1968

APPROVED G. J. [Signature], Owner

By [Signature] (Title)