



New Location
 Drill Deeper
 Abandonment

Company S. & R. Oil & Gas Co., James Scott, Agt.
 Address 124 Valley St., Salem, W. Va.
 Farm Will E. Morris
 Tract #1 Acres 80 Lease No. _____
 Well (Farm) No. 1 Serial No. _____
 Elevation (Spirit Level) 846
 Quadrangle Centerpoint C
 County Doddridge District McClellan
 Engineer Parker E. Peters
 Engineer's Registration No. 485
 File No. _____ Drawing No. _____
 Date Oct. 4, 1962 Scale 1" = 40 P.

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP

FILE NO. DOD-883-REVISED LOCATION
 (WLD 72276)

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.



STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

Quadrangle Centerpoint
DOD
Permit No. 883

WELL RECORD

Oil or Gas Well Both
(KIND)

Company S & R Oil & Gas Company
Address 124 Valley Street, Salem, W. Va.
Farm Will E. Morris Acres 80
Location (waters) Robinson Fork
Well No. 1 Elev. 846
District McClellan County Doddridge
The surface of tract is owned in fee by Lee Ash
Address Rt. 2, Salem, W. Va.
Mineral rights are owned by Harrison Ritchie Oil & Gas Co.
Address Clarksburg, W. Va.
Drilling commenced November 21, 1962
Drilling completed December 30, 1962
Date Shot _____ From _____ To _____
With _____
Open Flow 11/10ths Water in 1" Inch
_____/10ths Merc. in _____ Inch
Volume 30,000 Cu. Ft.
Rock Pressure 36 lbs. 12 hrs.
Oil 1/2 bbls., 1st 24 hrs.
WELL ACIDIZED No

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16"	15'	15'	Kind of Packer
13	33'		
10	215'		Size of
8 3/4			
6 5/8	896'	896'	Depth set
5 3/16	1969'	1969'	
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

WELL FRACTURED With 1200 bbls water and 53,000 lbs. sand.
RESULT AFTER TREATMENT 45,000 Cu. Ft. of gas & 1/2 bbl. oil in 24 hrs.
ROCK PRESSURE AFTER TREATMENT 46 lbs.
Fresh Water 18' & 39' Feet Salt Water None Feet

CASING CEMENTED Yes SIZE 5 1/2" No. Ft. 400 Ft. Date 1/1/63
70 sks. cement, 6 sks. aquagel,
GARATON
COAL WAS ENCOUNTERED AT 464 FEET to 471 INCHES
____ FEET _____ INCHES FEET _____ INCHES
____ FEET _____ INCHES FEET _____ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
Soil			0	29	Water @	18' & 39'	
Slate & Shells			29	35			
Sand			35	40			
Red rock			40	70			
Slate			70	130			
Sand			130	190			
Slate & Shells			190	425			
Red rock			425	435			
Slate			435	464			
Pitt. Coal			464	471			
Slate & shells			471	745			
Lime			745	815			
Red Rock			815	850			
Slate & shells			850	985			
Lime (gritty)			985	1140			
Sand			1140	1584			
Slate & lime			1584	1709			
Big lime			1709	1778			
Lime (gritty)			1778	1802	Gas @	1802-1817 & 1820-1831 &	
Sand			1802	1854		1845-1855	
Lime (dark)			1854	1857	Oil @	1802-1817 & 1820-1831 &	
Sand			1857	1928		1845-1855 & 1896-1902 &	
Slate			1928	1969		1922-1928	

(over)

