

Latitude 39° 17' 30"

+ 7.5'

80° 37' 30"

Longitude

Topo Location

7.5' Loc. 1.325 15' Loc. 4.205
2.17W (calc.) 4.40W

Company _____

Farm B. F. Davis #1

15' Quad Centiput SC
(sec.)

7.5' Quad Smithburg

District GRANT

WELL LOCATION PLAT

County 017 Permit 30107

B. F. DAVIS NO. 1 WELL.

No. 96 O.F. (Dodd).

Grant District, Doddridge County, W. Va.
 South Penn Oil Co., Chamber of Commerce Bldg., Pittsburgh, Pa.
 On 79 acres, surface ~~and mineral rights~~ owned by B. F. Davis Heirs,
 May Davis, Salem, W. Va., and mineral rights owned by G. F.
 Davis et al., Route 2, Salem, W. Va.

Elevation, 845.07' L.

1' conductor; 10" casing, 230' (pulled); 8 $\frac{1}{2}$ " 917' (pulled);
 6-5/8", 1717'; 2" tubing, 1809'.

Anchor packer, 2 x 6-5/8, set at 1741'.

Coal was encountered at 390-397'.

Abandonment reported to Dept. of Mines May 31, 1935.

Well was shot at 1789-1796'.

Producing hole in Injun Sand.

	Top.	Bottom.
Pittsburgh Coal	390	- 397
Little Dunkard Sand	841	- 852
Big Dunkard Sand	910	- 985
Gas Sand	1056	- 1131
1st Salt Sand	1230	- 1275
2nd Salt Sand	1290	- 1487
Maxton Sand	1630	- 1640
Little Lime	1660	- 1697
Pencil Cave	1697	- 1712
Big Lime	1712	- 1755
Big Injun Sand	1755	- 1860
Gantz Sand	1950	- 2070
Fifty-foot Sand	None	
30-Ft. Sand	None	
Gordon Stray Sand	None	
Gordon Sand	2430	- 2441
Fourth Sand	None	
5th Sand	None	
Total depth		2552

PRELIMINARY DATA SHEET NO. 1

Well No. 1
Company of Chamber of Commerce Plg.
on the B. F. Davis farm
containing 79 acres. Location Dodderidge County, West Virginia

The surface of the above tract is owned in fee by B. F. Davis heirs s/o May Davis,
G. F. Davis et al address, and the mineral rights are owned by
Rto #2, Salem, W. Va.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit
issued by the West Virginia Department of Mines, Oil and Gas Division

at 10 feet
Elevation of surface at top of well 945.07'
Snick Barometric

The number of feet of the different sized casings used in the well.
12 feet
250 (Pulled) feet 10" size, csg. 2" sub. 2000 1809', 2500 feet
917 (Pulled) feet 8-1/4" size, csg. feet
1717 feet 6-5/8" size, csg. feet
Anchor packer of 2 I 6-5/8" size, set at 1741'
packer of _____ size, set at _____

in casing perforated at _____ feet to _____ feet
in casing perforated at _____ feet to _____ feet
Coal was encountered at 590 feet, thickness 84 inches, and at _____ feet; thickness _____ inches; and at _____ feet; thickness _____ inches.

Linen were used as follows: (Give details) _____

Approved [Signature] SOUTH PENN OIL COMPANY, Owner
Date May 31, 1955.

State of West Virginia
e/o Auditor's Office,
Charleston, W. Va.
SOUTH PENN OIL COMPANY
Chamber of Commerce Plg.
Pittsburgh, Pa.
September 10, 1955.
WELL AND LOCATION
Grant District
Dodderidge County
Farm
Well No. 1
B. F. Davis

AFFIDAVIT
STATE OF WEST VIRGINIA
County of HARRISON
I, J. F. Black
being first duly sworn according to law depose and say that they are experienced in the work of plugging
and filling oil and gas wells and were employed by South Penn Oil Company, well operator,
and participated in the work of plugging and filling the above well, that said work was commenced on the
26th day of JUNE, 1955, and that the well was plugged and filled in
the following manner:

Manner in which said well was plugged:
Total Depth 2552'. Filled with non-porous material to 2410', - 20' above
Gordon Sand. Set wood plug 2410' - 2407'. Set cement plug 2407'-2597', -
sealing Gordon Sand. Filled with non-porous material to 1950', - 20' above
Cant's Sand. Set wood plug 1950' - 1927'. Set cement plug 1927', - 1917', -
sealing Cant's Sand. Set bridge 1867', - below Big Injun Sand. Filled with
non-porous material to 1725', - 20' above Big Injun Sand. Set wood plug
1725' - 1732'. Set cement plug 1732' - 1722', - sealing Big Injun Sand. Out
and pulled 437' of 6-5/8" casing. Set bridge 1917', - 30' below 2nd Salt
Sand. Filled with non-porous material to 1210', - 20' above 1st Salt Sand.
Set wood plug 1210'-1207'. Set cement plug 1207' - 1197', - sealing Salt
Sands. Set bridge 437'. Vent 437' to surface. Vent pipe perforated 437'-427'.
Set Morning Glory Packer 427', - 30' below Pittsburgh Coal. Cement vent pipe
427' - 370', - 20' above Pittsburgh Coal. Filled with non-porous material to
surface.

Description of monument. 2" pipe 8' above ground 2" tee, 2-2" elle pointing downward, 2' cement cone around vent pipe 2' above ground.

The above descriptions must be in detail and in accordance with the provisions of section 16, article 4, chapter 49 of the code, and that the work of plugging and filling said well was completed on the 24th day of JUNE, 1955.

And further deposes that he