

Latitude 39°12'30"

Longitude 88°23'08"

75'

Topo Location

7.5' Loc. 1.03S 15' Loc. 3.91S  
0.46W (calc.) 2.69W

Company C-149

Farm J. H. Cunningham

15' Quad Vada NE  
(sec.)

7.5' Quad Big Isaac

District GREENBERG

WELL LOCATION PLAT

County 017 Permit 30128



**AFFIDAVIT IN TRIPLICATE TO TIME AND MANNER OF  
PLUGGING AND FILLING WELL**

(REQUIREMENTS OF SECTION 5, ARTICLE 5, CHAPTER 24 OF THE CODE)

**WEST VIRGINIA DEPARTMENT OF MINES  
OIL AND GAS DIVISION**

No. 28711 AD 2011 SICRALLY RAAD & MOSS  
WELL OPERATOR OR OWNER NAME OF WELL OPERATOR  
SALES, W. VA.  
DATE OF WELL OPERATION  
MARCH 1, 1935  
WELL AND LOCATION  
GRANORLIN DODDRLING District  
County  
Well No. 4, (Formerly H. C. R. CO. #149)  
J. H. CUNNINGHAM Part

AFFIDAVIT TO BE MADE BY OPERATOR, WELL OWNER OR BY SOMEONE KNOWN TO HIM AND BELIEVED TO BE TRULY AND FAITHFULLY INFORMED AS TO THE FACTS CONCERNING THE TIME AND MANNER OF PLUGGING AND FILLING THE WELL.

**AFFIDAVIT**

STATE OF WEST VIRGINIA,  
 County of HARRIS ss:

BURT MITCHELL and ALPHA P. R. SR  
 being first duly sworn according to law depose and say that they are experienced in the work of plugging  
 and filling oil and gas wells and were employed by RAAD & MOSS well operator,  
 and participated in the work of plugging and filling the above well, that said work was commenced on the  
 day of OCT. 1935, and that the well was plugged and filled in  
 the following manner:

~~Manner in which said well was plugged:~~ Removed 2" tubing and filled hole with clay  
2840'-10' below where 5 3/16 casing was set and filled hole with clay  
cement and removed 5 3/16 casing, continued filling to 2780' placed  
plug. Installed bridge at 2310'-20" below big injun sand and  
 filled hole with clay to 2181'-10" below where 6 5/8 was set and  
 placed plug, removed 6 5/8 casing. Installed bridge at 2133'-20"  
 below second salt sand then filled hole with clay to 1660'-20" above  
 first salt sand and placed wood plug and cement. Installed  
Manner in which coal was plugged: bridge at 1065'-20" above little dunkard  
 sand and filled hole with mud clay to 774'30" below Pittsburgh Coal  
 Seam, filled with cement to 718'-20" above pittsburgh coal seam,  
 continued filling to the surface with clay.

10" CASING IS CEMENTED IN THE HOLE. COULD NOT REMOVE.  
DEPTH 335'.

Description of monument: Concrete Monument to be erected over the hole  
When Rig Removed.

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 5, ARTICLE 5, CHAPTER 24 OF THE CODE)  
 and that the work of plugging and filling said well was completed on the day of NOV.  
19 35.

And further deponents swear not.

*Burt Mitchell*

**WEST VIRGINIA DEPARTMENT OF MINES**

**OIL AND GAS DIVISION**

**PRELIMINARY DATA SHEET NO. 1**

File No. Do 1 138 A Well No. 4  
J. H. Raad & W. Moss Company of W. Va. (Formerly H. C. R. CO. # 149)  
containing oil on the Granorlin Part

The surface of the above tract is owned in fee by Mr. E. Cunningham County, West Virginia  
 of W. Va. address, and the mineral rights are owned by

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit  
 No. 100 issued by the West Virginia Department of Mines, Oil and Gas Division

Elevation of surface at top of well 100 feet  
 The number of feet of the different sized casings used in the well.

	feet	dia.	wt.	ft.	dia.	wt.	ft.	dia.	wt.
<u>288</u>	<u>10</u>	<u>3 1/2</u>	<u>111</u>	<u>111</u>	<u>3 1/2</u>	<u>111</u>	<u>111</u>	<u>3 1/2</u>	<u>111</u>
<u>217</u>	<u>10</u>	<u>3 1/2</u>	<u>111</u>	<u>111</u>	<u>3 1/2</u>	<u>111</u>	<u>111</u>	<u>3 1/2</u>	<u>111</u>
<u>200</u>	<u>10</u>	<u>3 1/2</u>	<u>111</u>	<u>111</u>	<u>3 1/2</u>	<u>111</u>	<u>111</u>	<u>3 1/2</u>	<u>111</u>

Coal was encountered at 340 feet, thick 20 inches, and at 720  
feet; thickness 77 inches; and at feet; thickness inches.

Lines were used as follows: (Give details) Top of line 274 below 271.2 with a shoe  
on bottom and a pocket on the top.