

Latitude 39°15'00"

7.5'
+

00, 00, 00"

Longitude

Topo Location

7.5' Loc. 0.75S 15' Loc. 0.75S
0.47W (calc.) 0.47W

Company W. L. Wolfe # C-755

Farm W. L. Wolfe #7

15' Quad Vadis NW
(sec.)

7.5' Quad New Milton

District New Milton

WELL LOCATION PLAT

County 017 Permit 30410

COAL OPERATOR OR OWNER
 ADDRESS
 COAL OPERATOR OR OWNER
 ADDRESS
 LEASE OR PROPERTY OWNER
 ADDRESS
 NAME OF WELL OPERATOR
 COMPLETE ADDRESS
 WELL AND LOCATION
 DISTRICT
 COUNTY
 FARM
 Well No. 1
 W. E. Wolfe

STATE INSPECTOR SUPERVISING PLUGGING State Inspector was not present.
 AFFIDAVIT
 STATE OF WEST VIRGINIA
 County of Harrison
 I, Harry Mitchell and Dayl Jun being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Read Supply Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 17th day of August, 1942, and that the well was plugged and filled in the following manner:

DEPTH OR ZONE RECORDED	DESCRIPTION	DATE	PLUGGING MATERIAL	PLUGS USED	CAUSING
Top of Big Lime	Clay	2053	1925	Wood cement	2" Tbg.
Sealing Big Injun	Clay	1975	1926	Wood & cement	1768'
Bottom of Salt Sand	Clay	1926	1913	Wood & cement	of 6-5/8 - 187
20' above Salt Sand	Clay	1700	1355	sk cement	
Sealing Salt Sand	Plug	1855	1342	Wood & cement	
Bottom of Dunkard	Clay	1150	1120	sk cement	1045'
Sealing Dunkard	Clay	900	900	sk cement	cf 34
Sealing W. Dunkard	Cement	900	900		
30' below Fresh Coal	Clay	605	550		
20' above "	Cemented	605	550		
Casing feet of 10"	Clay	550	550		
	Plug	550	550		
	Clay	550	550		

and that the work of plugging and filling said well was completed on the 17th day of August, 1942.
 Harry Mitchell
 Dayl Jun
 And further deponents saith not

Company Read Supply Company
 Address Salem, West Virginia
 Farm W. E. Wolfe
 Location (waters)
 Well No. 1 Formerly H.C. & R. Co No. 755
 District New Milton County Doddridge
 The surface of tract is owned in fee by L. L. Snider
 Address
 Mineral rights are owned by L. L. Snider
 Address
 Drilling commenced 3-24-22
 Drilling completed 5-6-22
 Date shot 1922-24-25 & 35
 Open Flow 10ths Water in / 10ths Merc. in
 Volume Cu Ft
 Rock Pressure lbs.
 Oil bbls. per 24 hrs
 Fresh water feet
 Salt water feet
 Kind of Packer Steel casing shoe on f bottom.
 Size of 8 1/2 & 6-5/8
 Depth set 1097
 Perf. bottom 6-5/8-1940
 Perf. top 14ft. in well.
 Perf. bottom
 Perf. top
 Used in Drilling
 Casing and Tubing
 Left in Well
 Packer
 Size
 Liners Used
 2" Tbg.
 CASING CEMENTED
 SIZE
 PITTSBURGH COAL
 COAL WAS ENCOUNTERED AT
 FEET FEET FEET
 INCHES INCHES INCHES

Formation	Color	Hard or Soft	Top	Bottom	Perf. Gas or Water	Depth Perforated	Remarks
Native Coal			22	24			
Pittsburgh Coal			570	575			
Big Dunkard			1092	1169			
Gas Sand			1280	1345			
First Salt			1375	1467			
Second Salt			1488	1660			
Third Salt			1626	1700			
Little Lime			1895	1915			
Pencil Cave			1915	1926			
Big Lime			1926				
Big Injun			1965				
Oil & Gas			1965	1971	Gas 10/10 W. 2" OWS.		
Hard			1971	1995			
Soft			1995	2002	Gas	2006	
Hard			2002	2003	Oil	2003	
Total Depth			2023'		Oil	2010	
					Gas	2017	