

70184

Central District, Doddridge County, W. Va.

By.....

Cairo Drilling Co., Contractor.

Date of completion, etc., not given. (Probably Dec. 9, 1913, when minute pressure taken).

8 1/2" casing, 400' (pulled out); 6 1/2", 1500'; 2" tubing, 1915'.

Rock pressure, Dec. 29, 1913, 410 lbs.

Minute pressure Dec. 9, 1913. 1/2 min., 300 lbs.; 1 min., 360 lbs.;  
 2 min., 375 lbs.; 3 min., 380 lbs.; 4 min., 380 lbs., 5 min.,  
 380 lbs.; 6 min., 380 lbs.; 7 min., 380 lbs.; 8 min., 385 lbs.;  
 9 min., 385 lbs.; 10 min., 390 lbs.

Second drilling: Bottom of perforation, 1876'; top of perforation,  
 1854'; bottom of packer, 1778'; top of packer, 1774'; 2nd drill-  
 ing, tubed with 2" tubing.

Record in Eastern Petroleum Co. Well Record book of Clifton Oil & Gas Co.

Pulled and plugged June 19, 1926.

	Top.	Bottom.
First Salt Sand	1070	- 1150
Second Salt Sand	1270	- 1350
3rd Salt Sand	1360	- 1405
Gas Sand	1500	- 1560
Little Line	1700	- 1725
Big Line (first gas, 1800-1807')	1725	- 1805
Total depth (first drilling)		1807
DEEPENED:		
Break	1335	- 1342
Squaw? Sand (gas, 1858-1861') (40/10 W. 2" tubing)	1842	- 1869
Total depth (second drilling)		1915