

WR-35
Rev (5-01)

DATE: 12-20-06
API #: 47-021-03836F

State of West Virginia
Department of Environmental Protection
Office of Oil and Gas

Well Operator's Report of Well Work

Farm name: Rosa Messenger Heirs

Operator Well No.: A. Messenger No. 1-A

LOCATION: Elevation: 1220'

Quadrangle: Gilmer 7.5

District: Glenville
Latitude: 9,600' Feet South of
Longitude 12,850' Feet West of

County: Gilmer
39 Deg. 00 Min. 00 Sec.
80 Deg. 40 Min. 00 Sec.

Company:

Company:	Casing & Tubing	Used in drilling	Left in well	Cement fill up Cu. Ft.
Continental Petroleum, LLC				
Address:				
Sand Fork Rd. Box 1 Sand Fork, WV 26430				
Agent: Robert R. Jones				
Inspector: Steve Mosser				
Date Permit Issued: 10-02-2006				
Date Well Work Commenced: 11-27-06				
Date Well Work Completed: 12-01-06				
Verbal Plugging:				
Date Permission granted on:				
Rotary Cable Rig				
Total Depth (feet):				
Fresh Water Depth (ft.): N/A				
Salt Water Depth (ft.): N/A				
Is coal being mined in area (N/Y)? N				
Coal Depths (ft.):				

OPEN FLOW DATA

Producing formation Riley Pay zone depth (ft) _____ ft.
 Gas: Initial open show _____ MCF/d Oil: Initial open flow _____ Bbl/d
 Final open flow 300 MCF/d Final open flow _____ Bbl/d
 Time of open flow between initial and final tests 8 Hours
 Static rock Pressure 450# psig (surface pressure) after 24 Hours

Second producing formation _____ Pay zone depth (ft) _____ ft.
 Gas: Initial open flow _____ MCF/d Oil: Initial open flow _____ Bbl/d
 Final open flow _____ MCF/d Final open flow _____ Bbl/d
 Time of open flow between initial and final tests _____ Hours
 Static rock Pressure _____ psig (surface pressure) after _____ Hours

* = commingled zones

NOTE: ON BACK OF THIS FORM PUT THE FOLLOWING: 1). DETAILS OF PERFORATED INTERVALS, FRACTURING OR STIMULATING, PHYSICAL CHANGE, ETC. 2). THE WELL LOG WHICH IS A SYSTEMATIC DETAILED GEOLOGICAL RECORD OF ALL FORMATIONS,

Signed:

By: ROBERT R. JONES II
Date: 12-20-06

Messenger No.1-A
47-021-03836F

Riley

Set plug 3518

4 perforations at 3574 to 3578

Squeezed 80 sks 50/50 pozz

Cement top 3190

Fractured Riley 12-01-06

Perforations 17 holes 3464-3468

30 sks sand

1579 Avg. Pressure

700 gal 15% acid

RECEIVED
Office of Oil & Gas

JUN 18 2012

WV Department of
Environmental Protection