


Latitude 38° 55' 00"



G.700  
O.23W

Longitude 80° 37' 30"

Topo Location

7.5' Loc. \_\_\_\_\_ 15' Loc. \_\_\_\_\_  
\_\_\_\_\_ (calc.) \_\_\_\_\_

Company HNG Co.

Farm Peter Farrell #5976

15' Quad \_\_\_\_\_  
(sec.)

7.5' Quad Gilmer

District Glennville

WELL LOCATION PLAT

County 021 Permit 30005

AFFIDAVIT IN TRIPPLICATE AND TIME AND MANNER OF PLUGGING AND FILLING WELL

REGULATED BY SECTION 8, CHAPTER 26, ACT OF 1929

WEST VIRGINIA DEPARTMENT OF MINES OIL AND GAS SECTION

Not in Coal area.

Hope Natural Gas Company

COAL OPERATOR

425 WEST MAIN Street

Clarksburg, W. Va.

COMPLETE ADDRESS

ADDRESS

COAL OPERATOR

WELL AND LOCATION

Glenville District

Gilmer County

ADDRESS

COAL OPERATOR

Well No. 5976

ADDRESS

Peter Farrell Farm

AFFIDAVIT TO BE MADE IN TRIPPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT. ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA,

COUNTY OF Lewis

Oil-5-A

being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Hope Natural Gas Company, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the

26th day of December, 1929, and that the well was plugged and filled in the following manner:

Manner in which said well was plugged: Total depth 2517. Filled solid with clay to 2444 and drove 6 5/8 M. & F. wood plug and cemented. Filled up solid with clay to 2241 and bridged with 3 bags of cement. Filled up solid with clay to 2040. Filled with stone to 2022 and drove 6 5/8 lead plug. Put 3 bags cement on lead plug. Well was shut off 7 days before 6 5/8 casing was pulled. Filled solid with clay to 1990. Put in 3 bags of cement to shut off gas. Filled up with clay to 1934. Put in 3 bags cement at 1934. Filled up with clay to 1748 and drove 8 1/2 wood plug. Put 4 bags cement on 8 1/2 wood plug. Filled solid with clay to 890 and pulled 8 1/2 casing. Filled solid with clay to 200 and pulled 10" casing. Filled solid with clay to top. All gas shut off before pulling casing.

2/18 7/18

No coal.

Description of monument: Concrete block 5 feet long, 8" square, with 3" hole extending through the center from end to end. Extends 30" above and 30" below the surface. Inscription: "H. N. G. Co. No. 5976"

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, OIL AND GAS ACT OF 1929.) and that the work of plugging and filling said well was completed on the 20th day of February

1929 And further deponents saith not.

MAR 3 1930

Ross E. Menold