

Latitude 38° 45' 00"

Longitude 80° 57' 30"



Corrected loc.
5/31/94 B.J.M.

1.87s₂

1.01W

Topo Location

| | | | |
|-----------|--------------|----------|--------------|
| 7.5' Loc. | <u>1.87s</u> | 15' Loc. | <u>1.87s</u> |
| | <u>1.01W</u> | (calc.) | <u>3.26W</u> |

Company South Penn Oil Co.

Farm W. 6 Bennett #5

15' Quad Gansaway (NW)
(sec.)

7.5' Quad Rosedale

District Center

WELL LOCATION PLAT

County 021 Permit 30027

Washington District, ~~Braxton~~ ^{Edmon} County, and Center District, Gilmer Co., W. Va.
South Penn Oil Co.

On 83.6 acres, surface owned by D. C. Mullens, Rosedale, W. Va.,
and mineral rights by Hunter M. Bennett, Weston, W. Va., and
Alice B. Bennett et al. (address not given).

Elevation, 1071'.

8½" casing, 345'; 6-5/8", 880'.

Coal was encountered at 1625-1645'. (?)

Abandonment reported to Dept. of Mines, Sept. 15, 1931.

Well was shot (depth not given).

| | Top. | Bottom. |
|-------------------------------|--------|---------|
| Sand | 150 - | 250 |
| Sand | 300 - | 345 |
| Rock | 345 - | 350 |
| Sand | 645 - | 855 |
| Sand | 880 - | 980 |
| Sand | 1180 - | 1280 |
| Slate and shells | 1280 - | 1380 |
| Gas Sand (oil and gas, 1485') | 1465 - | 1500 |
| Lime and shells | 1500 - | 1535 |
| Slate | 1535 - | 1625 |
| Coal (?) | 1625 - | 1645 |
| Salt Sand | 1665 - | 1685 |
| Slate and shells, to bottom | 1685 - | 1778 |

Well No. 5 - Center and Washington Districts, Braxton and Gilmer Counties, West Virginia.

SOUTH PENN OIL COMPANY
 P. O. Drawer 1255
 Pittsburgh, Pa.

Company
 Address *Well-27-A*

COMPLETION DATA SHEET
 NO. 2
 FORMATION RECORD

| Name | Color | Character | Oil, Gas or Water | Top | Bottom | Thickness | Total Depth | Remarks |
|----------------|-------|-----------|-------------------|------|--------|-----------|-------------|---------|
| Sand | | | | 150 | 250 | | | |
| Sand | | | | 300 | 345 | | | |
| Rock | | | | 345 | 350 | | | |
| Sand | | | | 645 | 855 | | | |
| Sand | | | | 880 | 980 | | | |
| Sand | | | | 1180 | 1280 | | | |
| Slate & Shells | | | | 1280 | 1380 | | | |
| Gas Sand | | | Oil & Gas | 1465 | 1500 | | | |
| Lime & Shells | | | | 1500 | 1535 | | | |
| Slate | | | | 1535 | 1625 | | | |
| Coal | | | | 1625 | 1645 | | | |
| Salt Sand | | | | 1665 | 1685 | | | |
| Slate & Shells | | | | 1685 | 1778 | | | |
| Total Depth | | | | | | | 1778 | |

WEST VIRGINIA DEPARTMENT OF MINES

Oil and Gas Section

bl 27-A

PRELIMINARY DATA SHEET NO. 1

File No.

Well No. 5

South Penn Oil

Company, of P. O. Drawer 1255, Pittsburgh, Pa.

on the W. G. Bennett

Farm

containing 83.6 acres. Location

Washington and Center District, in Braxton and Gilmer County, West Virginia.

The surface of the above tract is owned in fee by D. C. Mullens

of Rosedale, W. Va.

address, and the mineral rights are owned by

Hunter M. Bennett

Weston, W. Va.

Alice B. Bennett, et al.

of ?

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit No. issued by the West Virginia Department of Mines, Oil and Gas Section.

19.

Elevation of surface at top of well,

1071'

Spirit Barometric.

The number of feet of the different sized casings used in the well.

| | | | | | | | |
|-------------------------|-----------|-------------------------|------------|-----------------|---------|--------------|----------------|
| | feet | | size, csg. | | feet | size, csg. | Wood conductor |
| 345 | feet | 8 1/2" | size, csg. | | feet | size, csg. | |
| 880 | feet | 6 5/8" | size, csg. | | feet | size, csg. | |
| | feet | | size, csg. | | feet | size, csg. | |
| | | packer of | | | | size, set at | |
| | | packer of | | | | size, set at | |
| | | in casing perforated at | | | feet to | | feet. |
| | | in casing perforated at | | | feet to | | feet. |
| Coal was encountered at | 1625-1645 | feet; thickness | 240 | inches, and at | | | |
| feet; thickness | | inches; and at | | feet; thickness | | inches. | |

Liners were used as follows: (Give details)

AFFIDAVIT IN TRIPPLICATE TO TIME AND MANNER OF PLUGGING AND FILLING WELL

(REQUIRED BY SECTION 9, ARTICLE 4, CHAPTER 22 OF THE CODE)

WEST VIRGINIA DEPARTMENT OF MINES OIL AND GAS DIVISION

Hunter M. Bennett
COAL OPERATOR OR OWNER

Reston, W. Va.
ADDRESS

COAL OPERATOR OR OWNER

ADDRESS

COAL OPERATOR OR OWNER

ADDRESS

SOUTH PENN OIL COMPANY

NAME OF OPERATOR

P. O. Drawer 125, Pittsburgh, Pa.

COMPLETE ADDRESS

NOVEMBER 1931

WELL NO.

Center

Gilmer

Well No. 5

W. G. ...

AFFIDAVIT TO BE MADE IN TRIPPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO THE OPERATOR IN THE THIRD COPY (AND EXTRA COPIES IF REQUIRED); TO BE MAILED TO EACH COAL OPERATOR ABOVE AND TO THE DEPARTMENT.

AFFIDAVIT

STATE OF WEST VIRGINIA,

COUNTY OF Roane

ss:

John Starkey

being first duly sworn according to law depose and say that they are experienced in the work of plugging

and filling oil and gas wells and were employed by SOUTH PENN OIL COMPANY and participated in the work of plugging and filling the above well, that said well was plugged and filled

on the 23rd day of September, 1931, and that the well was plugged and filled in the following manner:

Manner in which sand was plugged: Total depth of well 1665'; set wood plug 6 5/8" to 162'; lead wool from 1662' to 1660'; set cement 1605'; filled up with non-porous sediment from 1605' to 1442'; set 6 5/8" x 3' wood plug from 1445' to 1442'; set 1442' to 1432'; set bridge at 1280'; filled up with sediment to 1000'; pulled 6 5/8" casing; set 8 1/2" x 355' o 352'; filled up with non-porous sediment from 352' to 350'. Pull 8 1/2" casing after 8 1/2" wood plug was set.

Manner in which coal was plugged:

Description of monument: Erected marker as described in Rule 20 of 1931 Regulations. All done in workman-like manner.

THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION 9, ARTICLE 4, CHAPTER 22 OF THE CODE.

546
8.2.113