





Troy District, Gilmer County, W. Va. - 75-A  
 Hope Cons. & Ref. Co., 445 W. Main St., Clarksburg, W. Va.  
 On 270 acres, surface owned by B. S. Messenger, Baldwin, W. Va.;  
 coal underlying part of tract was sold to N. T. Arnold,  
 address unknown.

Elevation, 841' L.

6-5/8" casing, 1523'; 2" tubing, 1687'.

Starts "below coal".

Abandonment reported to Dept. of Mines June 11, 1935.

Well was not shot.

No record of water.

Gas well; exhausted to extent that no longer commercially productive.

	Top.	Bottom.
Red rock cave	40	90
First Cow Run Sand	220	250
Second Cow Run Sand	300	392
First Salt Sand	1005	1083
Second Salt Sand (show gas, 1184')	1112	1278
Third Salt Sand	1295	1360
Maxton Sand	1418	1438
Little Lime	1461	1493
Pencil Cave	1493	1498
Big Lime (show gas, 1556')	1498	1590
Big Injun Sand (gas, 1604-1637')	1590	1645
Total depth		1687

GIL - 75-A

Name \_\_\_\_\_  
Date \_\_\_\_\_

Red Rock Cave-----			
First Cow Run Sand-----	235	235	10'
Second Cow Run Sand-----	300	392	92'
First Salt Sand-----	1005	1083	78'
Second Salt Sand-----	1112	1278	166'
Third Salt Sand-----	1295	1360	65'
Maxon Sand-----	1418	1435	17'
Little Lime-----	1461	1493	32'
Pencil Cave-----	1493	1498	5'
Big Lime-----	1498	1590	92'
Big Injun Sand-----	1590	1645	55'
	Gas-1604-1637		1667

~~shot~~ Well was not shot at **Not shot** feet well was shot at \_\_\_\_\_ feet.

~~made~~ Fresh water at **No record** feet ~~made~~ water at **Not recorded** feet.

~~stop~~ producing Well was \_\_\_\_\_ hole **Exhausted to extent that no longer commercially productive.**

June 11th, 1935.  
Date

Applied Hope Construction & Refining Company  
By \_\_\_\_\_

NOTE: All bottom formations must be noted as indicated above and all key rocks and oil and gas sands must be recorded under

WEST VIRGINIA DEPARTMENT OF MINES

OIL AND GAS DIVISION

PRELIMINARY DATA SHEET NO. 1

File No.

Well No. **A-100**

**Hope Construction & Refining**

Company of

**445 West Main St.**

**Clarksburg, W. Va.,**

on the

**Messenger Heirs**

Parm

containing **270**

acres, located

**Troy**

District, in

**Gilmer**

County, West Virginia

The surface of the above tract is owned in fee by **B. S. Messenger**

of **Baldwin, W. Va.,**

address, and the mineral rights are owned by

**Coal underlying part of tract was sold to N. T. Arnold,**

**Address; Unknown**

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit

No.

--

issued by the West Virginia Department of Mines, Oil and Gas Division

--

193

Elevation of surface at top of well.

**841**

Spirit

The number of feet of the different sized casings used in the well.

**1523**

feet

**6-5/8"**

size, casing

feet

size. Wood conductor

size, casing

**1687**

feet

size, casing

size, casing

feet

size, casing

feet

size, casing

feet

size, casing

packer of

size, set at

packer of

size, set at

, in casing perforated at

feet to

feet

, in casing perforated at

feet to

feet

Coal was encountered at

**Below Coal**

feet, thick near

inches, and at

feet, thickness

inches; and at

feet, thickness

inches

Liners were used as follows (Give details)

June 11th, 1935.

AFFIDAVIT IN TRIPPLICATE TO TIME AND MANNER OF PLUGGING AND FILLING WELL

(REQUIRED BY SECTION 9, ARTICLE 4, CHAPTER 22 OF THE CODE)

WEST VIRGINIA DEPARTMENT OF MINES OIL AND GAS DIVISION

Well does not penetrate coal.  
COAL OPERATOR OR OWNER

Hope Construction & Refining Company  
NAME OF WELL OPERATOR

Coal Owner; ADDRESS  
Unknown.  
COAL OPERATOR OR OWNER

Clarksburg, W. Va.,  
COMPLETE ADDRESS  
July 16th, 1935. 19

ADDRESS  
COAL OPERATOR OR OWNER

WELL AND LOCATION  
Troy District  
Oliver County

ADDRESS  
COAL OPERATOR OR OWNER

Well No. A-100  
Messenger Mine Farm

AFFIDAVIT TO BE MADE IN TRIPPLICATE, ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE DELIVERED BY THE WELL OPERATOR AND THE THIRD COPY LEFT EITHER DEPOSITED OR REGISTERED TO BE DELIVERED TO THE COUNTY CLERK OF THE COUNTY WHERE LOCATED.

AFFIDAVIT

STATE OF WEST VIRGINIA,

COUNTY OF \_\_\_\_\_

JCH. L. AMAS

and WALTER A. WATTS

being first duly sworn according to law depose and say that they are experienced in the work of plugging

and filling oil and gas wells and were employed by HOPE CONSTRUCTION & REFINING CO. well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the

\_\_\_\_\_ day of JUNE 1935 and that the well was plugged and filled in the following manner:

Manner in which sand was plugged: Drive Lead Plug size 6-3/8" at 950 Ft.

Permanent bridge installed at 1750 Ft. and filled with sand to 1800 Ft.

and Cement Plug set at 1010 Ft. Permanent bridge set at 750 Ft. and filled with sand to surface of ground.

Manner in which coal was plugged: as usual.

Description of monument: Concrete monument 5 ft. in length set 2 1/2 ft. in ground extending 2 1/2 ft. above ground, and inscribed "Hope Well # A-100"

THE ABOVE DESCRIPTIONS MUST BE IN ACCORDANCE WITH THE PROVISIONS OF SECTION 9, ARTICLE 4, CHAPTER 22 OF THE CODE.

and that the work of plugging and filling said well was completed on the 16th day of July 1935