


Latitude 39° 05' 00"

Longitude 80° 05' 08"



2.300
1.370

Topo Location

7.5' Loc. _____ 15' Loc. _____
_____ (calc.) _____

Company Hope Const. & Red

Farm Fisher Heirs # 3648

15' Quad _____
(sec.)

7.5' Quad Auburn

District Troy

WELL LOCATION PLAT

County 021 Permit 30104



File-104A

Location

Company Hope Natural Gas Co.
 Address Clarksburg W. Va.
 Farm Emily Fisher Mrs.

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL RECORD

Oil or Gas Well Oil

Permit No. _____

Company **Hope Construction & Refining Company**
 Address **Clarksburg, W. Va.,**
 Farm **Fisher Heirs** Acres **95**
 Location (waters) **Upper Big Run**
 Well No. **3648** Elev. **1156**
 District **Troy** County **Gilmer**

Casing and Tubing

Used in Drilling

Left in Well

Packers

The surface of tract is owned in fee by _____

Mineral rights are owned by _____

Drilling commenced **6-11-1918**

Drilling completed **6-1-1919**

Date shot **8-3-1918** Depth of shot **In Cantz**

Open Flow 10ths Water in _____ Inch
 10ths Merc. in _____ Inch

Volume _____ Cu. Ft.

Rock Pressure _____ lbs. _____ hrs.

Oil ? _____ bbls. 1st 24 hrs.

Fresh water **None recorded** feet

Salt water **None recorded** feet

CASING CEMENTED

Not cemented

COAL WAS ENCOUNTERED AT

No coal

FRESH WATER ENCOUNTERED AT

No fresh water

SIZE

1 1/2"

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

FEET

14

INCHES

14

Formation	Color	Hard or Soft	Top	Bottom	Oil Gas or Water	Depth Found	Remarks
sand			400	420			
slate			958	961			
Little Dunkard			965	975			
Big Dunkard sand			1025	1062			
Gas sand			1165	1200			
First salt sand			1300	1330			
Second salt sand			1340	1395			
Maxon sand			1615	1800			
Little Lime			1892	1920			
Big Lime			1925	2025			
Big Injun sand			2025	2115			
Squaw sand			2145	2250			
Cantz sand			2402	2422			
			Total Depth-----				
			2434				

**AFFIDAVIT - TRIPPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL**
(REVISED BY SECTION 8, ARTICLE 4, CHAPTER 22 OF THE CODE)

**WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION**

well not in coal area. <small>TOTAL OPERATOR OR OWNER</small> ADDRESS <small>TOTAL OPERATOR OR OWNER</small> ADDRESS surface; Scott Mason, Cox's Mill, W. Va., <small>LEASE OR PROPERTY OWNER</small> ADDRESS	Hope Construction & Refining Company <small>NAME OF WELL OPERATOR</small> Clarksburg, W. Va., <small>COMPLETE ADDRESS</small> February 10, 1938 <small>WELL AND LOCATION</small> Troy District Gilmer County Well No. 5648 Fisher Heira Farm
---	---

AFFIDAVIT TO BE MADE IN TRIPPLICATE, ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY, LEASE EXTRACTOR IF REQUIRED, TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA }
 COUNTY OF LEWIS } SS:

ERNEST B. WHITE and BRADMAN W. TITUS
 being first duly sworn according to law depose and say that they are experienced in the work of plugging
 and filling oil and gas wells and were employed by HOPE CONSTRUCTION & REFINING CO. well operator,
 and participated in the work of plugging and filling the above well, that said work was commenced on the
17 day of JANUARY, 1938, and that the well was plugged and filled in
 the following manner:

Manner in which sand was plugged: FILLED WITH CLAY TO 2382 Ft. and set Cement Plug.
Bridge installed at 214 Ft. and filled with clay to 2005, Set Lead Plug at 2005.
Bridge installed at 142 and filled with clay to 1280 Ft. and set Cement Plug.
Bridge installed at 105 and Cement Plug set, filled with clay to 945 ft. and set
Wood plug at 945 ft. Bridged at 410 and filled solid with clay to surface.
 Manner in which coal was plugged:

Description of monument: Monument erected over hole showing Company name and
Well number, made of concrete set 2 1/2 ft in ground, and 2 1/2 ft above ground.

(THE ABOVE DESCRIPTION MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 4, CHAPTER 22 OF THE CODE.)
 and that the work of plugging and filling said well was completed on the 11th day of February
 1938.

And further deponents say not.

E. B. White
Bradman W. Titus