

Latitude 39 00

3.52 S
2.97 W

Norris Hrs.

☀ No 7467

Clarence Stump

A.M. Springston

Clarence Stump
&
R.H. Stalnaker

No 7474

R.H. Stalnaker

S.A. Vanoy

A.M. Springston

C.C. Kelley

3.55 S
3.00 W

New Location
Drill Deeper
Abandonment

Company Pittsburgh & W.Va. Gas Co.
 Address Clarksburg W.Va.
 Farm A.M. Springston
 Tract _____ Acres 41 Lease No. 16372
 Well (Farm) No. One Serial No. 7474
 Elevation (Spirit Level) 1103
 Quadrangle Glenville N.W. 13
 County Gilmer District DeKalb
 Engineer James D. Jeffers
 Engineer's Registration No. 1084
 File No. _____ Drawing No. _____
 Date 11-7-35 Scale 1"=300'

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION
CHARLESTON

WELL LOCATION MAP
FILE NO. GIL-173-A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
- Denotes one inch spaces on border line of original tracing.

Dekalb District, Gilmer County, W. Va.

By Pittsburgh & W. Va. Gas Co., Clarksburg, W. Va.

Abandoned under permit Gil-173-A.

On 41 acres; Glenville N/W 1-3.

Elevation, 1103' V. A.

Surface owned by R. B. Vannoy, Belpre, Ohio, and minerals by A. H.

Jackson, Big Springs, W. Va.

Drilling commenced January 12, 1926(?); completed, February 6, 1926 (?).

10" casing, 112'; 8 $\frac{1}{4}$ ", 940'; 6 $\frac{5}{8}$ ", 1940'; all left in.

Coal was encountered at 810-815'.

Gas well. Abandonment reported to Dept. of Mines Feb. 25, 1942.

Record to RCT from Mrs. Griffith May 22, 1942. Old File No. 325.

	Top.	Bottom.
Clay, red, soft	0	10
Sand, light, hard	10	50
Red rock, soft	50	65
Lime, blue, hard	65	75
Sand, yellow, soft	75	85
Sand, light, soft	85	110
Red rock, soft	110	150
Sand, light, hard	150	200
Slate and shells, light, hard and soft	200	220
Red rock, soft	220	260
Slate and shells, soft and hard	260	270
Sand, light, soft and hard	270	310
Slate and shells, light, soft and hard	310	415
Sand, light, soft	415	433
Red rock, soft	433	440
Slate and shells, light, soft	440	470
Red rock, soft	470	495
Slate and shells, light, soft and hard	495	585
Red rock, soft	585	630
Slate and shells, light, soft	630	640
Red mud, soft	640	660
Slate and shells, light, hard and soft	660	690
Lime, light, hard	690	775
Slate and shells, light, hard and soft	775	810
Coal, dark	810	815
Slate and shells, light, hard and soft	815	850
Sand, light, hard	850	862
Slate, light, soft	862	875
Lime, light, hard	875	910
Slate, dark, soft	910	935
Little Dunkard Sand, light, hard	935	950
Slate, light, soft	950	1085
Big Dunkard Sand, light, close	1085	1185
Slate and shells, light, hard and soft	1185	1200
Gas Sand, light, hard and soft	1200	1340
Slate and shells, dark, hard and soft	1340	1380
1st Salt Sand, light, soft	1380	1415
Slate and shells, dark, soft	1415	1455
2nd Salt Sand, light, soft	1455	1475
Slate, dark, hard and soft	1475	1535
3rd Salt Sand, light, hard	1535	1635
Slate, dark, soft	1635	1800
Maxton Sand, light, hard (gas and water, 1854')	1800	1877

(OVER)

A. M. SPRINGSTON NO. 1 (7474) WELL (Continued).

	Top.	Bottom.
Slate, light, soft	1877	- 1891
Little Lime, dark, hard	1891	- 1905
Slate, light, soft	1905	- 1908
Sand, light, hard	1908	- 1912
Slate, light, soft	1912	- 1916
Blue Monday Sand, light, hard	1916	- 1933
Slate, light, soft	1933	- 1935
Big Lime, gray, hard	1935	- 1984
Big Injun Sand (gas, 1986-1994)	1984	- 2085
Slate, light, soft	2085	- 2100
Sand, blue, hard	2100	- 2107
Slate, light, soft	2107	- 2175
Total depth		2175

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

325

WELL RECORD

Permit No. 73-A

Oil or Gas Well GAS
(KIND)


Company Pittsburgh & West Va Gas Company.
Address Clarksburg, West Va.,
Farm A. M. Springston Acres 41
Location (waters) Glenville N/W. 1-3
Well No. 7474 Elev. 1103'
District Beulah County Glimer
The surface of tract is owned in fee by R. H. Vannoy
Address Belpre, Ohio.
Mineral rights are owned by A. H. Jackson
Address Hig Springs, W. Va.,
Drilling commenced January 12, 1926
Drilling completed February 6, 1926
Date Shot From To
With

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10	112'	112'	Size of
8 1/4	940'	940'	
6 5/8	1940'	1940'	Depth set
5 3/16			
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

Open Flow /10ths Water in _____ Inch
/10ths Merc. in _____ Inch
Volume _____ Cu. Ft.
Rock Pressure _____ lbs. _____ hrs.
Oil _____ bbls., 1st 24 hrs.
Fresh water _____ feet _____ feet
Salt water _____ feet _____ feet

CASING CEMENTED _____ SIZE _____ No. Ft. _____ Date _____
COAL WAS ENCOUNTERED AT 810 FEET 60 INCHES
_____ FEET _____ INCHES _____ FEET _____ INCHES
_____ FEET _____ INCHES _____ FEET _____ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Clay	Red	Soft	0	10			
Sand	Light	Hard	10	50			
Red Rock	Red	Soft	50	65			
Lime	Blue	Hard	65	75			
Sand	Yellow	Soft	75	85			
"	Lite	"	85	110			
Red Rock	Red	"	110	150			
Sand	Lite	Hard	150	200			
Slate&Shells	"	Hard&Soft	200	220			
Red Rock	Red	Soft	220	260			
Slate&Shells	"	" Hard	260	270			
Sand	Light	" "	270	310			
Slate&Shells	"	" "	310	415			
Sand	"	" "	415	433			
Red Rock	Red	"	433	440			
Slate&Shells	Light	"	440	470			
Red Rock	Red	"	470	495			
Slate&Shells	Light	Soft&Hard	495	585			
Red Rock	Red	Soft	585	630			
Slate&Shells	Light	"	630	640			
Red Mud	Red	"	640	660			
Slate&Shells	Light	Hard&Soft	660	690			
Lime	"	"	690	775			
Slate&Shells	"	" & Soft	775	810			
Coal	Dark		810	815			
Slate&Shells	Light	Hard&Soft	815	850			
Sand	"	Hard	850	862			
Slate	"	Soft	862	875			
Lime	"	Hard	875	910			
Slate	Dark	Soft	910	935			
L. Dunkard	Light	Hard	935	950			
Slate	"	Soft	950	1085			
Hig Dunkard	"	Close	1085	1185			
Slate&Shells	"	Hard&Soft	1185	1200			
Gas Sand	"	" "	1200	1340			
Slate&Shells	Dark	" "	1340	1380			
1st. Salt Sand	Light	Soft	1380	1415			
Slate&Shells	Dark	"	1415	1455			
2nd. Salt Sand	Light	"	1455	1475			
Slate	Dark	Hard&Soft	1475	1535			
3rd. Salt Sand	Light	Hard	1535	1635			
Slate	Dark	Soft	1635	1800			
Maxon Sand	Light	Hard	1800	1877	Gas & Water	1836'	



MAY 22 1942

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Slate	Light	Soft	1877	1891			
ls lime	Dark	Hard	1891	1905			
Slate	Light	Soft	1905	1908			
Sand	"	Hard	1908	1912			
Slate	"	Soft	1912	1916			
Blue Monday	"	Hard	1916	1933			
Slate	"	Soft	1933	1935			
lime (Big)	Grey	Hard	1935	1984			
Big Injun			1984	2085	Gas	1986-1994'	
Slate	Light	Soft	2085	2100			
Sand	Blue	Hard	2100	2107			
Slate	Light	Soft	2107	2175			
Total Depth				2175			

Date **February 25, 1942**, 194
PITTSBURGH & WEST VA GAS COMPANY.

APPROVED _____, Owner

F. E. Bridgen.

By _____ (Title)

COMPANY

Record of Well No. *7474* Located on *M. Springston* Farm 19
Neckal District *Gilmer* County *W. Va.* State
 Division *K* District No. *13* Drilled under Well Order *193*
 Rig built by *Jacob Craig* Began *Dec 12* 19*25* Completed *Dec 21* 19*25*
 Well drilled by *W. Katterfield* Began *Jan 12* 19*26* Completed *Feb 6* 19*26*
 Depth of Well ~~*747*~~ *2175* feet Size of Hole *6 7/8* Producing *Gas*

Elev: 11036 Cased with REMARKS

AMOUNT	SIZE	KIND
<i>16'</i>	<i>13"</i>	<i>Wood</i>
<i>112'</i>	<i>10"</i>	<i>Casg</i>
<i>940'</i>	<i>8 1/2"</i>	<i>Casg</i>
<i>1940'</i>	<i>6 7/8"</i>	<i>Casg</i>
<i>1995'</i>	<i>3"</i>	<i>Subg</i>

COAL VEINS

FORMATIONS

NAME	TOP	BOTTOM	OIL	GAS	WATER	REMARKS
<i>Gas Sand</i>	<i>1400</i>	<i>1340</i>				
<i>Sand</i>	<i>1380</i>	<i>1470</i>				
<i>2nd Sand</i>	<i>1035</i>					
<i>Major Sand</i>	<i>1500</i>	<i>1877</i>		<i>1804</i>	<i>1804</i>	<i>Shaw</i>
<i>Little Guel</i>	<i>1891</i>					
<i>Big Guel</i>	<i>1937</i>	<i>1984</i>				
<i>Big Impur</i>	<i>1984</i>			<i>1986</i>	<i>1994</i>	<i>No More 6 7/8" Casg</i>

42706

FIRST PRESSURE TEST IN 6 5/8 CASING

REMARKS

30 Sec.	105	lbs.
1 Min.	180	"
2 "	210	"
5 "	280	"
10 "	375	"
20 "	450	"
30 "		"

235/270

Rock Pressure 540 " in 16 hrs 6/8 "

Taken Feb 6 1926

By H. E. Witt

WELL TUBED AND PACKED 2-10th 1926

VIZ:- 94ft to 1995' of 3" tubing
6 1/2 x 3" anchor
3ft to 35 ft anchor

FIRST PRESSURE TEST IN 3" TUBING

REMARKS

30 Sec.		lbs.
1 Min.		"
2 "		"
5 "		"
10 "		"
15 "		"
30 "		"

Rock Pressure 540 " in 24 hrs

Taken July 11th 1926

By H. E. Witt

MATERIAL FOR THIS WELL RECEIVED FROM FOLLOWING SOURCES:

Rig Haus, Lumber & Timber Saw Stumps 7467

A.M. Springston, well No 7474: FORMATIONS

NAME	Top	Bottom	OIL	GAS	WATER	REMARKS
Clay	00	10				
sand	10	50				
Red Rock	50	65				
Lime	65	75				
slate	75	85				
Sand	85	110				
Red Rock	110	150				
Sand	150	200				
slate & shells	200	220				
Red Rock	220	260				
slate & shells	260	270				
sand	270	310				
slate shells	310	415				
sand	415	433				
Red Rock	433	440				
slate & shells	440	470				
Red Rock	470	495				
slate & shells	495	585				
Red Rock	585	650				
slate shells	620	640				
Red Mud	640	660				
slate & shells	660	690				
Lime	690	775				
slate & shells	775	810				
Coal	810	815				
slate & shells	815	850				
Sand	850	862				
slate	862	872				
Lime	872	910				
slate	910	935				
Sand	935	950				
slate	950	1085				
Big Dunkard	1085	1185				
slate shells	1185	1200				
Gas sand	1200	1340				
slate & shells	1340	1380				
1st salt sand	1380	1415				
slate shells	1415	1455				
2nd salt sand	1455	1475				
slate	1475	1535				
3rd salt sand	1535	1635				
slate	1635	1800				
Maxon sand	1800	1877		1854	1854	
slate	1877	1891				
Little lime	1891	1905				
slate	1905	1908				
Sand	1908	1912				
slate	1912	1916				
Blue Monday	1916	1933				
slate	1933	1935				
Big Lime	1935	1984				
Big Injun sand	1984	2085		1986		
slate	2085	2100		1994		
sand	2100	2107				
slate	2107	2175	sd.			