

west virginia department of environmental protection

Office of Oil and Gas 601 57th Street, S.E. Charleston, WV 25304 (304) 926-0450 fax: (304) 926-0452

Austin Caperton, Cabinet Secretary www.dep.wv.gov

Thursday, January 7, 2021 PERMIT MODIFICATION APPROVAL Horizontal 6A / New Drill

HG ENERGY II APPALACHIA, LLC 5260 DUPONT ROAD

PARKERSBURG, WV 26101

Re: Permit Modification Approval for ANTONIO 1206 N-3H

47-033-05980-00-00

Lengthen Surface casing 75'/KK

HG ENERGY II APPALACHIA, LLC

The Office of Oil and Gas has reviewed the attached permit modification for the above referenced permit. The attached modification has been approved and well work may begin. Please be reminded that the oil and gas inspector is to be notified twenty-four (24) hours before permitted well work is commenced.

If there are any questions, please feel free to contact me at (304) 926-0450.

James A. Martin Chief

Operator's Well Number: ANTONIO 1206 N-3H

Farm Name: CHARLES R. & FRANKLIN L. SUTTON

U.S. WELL NUMBER: 47-033-05980-00-00

Horizontal 6A New Drill

Date Modification Issued: 1/7/2021

Promoting a healthy environment.

WW-6B (04/15)

API NO. 47- 033 - 05980

OPERATOR WELL NO. Antonio 1206 N-3H

Well Pad Name: Antonio 1206

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS WELL WORK PERMIT APPLICATION

	HC En	orav II Δnna	lachia I	494519932	Harrison	Grant	West Milford 7.5'
1) Well Operate	or: IIG EII	icigy ii Appa	idoi iid,	Operator ID	County	District	Quadrangle
2) Operator's V	Well Numbe	er: Antonio 12	206 N-3H	Well I	Pad Name: An	tonio 1206	
3) Farm Name/	/Surface Ow	vner: HG Energ	y II Appalach	nia, LLC Public R	Load Access: _	Hackers Cree	ek Rd @ SR 19
4) Elevation, co	urrent grour	nd: <u>1364'</u>	El	levation, propos	ed post-constru	ction: 1350'	
5) Well Type	(a) Gas	x	_ Oil	Uı	nderground Sto	rage	
	Other						
	(b)If Gas	Shallow	<u>X</u>	Deep			-
		Horizontal	<u>X</u>				
6) Existing Pac						17	
				cipated Thicknes Anticipated press		l Pressure(s):	
8) Proposed To	otal Vertical	Depth: 725	2'				
9) Formation a			Marcellus	S			
10) Proposed	Гotal Measu	red Depth:	20,233'				
11) Proposed I	Horizontal L	Leg Length:	12,511'				
12) Approxima	ate Fresh W	ater Strata De	pths:	135', 480', 63	7', 731'		
13) Method to	Determine	Fresh Water I	opuio.	Nearest offset			
14) Approxima			o S/W dept	hs found on WR-35	s's for offset wells,	salt water exped	cted to be below elevation
15) Approxima	ate Coal Sea	am Depths: 6	23', 1010	0' to 1015'			
16) Approxima	ate Depth to	Possible Voi	d (coal m	ine, karst, other): None		
17) Does Prop				ms Yes		No X	
(a) If Yes, pr	ovide Mine	Info: Name	:				RECEIVED Office of Oil and Gas
, , , , , , , , , , , , , , , , , , , ,		Depth	:				NOV 1 6 2020
		Seam					WV Department of
		Owne	r·				Environmental Protection

WW-6B (04/15) API NO. 47- 033 - 05980

OPERATOR WELL NO. Antonio 1206 N-3H
Well Pad Name: Antonio 1206

18)

CASING AND TUBING PROGRAM

TYPE	Size (in)	New or Used	Grade	Weight per ft. (lb/ft)	FOOTAGE: For Drilling (ft)	INTERVALS: Left in Well (ft)	CEMENT: Fill-up (Cu. Ft.)/CTS
Conductor	30"	New	LS	157.5	125'	125'	Drilled In
Fresh Water/Coal	20"	NEW	J-55	94	1175'	1175'	40% excess,CTS
Intermediate 1	13 3/8"	NEW	J-55	68	2200'	2200'	40% excess,CTS
Intermediate 2	9 5/8"	NEW	J-55	40	3000'	3000'	40% excess tail, CTS
Production	5 1/2"	NEW	P-110	23	20233'	20233'	20% excess tail, CTS
Tubing							
Liners							

5DW 11/13/2020

TYPE	Size (in)	Wellbore Diameter (in)	Wall Thickness (in)	Burst Pressure (psi)	Anticipated Max. Internal Pressure (psi)	Cement Type	Cement <u>Yield</u> (cu. ft./k)
Conductor	30"	30"	.500				Drilled In
Fresh Water/Coal	20"	24"	.438	2110	1200	Type 1, Class A	40 % excess yield = 1.29, CTS
Intermediate1	13 3/8"	17 1/2"	.480	3450		Type 1/Class A	Lead 40% axcess, Tail 0% excess
Intermediate 2	9 5/8"	12 1/4"	.395	3950		Type 1/Class A	Lead 40% excess, Tall 0% Excess
Production	5 1/2"	8 1/2"	.415	16240	12500	Type 1/ClassA	20% excess yield = 1.15, tail yield 1.91
Tubing							
Liners							

PACKERS

RECEIVE Office of Oil an
NOV 1 6 2
WV Departme Environmental Pr

API NO. 47- 033 - 05980

OPERATOR WELL NO. Antonio 1206 N-3H

Well Pad Name: Antonio 1206

19) Describe proposed well work, including the drilling and plugging back of any pilot hole:

Drill the vertical depth to the Marcellus at an estimated total vertical depth of approximately 7252 feet. Drill horizontal leg to estimated 12,511' lateral length, 20,233' TMD. Hydraulically fracture stimulate and be capable of producing from the Marcellus Formation. Should we encounter an unanticipated void in the coal, we will install a minimum of 20' of casing below the void but not more than 100' below the void, set a basket and grout to surface. We plan to run an ECP above the Gantz/Dominion Storage interval to aid in sealing off and isolating the storage interval.

20) Describe fracturing/stimulating methods in detail, including anticipated max pressure and max rate:

The stimulation will be completed with multiple stages divided over the lateral length of the well. Stage spacing is dependent upon engineering design. Slickwater fracturing technique will be utilized on each stage using sand, water, and chemicals. See attached list. Maximum pressure not to exceed 12,500 psi.

- 21) Total Area to be disturbed, including roads, stockpile area, pits, etc., (acres): 68.187 acres
- 22) Area to be disturbed for well pad only, less access road (acres): 11.058 acres
- 23) Describe centralizer placement for each casing string:

No centralizers will be used with conductor casing.
Freshmeter - centralized every 3 joints to surface.
Coal- Bow Spring on every joint, will also be running ACP for isolating storage zono
Intermediate - Bow Spring on first 2 joints then every third joint to 100' from surface.
Intermediate - Bow Spring on first 2 joints then every third joint to 100' from surface.
Frequenciars - Run 1 spring centralizer every 5 joints from the top of the curve.
Production. Run 1 spring centralizer every 5 joints from the top of the curve.

24) Describe all cement additives associated with each cement type:

Conductor -N/A, Casing to be drilled in wi Dual Rotary Rig.

Fresh Water - 15.8 pag PNE-1 + 3% bwoc CaCI, 40% Excess Yield = 1.20, CTS

Fresh Water - 15.8 pag PNE-1 + 3.5% bwoc CaCI, 40% Excess / Tail: 15.9 pag PNE-1 + 2.5% bwoc CaCI zero% Excess, CTS*

Intermediate 1 - T.ead: 15.4 pag PNE-1 + 2.5% bwoc CaCI40% Excess / Tail: 15.9 pag PNE-1 + 2.5% bwoc CaCI zero% Excess, CTS*

Intermediate 2 - T.ead: 15.4 pag PNE-1 + 2.5% bwoc CaCI40% Excess / Tail: 15.9 pag PNE-1 + 2.5% bwoc CaCI zero% Excess, CTS*

Intermediate 2 - T.ead: 15.4 pag PNE-1 + 2.5% bwoc CaCI40% Excess / Tail: 15.9 pag PNE-1 + 2.5% bwoc CaCI40% Excess / Tail: 15.9 pag PNE-1 + 2.5% bwoc CaCI40% Excess / Tail: 15.9 pag PNE-1 + 2.5% bwoc CaCI40% Excess / Tail: 15.9 pag PNE-1 + 2.5% bwoc CaCI40% Excess / Tail: 15.9 pag PNE-1 + 2.5% bwoc R3 + 0.75 gal/sk FP13L + 50% bwoc ASCA1 + 0.5% bwoc MPA17020% Excess Lead Yield=1.94CT.

Production - T.ead: 14.5 pag POZ:PNE-1 + 0.3% bwoc R3 + 1% bwoc EC1 + 0.75 gal/sk FP13L + 0.3% bwoc R3 + 0.75 gal/sk FP13L + 50% bwoc ASCA1 + 0.5% bwoc MPA17020% Excess Lead Yield=1.94CT.

25) Proposed borehole conditioning procedures:

Conductor - Ensure the hole is clean at TD.
Fresh Water - Once casing is at setting depit, circulate a minimum of one hole volume with Fresh Water prior to pumping cornent.
Fresh Water - Once casing is at setting depit, circulate and condition at TD. Circulate a minimum of one hole volume prior to pumping cornent.
Coal - Once casing is at setting depit, Circulate and condition and at TD. Circulate a minimum of one hole volume prior to pumping cornent.
Intermediate - Once casing is at setting depit, Circulate and condition mud at TD. Circulate a minimum of one hole volume prior to pumping cornent.
Production - Once no bolloan/TD with casing, circulate at max allowable pump rate for at least 2x bottom up, or until returns and pump pressures indicate the hole is clean. Circulate a minimum of one hole volume prior to pumping cornent.

RECEIVED
Office of Oil and Gas

NOV 16 2020

WV Department of Environmental Protection

*Note: Attach additional sheets as needed.



1206 N-3H Marcellus Shale Horizontal Harrison County, WV

		1							namson oc		
						1206 N	-3H SH	L	14	220784.42N 181550)4.48E
Ground Elevation 1350'				1206 N-3H LP			14220893.75N 1815483.51E 14232686.05N 1811316.55E				
Azm WELLBORE DIAGRAM		340.538°			1206 N-3H BHL						
		tiol F		GEOLOGY	TOP	BASE	MUD	CEMENT	CENTRALIZERS	CONDITIONING	COMMENTS
WELLBOR	E DIAGRAM	HOLE	CASING	GEOLOGY	TOP	DAGE	MOD	OLIMEIV)	OE(())(()E)EE((O	70000	
		30"	30" 157.5# LS	Conductor	0	125	AIR	N/A, Casing to be drilled in w/ Dual Rotary Rig	N/A	Ensure the hole is clean at TD.	Conductor casing = 0.5" wal thickness
				Fresh Water	0	135, 480, 637, 731		15.6 ppg PNE-1 + 3% bwoc CaCl 40% Excess Yield=1.20 / CTS		Once casing is at setting depth, circulate a minimum	Surface casing = 0,438" wall
		24"	20" 94# J-55	Coal	1010	1015	AIR		Centralized every 3 joints to surface	of one hole volume with	thickness
x	×		34# U-00	Surface / FW	0	1175				Fresh Water prior to pumping cement.	Burst=2110 psi
							1.7	Lead: 15.4 ppg PNE-1 +	Bow Spring on every	Once casing is at setting depth, Circulate and	
		11 33 5	13-3/8" 68# J-55 BTC	Little/Big Lime	1555 / 1596	1575 / 1658		nog PNF-1 + 2 5% bwoc	joint *will also be running ACP for isolating storage zone*	condition at TD. Circulate and minimum of one hole volume prior to pumping cement.	Intermediate casing = 0.480 wall thickness Burst=3450 psi
×	x	17.5"		Injun / Gantz (Storage)	1658 / 1985	1770 / 2050	Salt Polymer				
				Intermediate 1	0	2200					
x	X			Fifty / Thirty Foot	2095 / 2182	2157 / 2200	5 AIR / KCL Salt	nng PNF-1 + 2.5% hwoc	Bow Spring on first 2 joints then every third	Once casing is at setting depth, Circulate and condition mud at TD. Circulate a minimum of one	Intermediate casing = 0,395' wall thickness Burst=3950 psi
		12.25"	9-5/8" 40# J-55 BTC	Gordon Stray / Gordon	2232 / 2272	2272 / 2385					
	100			5th Sand	2515	2527					
x	×			Bayard / Warren	2591 / 2891 2601 / 2931 Polym	Polymer	CaCl zero% Excess. CTS	surface	hole volume prior to pumping cement.	23101 7533 255	
				Intermediate 2	0	3000		Zero% Excess. C13		Lambard assurant	
×	×		/ertical	Speechley	3204	3224	9.0ppg SOBM	<u>Lead</u> : 14.5 ppg POZ:PNE-1 + 0.3%	Run 1 spiral centralizer every 5 joints from the top of the curve to surface.	Once on bottom/TD with casing, circulate at max allowable pump rate for at least 2x bottoms up, or until returns and pump pressures indicate the hole is clean. Circulate a minimum of one hole	wall thickness Burst=16240 psi
		8.5" Vertical		Balltown	3438	3448					
				Benson	4505	4525					
								bwoc R3 + 1% bwoc EC1 + 0.75 gal/sk			
- 101			5-1/2" 23# urve P-110 HP CDC HTQ	Rhinestreet	6395	6651		FP13L + 0.3% bwoc			
				Cashaqua	6651	6751		g gal/sk FP13L + 50%			
X	X	0.00		Middlesex	6751	6783	11.5ppg- 0.3 12.5ppg g				
- 11		8.5" Curve		West River	6783	6854 6864					
- 10				Burkett	6854 6864	6972		bwoc MPA170 20% Excess			
				Tully Limestone Hamilton	6972	7081		Lead Yield=1.19 Tail Yield=1,94 CTS			
9		8.5" Lateral	eral	Marcellus	7081	7260	11.5ppg-				
				TMD / TVD (Production)	20233	7252					= ± 0 = ≤
×	×	1		Onondaga	7260						2020 Prote
l'i	-	X	X	Χ	X		X	Α	X	, X	25 _ 2
	LP @ 72	252' TVD / 7722 MD	ř.		8.5" Hole - Cement 5-1/2" 23# P-110				+/-125	511' ft Lateral	TD @ +/-7252' TVD +/-20233' MD
	X	Х	X	X	X		X	X	X	, X	X=centralizers



HG Energy, LLC 5260 Dupont Road Parkersburg, WV 26101 (304) 420-1100 - Office (304) 863-3172 - Fax

December 5, 2020

Charles R. Sutton 593 Long Run Road Lost Creek, WV 26385

RE: Antonio 1206 N-1H thru S-10H Well Work Permit Applications - Notifications

Modification Request to Extend Surface Casing 75' to 1175' to Cover an Additional Seam of Coal Grant District, Harrison County, West Virginia

Dear Mr. Sutton:

Enclosed are copies of various application papers that we will be filing with the West Virginia Department of Environmental Protection (WVDEP), Office of Oil and Gas. A well work permit modification is being requested for the above-referenced well to extend the FW casing 75 feet to 1175' to cover an additional seam of coal.

Pursuant to WV Code Chapter 22B, Article 6, you are receiving copies of this correspondence because the well or other anticipated disturbance is located on your surface property. Your rights as a surface owner (road) are detailed in the enclosed permit application papers.

No action on your part is required. If you have any questions or comments regarding this notification, you may call this office at (304) 420-1119 or mailto:dwhite@hgenergyllc.com dwhite@hgenergyllc.com.

Very truly yours, Diane white

Diane C. White

RECEIVED Office of Oil and Gas

DEC 1 0 2020

Enclosures



HG Energy, LLC 5260 Dupont Road Parkersburg, WV 26101 (304) 420-1100 - Office (304) 863-3172 - Fax

December 5, 2020

Antonio PLLC c/o Mike Ross P. O. Box 219 Coalton, WV 26257

RE:

Antonio 1206 N-1H thru S-10H Well Work Permit Applications - Notifications

Modification Request to Extend Surface Casing 75' to 1175' to Cover an Additional Seam of Coal

Grant District, Harrison County, West Virginia

Dear Mr. Ross:

Enclosed are copies of various application papers that we will be filing with the West Virginia Department of Environmental Protection (WVDEP), Office of Oil and Gas. A well work permit modification is being requested for the above-referenced well to extend the FW casing 75 feet to 1175' to cover an additional seam of coal.

Pursuant to WV Code Chapter 22B, Article 6, you are receiving copies of this correspondence because the well or other anticipated disturbance is located on your surface property. Your rights as a surface owner (road) are detailed in the enclosed permit application papers.

No action on your part is required. If you have any questions or comments regarding this notification, you may call this office at (304) 420-1119 or mailto:dwhite@hgenergyllc.com dwhite@hgenergyllc.com.

Very truly yours,

Diane White

RECEIVED Office of Oil and Gas

DEC 1 0 2020

Enclosures

WW-6A (9-13)

API NO. 47	
OPERATOR WELL	NO. 1206 N-1H to S-10H
Well Pad Name: Anto	

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS NOTICE OF APPLICATION

Notice Time Requirement: notice shall be provided no later than the filing date of permit application. Date of Notice: 12/07/20 Date Permit Application Filed: 11/30/20 Notice of: RECEIVED Office of Oil and Gas ✓ CERTIFICATE OF APPROVAL FOR THE PERMIT FOR ANY CONSTRUCTION OF AN IMPOUNDMENT OR PIT DEC 1 0 2020 WELL WORK Delivery method pursuant to West Virginia Code § 22-6A-10(b) WV Department of Environmental Protection METHOD OF DELIVERY THAT REQUIRES A ☐ REGISTERED PERSONAL RECEIPT OR SIGNATURE CONFIRMATION SERVICE MAIL Pursuant to W. Va. Code § 22-6A-10(b) no later than the filing date of the application, the applicant for a permit for any well work or for a certificate of approval for the construction of an impoundment or pit as required by this article shall deliver, by personal service or by registered mail or by any method of delivery that requires a receipt or signature confirmation, copies of the application, the erosion and sediment control plan required by section seven of this article, and the well plat to each of the following persons: (1) The owners of record of the surface of the tract on which the well is or is proposed to be located; (2) The owners of record of the surface tract or tracts overlying the oil and gas leasehold being developed by the proposed well work, if the surface tract is to be used for roads or other land disturbance as described in the erosion and sediment control plan submitted pursuant to subsection (c), section seven of this article; (3) The coal owner, operator or lessee, in the event the tract of land on which the well proposed to be drilled is located [sic] is known to be underlain by one or more coal seams; (4) The owners of record of the surface tract or tracts overlying the oil and gas leasehold being developed by the proposed well work, if the surface tract is to be used for the placement, construction, enlargement, alteration, repair, removal or abandonment of any impoundment or pit as described in section nine of this article; (5) Any surface owner or water purveyor who is known to the applicant to have a water well, spring or water supply source located within one thousand five hundred feet of the center of the well pad which is used to provide water for consumption by humans or domestic animals; and (6) The operator of any natural gas storage field within which the proposed well work activity is to take place. (c)(1) If more than three tenants in common or other co-owners of interests described in subsection (b) of this section hold interests in the lands, the applicant may serve the documents required upon the person described in the records of the sheriff required to be maintained pursuant to section eight, article one, chapter eleven-a of this code. (2) Notwithstanding any provision of this article to the contrary, notice to a lien holder is not notice to a landowner, unless the lien holder is the landowner. W. Va. Code R. § 35-8-5.7.a requires, in part, that the operator shall also provide the Well Site Safety Plan ("WSSP") to the surface owner and any water purveyor or surface owner subject to notice and water testing as provided in section 15 of this rule. ☐ Application Notice ☐ WSSP Notice ☐ E&S Plan Notice ☐ Well Plat Notice is hereby provided to: ☐ COAL OWNER OR LESSEE ☐ SURFACE OWNER(s) Name: Antonio PLLC, c/o Mike Ross Name: _____ Address: P. O. Box 219 Address: Coalton, WV 26257 COAL OPERATOR Charles R. Sutton Name: Address: 593 Long Run Road Name: Lost Creek, WV 26385 Address: ☐ SURFACE OWNER(s) (Road and/or Other Disturbance) Name: See Above ☐ SURFACE OWNER OF WATER WELL AND/OR WATER PURVEYOR(s) Address: Name: Address: Name: Address: OPERATOR OF ANY NATURAL GAS STORAGE FIELD ☐ SURFACE OWNER(s) (Impoundments or Pits) Name: ___ Address: Name: See Above Address: *Please attach additional forms if necessary

WW-6A (8-13)

API NO. 47-OPERATOR WELL NO. 1206 N-1H to S-10H Well Pad Name: Antonio 1206

Notice is hereby given:

Pursuant to West Virginia Code § 22-6A-10(b), notice is hereby given that the undersigned well operator has applied for a permit for well work or for a certificate of approval for the construction of an impoundment or pit.

Pursuant to W. Va. Code § 22-6A-10(b), this notice shall include: (1) copies of the application; (2) the erosion and sediment control of 2020 plan required by section seven of this article; and (3) the well plat. WV Department of Environmental Protection

Pursuant to W. Va. Code § 22-6A-10(f), this notice shall include: (1) a statement of the time limits for filing written comments; (2) who may file written comments; (3) the name and address of the secretary for the purpose of filing the comments and obtaining additional information; and (4) a statement that the persons may request, at the time of submitting written comments, notice of the permit decision and a list of persons qualified to test water.

Pursuant to W. Va. Code R. § 35-8-5.7.a, the operator shall provide the Well Site Safety Plan to the surface owner and any water purveyor or surface owner subject to notice and water testing as provided in section 15 of this rule.

Pursuant to W. Va. Code R. § 35-8-15.2.c, this notice shall: (1) contain a statement of the surface owner's and water purveyor's right to request sampling and analysis; (2) advise the surface owner and water purveyor of the rebuttable presumption for contamination or deprivation of a fresh water source or supply; advise the surface owner and water purveyor that refusal to allow the operator to conduct a pre-drilling water well test constitutes a method to rebut the presumption of liability; (3) advise the surface owner and water purveyor of his or her independent right to sample and analyze any water supply at his or her own expense; advise the surface owner and water purveyor whether or not the operator will utilize an independent laboratory to analyze any sample; and (4) advise the surface owner and or water purveyor that he or she can obtain from the Chief a list of water testing laboratories in the subject area capable of and qualified to test water supplies in accordance with standard acceptable methods.

Additional information related to horizontal drilling may be obtained from the Secretary, at the WV Department of Environmental Protection headquarters, located at 601 57th Street, SE, Charleston, WV 25304 (304-926-0450) or by visiting www.dep.wv.gov/oiland-gas/pages/default.aspx

Well Location Restrictions

Pursuant to W. Va. Code § 22-6A-12, Wells may not be drilled within two hundred fifty feet measured horizontally from any existing water well or developed spring used for human or domestic animal consumption. The center of well pads may not be located within six hundred twenty-five feet of an occupied dwelling structure, or a building two thousand five hundred square feet or larger used to house or shelter dairy cattle or poultry husbandry. This limitation is applicable to those wells, developed springs, dwellings or agricultural buildings that existed on the date a notice to the surface owner of planned entry for surveying or staking as provided in section ten of this article or a notice of intent to drill a horizontal well as provided in subsection (b), section sixteen of this article was provided, whichever occurs first, and to any dwelling under construction prior to that date. This limitation may be waived by written consent of the surface owner transmitted to the department and recorded in the real property records maintained by the clerk of the county commission for the county in which such property is located. Furthermore, the well operator may be granted a variance by the secretary from these distance restrictions upon submission of a plan which identifies the sufficient measures, facilities or practices to be employed during well site construction, drilling and operations. The variance, if granted, shall include terms and conditions the department requires to ensure the safety and protection of affected persons and property. The terms and conditions may include insurance, bonding and indemnification, as well as technical requirements. (b) No well pad may be prepared or well drilled within one hundred feet measured horizontally from any perennial stream, natural or artificial lake, pond or reservoir, or a wetland, or within three hundred feet of a naturally reproducing trout stream. No well pad may be located within one thousand feet of a surface or ground water intake of a public water supply. The distance from the public water supply as identified by the department shall be measured as follows: (1) For a surface water intake on a lake or reservoir, the distance shall be measured from the boundary of the lake or reservoir. (2) For a surface water intake on a flowing stream, the distance shall be measured from a semicircular radius extending upstream of the surface water intake. (3) For a groundwater source, the distance shall be measured from the wellhead or spring. The department may, in its discretion, waive these distance restrictions upon submission of a plan identifying sufficient measures, facilities or practices to be employed during well site construction, drilling and operations to protect the waters of the state. A waiver, if granted, shall impose any permit conditions as the secretary considers necessary. (c) Notwithstanding the foregoing provisions of this section, nothing contained in this section prevents an operator from conducting the activities permitted or authorized by a Clean Water Act Section 404 permit or other approval from the United States Army Corps of Engineers within any waters of the state or within the restricted areas referenced in this section. (d) The well location restrictions set forth in this section shall not apply to any well on a multiple well pad if at least one of the wells was permitted prior to the effective date of this article. (e) The secretary shall, by December 31, 2012, report to the Legislature on the noise, light, dust and volatile organic compounds generated by the drilling of horizontal wells as they relate to the well location restrictions regarding occupied dwelling structures pursuant to this section. Upon a finding, if any, by the secretary that the well location restrictions regarding occupied dwelling structures are inadequate or otherwise require alteration to address the items WW-6A (8-13) API NO. 47-____OPERATOR WELL NO. 1206 N-1H to S-10H
Well Pad Name: Antonio 1206

examined in the study required by this subsection, the secretary shall have the authority to propose for promulgation legislative rules establishing guidelines and procedures regarding reasonable levels of noise, light, dust and volatile organic compounds relating to drilling horizontal wells, including reasonable means of mitigating such factors, if necessary.

Water Well Testing:

Pursuant to West Virginia Code § 22-6A-10(d), notification shall be made, with respect to surface landowners identified in subsection (b) or water purveyors identified in subdivision (5), subsection (b) of this section, of the opportunity for testing their water well. The operator shall provide an analysis to such surface landowner or water purveyor at their request.

Water Testing Laboratories:

Pursuant to West Virginia Code § 22-6A-10(i), persons entitled to notice pursuant to subsection (b) of this section may contact the department to ascertain the names and locations of water testing laboratories in the subject area capable and qualified to test water supplies in accordance with standard accepted methods. In compiling that list of names the department shall consult with the state Bureau for Public Health and local health departments. A surface owner and water purveyor has an independent right to sample and analyze any water supply at his or her own expense. The laboratory utilized by the operator shall be approved by the agency as being certified and capable of performing sample analyses in accordance with this section.

Rebuttable Presumption for Contamination or Deprivation of a Fresh Water Source or Supply:

W. Va. Code § 22-6A-18 requires that (b) unless rebutted by one of the defenses established in subsection (c) of this section, in any action for contamination or deprivation of a fresh water source or supply within one thousand five hundred feet of the center of the well pad for horizontal well, there is a rebuttable presumption that the drilling and the oil or gas well or either was the proximate cause of the contamination or deprivation of the fresh water source or supply. (c) In order to rebut the presumption of liability established in subsection (b) of this section, the operator must prove by a preponderance of the evidence one of the following defenses: (1) The pollution existed prior to the drilling or alteration activity as determined by a predrilling or prealteration water well test. (2) The landowner or water purveyor refused to allow the operator access to the property to conduct a predrilling or prealteration water well test. (3) The water supply is not within one thousand five hundred feet of the well. (4) The pollution occurred more than six months after completion of drilling or alteration activities. (5) The pollution occurred as the result of some cause other than the drilling or alteration activity. (d) Any operator electing to preserve its defenses under subdivision (1), subsection (c) of this section shall retain the services of an independent certified laboratory to conduct the predrilling or prealteration water well test. A copy of the results of the test shall be submitted to the department and the surface owner or water purveyor in a manner prescribed by the secretary. (e) Any operator shall replace the water supply of an owner of interest in real property who obtains all or part of that owner's supply of water for domestic, agricultural, industrial or other legitimate use from an underground or surface source with a comparable water supply where the secretary determines that the water supply has been affected by contamination, diminution or interruption proximately caused by the oil or gas operation, unless waived in writing by that owner. (f) The secretary may order the operator conducting the oil or gas operation to: (1) Provide an emergency drinking water supply within twenty-four hours; (2) Provide temporary water supply within seventy-two hours; (3) Within thirty days begin activities to establish a permanent water supply or submit a proposal to the secretary outlining the measures and timetables to be used in establishing a permanent supply. The total time in providing a permanent water supply may not exceed two years. If the operator demonstrates that providing a permanent replacement water supply cannot be completed within two years, the secretary may extend the time frame on case-by-case basis; and (4) Pay all reasonable costs incurred by the real property owner in securing a water supply. (g) A person as described in subsection (b) of this section aggrieved under the provisions of subsections (b), (e) or (f) of this section may seek relief in court... (i) Notwithstanding the denial of the operator of responsibility for the damage to the real property owner's water supply or the status of any appeal on determination of liability for the damage to the real property owner's water supply, the operator may not discontinue providing the required water service until authorized to do so by the secretary or a court of competent jurisdiction.

Written Comment:

Pursuant to West Virginia Code § 22-6A-11(a), all persons described in subsection (b), section ten of this article may file written comments with the secretary as to the location or construction of the applicant's proposed well work within thirty days after the application is filed with the secretary. All persons described in West Virginia Code § 22-6A-10(b) may file written comments as to the location or construction of the applicant's proposed well work to the Secretary at:

RECEIVED
Office of Oil and Gas

Chief, Office of Oil and Gas Department of Environmental Protection 601 57th St. SE Charleston, WV 25304 (304) 926-0450

DEC 1 0 2020

WV Department of Environmental Protection

Such persons may request, at the time of submitting written comments, notice of the permit decision and a list of persons qualified to test water. NOTE: YOU ARE NOT REQUIRED TO FILE ANY COMMENT.

API NO. 47-____ OPERATOR WELL NO. 1206 N-1H to S-10H
Well Pad Name: Antonio 1206

Time Limits and Methods for Filing Comments.

The law requires these materials to be served on or before the date the operator files its Application. You have THIRTY (30) DAYS after the filing date to file your comments. Comments must be filed in person or received in the mail by the Chief's office by the time stated above. You may call the Chief's office to be sure of the date. Check with your postmaster to ensure adequate delivery time or to arrange special expedited handling. If you have been contacted by the well operator and you have signed a "voluntary statement of no objection" to the planned work described in these materials, then the permit may be issued at any time.

Pursuant to West Virginia Code § 22-6A-11(c)(2), Any objections of the affected coal operators and coal seam owners and lessees shall be addressed through the processes and procedures that exist under sections fifteen, seventeen and forty, article six of this chapter, as applicable and as incorporated into this article by section five of this article. The written comments filed by the parties entitled to notice under subdivisions (1), (2), (4), (5) and (6), subsection (b), section ten of this article shall be considered by the secretary in the permit issuance process, but the parties are not entitled to participate in the processes and proceedings that exist under sections fifteen, seventeen or forty, article six of this chapter, as applicable and as incorporated into this article by section five of this article.

Comment Requirements

Your comments must be in writing and include your name, address and telephone number, the well operator's name and well number and the approximate location of the proposed well site including district and county from the application. You may add other documents, such as sketches, maps or photographs to support your comments.

Disclaimer: All comments received will be placed on our web site http://www.dep.wv.gov/oil-and-gas/Horizontal-Permits/Pages/default.aspx and the applicant will automatically be forwarded an email notice that such comments have been submitted. The applicant will be expected to provide a response to comments submitted by any surface owner, water purveyor or natural gas storage operator noticed within the application.

Permit Denial or Condition

The Chief has the power to deny or condition a well work permit. Pursuant to West Virginia Code § 22-6A-8(d), the permit may not be issued or be conditioned, including conditions with respect to the location of the well and access roads prior to issuance if the director determines that:

- (1) The proposed well work will constitute a hazard to the safety of persons;
- (2) The plan for soil erosion and sediment control is not adequate or effective;
- (3) Damage would occur to publicly owned lands or resources; or
- (4) The proposed well work fails to protect fresh water sources or supplies.

A permit may also be denied under West Virginia Code § 22-6A-7(k), the secretary shall deny the issuance of a permit if the secretary determines that the applicant has committed a substantial violation of a previously issued permit for a horizontal well, including the applicable erosion and sediment control plan associated with the previously issued permit, or a substantial violation of one or more of the rules promulgated under this article, and in each instance has failed to abate or seek review of the violation within the time prescribed by the secretary pursuant to the provisions of subdivisions (1) and (2), subsection (a), section five of this article and the rules promulgated hereunder, which time may not be unreasonable.

Pursuant to West Virginia Code § 22-6A-10(g), any person entitled to submit written comments to the secretary pursuant to subsection (a), section eleven of this article, shall also be entitled to receive from the secretary a copy of the permit as issued or a copy of the order modifying or denying the permit if the person requests receipt of them as a part of the written comments submitted concerning the permit application. Such persons may request, at the time of submitting written comments, notice of the permit decision and a list of persons qualified to test water.

RECEIVED
Office of Oil and Gas

DEC 1 0 2020

WW-6A (8-13)

API NO. 47-OPERATOR WELL NO. 1206 N-1H to S-10H Well Pad Name: Antonio 1206

Notice is hereby given by:

Well Operator: HG Energy II Appalachia, LLC

304-420-1119 Telephone:

dwhite@hgenergyllc.com Email:

Address: 5260 Dupont Road

Parkersburg, WV 26101

Facsimile: 304-863-3172

Oil and Gas Privacy Notice:

The Office of Oil and Gas processes your personal information, such as name, address and telephone number, as part of our regulatory duties. Your personal information may be disclosed to other State agencies or third parties in the normal course of business or as needed to comply with statutory or regulatory requirements, including Freedom of Information Act requests. Our office will appropriately secure your personal information. If you have any questions about our use or your personal information, please contact DEP's Chief Privacy Officer at depprivacyofficer@wv.gov.

My Commission Expires

Diane White



Subscribed and sworn before me this 5th day of December Notary Public

> RECEIVED Office of Oil and Gas

DEC 1 0 2020

WW 6A 1206 NIH - SIOH MOD Certified Notice Receipts

	U.S. Postal Service"	and the second
	O.C. I COMI DELVICE	
	CERTIFIED MAIL® RE	CEIPT
LALL	Domestic Mail Only	
=		The second secon
-	For delivery information, visit our webs	ite at www.usps.com*
	The same of the sa	47 0% 00
L	Certified Mail Fee	See Self and Carl
=	3 Caltura Mail Mai	
TAE.T	1 5	O MIN WAS
		A STATE OF THE STA
DUUU	☐ Return Receipt (efectronic) \$	Fostmark
E	Centried Mari Flashricted Delivery 8 /S	Here o
	Adult Signature Required 5	Sec. Sec.
		000
PAR	Postage	- 27
1	is to	- 0.
П	Total Postage and Fees	- SONIH-SICH
П		1200 FW MOD
IT	Sont To	
L		Mike Ross
711	Street and Apt. No., or PO Box No.	
P	PO BOX 219	
	City, State, 21944	6257
	Tree of the second seco	The state of the s
	PS Form 3000. April 2015 PSN 7039-16 000 1647	See Reverse for Instructions
	U.S. Postal Service"	
	CERTIFIED MAIL® REC	SEIDT
m	CENTRIC MARE DE	7-1.1
	Domestic Mail Only	
77	For delivery information, visit our websiti	P. M. Parkini, A. Charles and Physics and
m	For delice without framon was convension	TO BUILD OF STREET
	The same of the sa	
83	Confiled Mall Fee	
1	Ceratica Mail Pee	AURG WV
1	8	550
	Extra Services & Pees (break box, and rise as prescharge) Return Receipt (hardcopy) 3	
0000	Return Receipt hardcopy) 3 Return Receipt (Mechanic) 3	
	CT Confilled Mail Restricted Dalivary 8	Postmark
	Adul Skralure Regulad S	Hote Bro
_	Adult Signature Heatricted Delivery 5	17
	Postage	20.00
FD.	- manage	ales
2280	S. Sand D. San	NIH - 510H
TU	Yoral Postage and Fees	
-	S	1206 FW MOD
	Sent To Charles R S. JL	
701	Charles R Sutton	
-		
	593 Long Run Koad	
	LOST Creek WV 2	6385
	95 Ferm 3800, 4570 2015 PSD 703-1-00-01-0	AND THE PROPERTY OF THE PROPERTY OF



HG Energy, LLC 5260 Dupont Road Parkersburg, WV 26101 (304) 420-1100 - Office (304) 863-3172 - Fax

November 13, 2020

Mr. Wade Stansberry WVDEP Division of Oil & Gas 601 57th Street Charleston, West Virginia 25304

RE:

Antonio 1206 N-1H thru S-10H (47-033-05978,79,80,81,82,83,84,85,86,87))

Modification Request to Extend Surface Casing 75' to Cover an Additional Seam of Coal

Grant District, Harrison County, West Virginia

Dear Mr. Stansberry:

Per discussions with Sam Ward and Taylor Brewer, enclosed are revised WW-6B's and casing schematics for the ten permitted laterals on the Antonio 1206 well pad. We request the drill permits be modified to extend the surface casing from 1100' to 1175' to cover an additional seam of coal which was encountered during the drilling process.

Please let me know if you have any questions or require additional information. I can be reached at (304) 420-1119 or dwhite@hgenergyllc.com.

Very truly yours,

Diane White

RECEIVED Office of Oil and Gas

NOV 16 2020

WV Department of Environmental Protection

Diane C. White

Enclosures

cc: Sam Ward - DEP Inspector

Diane White

From:

Josh Hinton

Sent:

Friday, November 13, 2020 8:07 AM

To:

Diane White

Cc:

Dale Fidurko; Lori Barr

Subject:

RE: Permit modification

We will need to make this change to the other (9) wells on this pad. This is Surface Casing/Fresh Water Protection string.

So make TD/Hole Depth 1175' and Casing Shoe Set depth 1145'

From: hgtopholerig1@gmail.com <hgtopholerig1@gmail.com>

Sent: Friday, November 13, 2020 8:04 AM

To: Dale Fidurko <dfidurko@hgenergyllc.com>; Chip Queen <queenserviceswv@gmail.com>; Josh Hinton <jhinton@hgenergyllc.com>; Lori Barr <lbarr@hgenergyllc.com>; Diane White <dwhite@hgenergyllc.com>

Subject: Permit modification

Antonio 1206 N1 H and pad modification TD hole depth 1174', New casing shoe depth 1144', Last coal seam encounter 1126' to 1130' Reason for modification was the coal seam depth Chip has talk to Sam Ward about this modification Thanks Mike

RECEIVED
Office of Oil and Gas

NOV 1 6 2020