



## WEST VIRGINIA DEPARTMENT OF MINES

## OIL AND GAS DIVISION

## PRELIMINARY DATA SHEET NO. 1

File No. \_\_\_\_\_

Well No. 2  
H C & R 262.

J. H. Reed & Wm. Moss Company of \_\_\_\_\_  
Salem, W. Va., on the J. E. Sprout Farm  
 containing 20 acres. Location \_\_\_\_\_

Sardin District, in Harrison County, West Virginia

The surface of the above tract is owned in fee by Cecil Cunningham  
 of Wallace, W. Va., Route #2, address, and the mineral rights are owned by  
 \_\_\_\_\_ of \_\_\_\_\_

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit  
 No. \_\_\_\_\_ issued by the West Virginia Department of Mines, Oil and Gas Division  
 \_\_\_\_\_ 192 \_\_\_\_\_

Elevation of surface at top of well, 1493 Spirit \_\_\_\_\_

The number of feet of the different sized casings used in the well.

_____ feet	_____ size.	_____ Wood conductor.
<u>1855</u> feet <u>10"</u> size, csg. <u>1923</u> feet <u>8 1/2"</u> sized csg.		
<u>8329</u> feet <u>6-5/8"</u> size, csg. <u>3037</u> feet <u>5-3/16"</u> sized csg.		
<u>3136</u> feet <u>2"</u> size, csg. _____ feet _____ sized csg.		

\_\_\_\_\_ packer of \_\_\_\_\_ size, set at \_\_\_\_\_

\_\_\_\_\_ packer of \_\_\_\_\_ size, set at \_\_\_\_\_

\_\_\_\_\_ is casing perforated at \_\_\_\_\_ feet to \_\_\_\_\_ feet.

\_\_\_\_\_ is casing perforated at \_\_\_\_\_ feet to \_\_\_\_\_ feet.

Coal was encountered at 574 feet, thickness 48 inches, and at 1024

feet; thickness 72 inches; and at \_\_\_\_\_ feet; thickness \_\_\_\_\_ inches.

Liners were used as follows: (Give details): \_\_\_\_\_

Date \_\_\_\_\_

J. H. Reed &amp; Wm. Moss

J. H. Reed & Co. Mine

Company

COMPLETION DATA SHEET

Salmon, T. Va.

Address

NO. 2

Well No. 2 (H.C. & R. Company #262)

1142-211-A

FORMATION RECORD

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Native Coal				576	480	4'		
Pittsburgh Coal				1024	1030	6'		
Little Dunkard Sand				1385	1500	115'		1250 - 10'
Big Dunkard Sand				1535	1550	15'		
First Salt Sand				1735	1820	85'		
Second Salt Sand		Water	1805	1920	1959	39'		1968 - 2 1/2'
Maxon Sand		Water	1954	2143	2212	69'		
Little Lime		Water	2150	2257	2264	7'		
Pencil Cave				2264	2267	3'		
Big Lime				2267	2318	51'		
Big Injun Sand				2318	2422	104'		2329 - 2 1/2'
Squaw Sand		Gas	2318-2330	2456	2443	7'		
Berea Sand				2525	2575	50'		
Gantz Sand				2768	2800	32'		
Fifty Foot Sand				2879	2905	26'		
Thirty Foot Sand		Gas	2895	2990	3008	18'		
Gordon Stray Sand				3022	3084	62'		2037 - 2 3/4'
Gordon Sand		Oil	3105 & 3120	3100	3137	37'	3138	2118 - 2'

shot  
Well was shot at 3113 - 3121 feet; well was shot at \_\_\_\_\_ feet.

Producing  
Well was producing hole  
dry

fresh water at \_\_\_\_\_ feet; fresh water at 1805-1954 & 2150 feet.

**AFFIDAVIT IN TRIPlicate TO TIME AND MANNER OF  
PLUGGING AND FILLING WELL**

(REQUIRED BY SECTION 8, ARTICLE 4, CHAPTER 22 OF THE CODE)

**WEST VIRGINIA DEPARTMENT OF MINES  
OIL AND GAS DIVISION**

No Coal operation in this section \_\_\_\_\_

COAL OPERATOR OR OWNER

Raad & Moyer,

NAME OF WELL OPERATOR

ADDRESS \_\_\_\_\_

Salem, W. Vir. Va.

COMPLETE ADDRESS

COAL OPERATOR OR OWNER \_\_\_\_\_

March 1936 19

WELL AND LOCATION

ADDRESS \_\_\_\_\_

Sardis District

COAL OPERATOR OR OWNER \_\_\_\_\_

Harrison County

ADDRESS \_\_\_\_\_

Well No. 2 (Formerly HC&RCO. #262)

J. W. Sprout Farm

AFFIDAVIT TO BE MADE IN TRIPlicate, ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

**AFFIDAVIT**

STATE OF WEST VIRGINIA,

County of Harrison

ss:

Burt Mitchell

and

Alpha Parker

being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Raad & Moyer, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the day of Oct. 1934, 19, and that the well was plugged and filled in the following manner:

Manner in which said well was plugged: Removed 4" tubing and filled hole with clay to 3080'-20" above Gordon sand and placed wood plug & removed 5 3/16 casing and continued filling with clay to about 2780' and placed wood plug to completely seal the hole.

Installed permanent bridge at 2452'-30" below big injun sand and filled hole with clay to 2330' removed 6 5/8 casing and continued filling to 2298'-20" above big injun sand and placed cement plug. continued filling to 1975' placed a plug of cement, removed casing which is set at 1968' continue filling to 1725'-20" above salt sand and placed cement plug.

Installed permanent bridge and placed wood plug at 1499' filled with clay to 1265'-10" below 10" casing, placed a plug of cement & removed 10" casing, continued filling to 1060'-30" below Pittsburgh coal seam, then filled with cement to 1004'-20" above Pittsburgh coal seam, filled with clay to 510'-30" below the next higher coal seam, then filled with cement to 456'-20" above said coal seam, and from this point to the surface the hole was filled with mud and clay.

Description of monument:

Concrete monument to be erected over the hole when

Rig removed.

THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 4, CHAPTER 22 OF THE CODE.

and that the work of plugging and filling said well was completed on the \_\_\_\_\_ day of November

1934.

And further deponents each say:

HAR-211-A  
Burt Mitchell