

WELL RECORD

Permit No. 140

Oil or Gas Well

Company	South Penn Oil Company	Casing and Tubing	Used in Drilling	Left in Well	Packers
Address	111 Seventh Av., Pittsburg, Pa.				
Farm	N. W. Rector Acres 40				
Location (water)	Cocks Run				
Well No.	1	Flow 1196.73			Kind of Packor
District	Clay	County	Harrison		Callison Anchor
The surface of tract is owned in fee by	E. W. Thompson				Size of
R. D. No. 2	Address Shinnston, W. Va.	8 1/2	205'		-
Mineral rights are owned by	Nancy A. Rector et al	8 1/2	1549'		Depth set
R 82	Address Shinnston, W. Va.	8 1/2	1514' 3"		-
Drilling commenced	March 21, 1910				Perf top
Drilling completed	May 6, 1910				Perf bottom
Test shot	see below	Depth of shot			Perf top
Open Flow	10ths Water in				Perf bottom
	10ths Merc. in				
Volume		Co. Ft.	CASING CEMENTED	SIZE	No. FT.
Rock Pressure		lbs.			Date
Oil	35		COAL WAS ENCOUNTERED AT	98	FEET 96 INCHES
Brack water	170	feet			FEET - INCHES
Salt water	820	feet			FEET - INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil Gas or Water	Depth Found	Remarks
Pittsburgh Coal			98	106			
Little Dunkard Sand			500	520	Water	170	
Big Dunkard Sand			810	848			
Gas Sand			815	1020			
Salt Sand			1050	1160	Water	820	
Big Lime			1388	1867			
Big Injun			1567	1590			
Fifty Foot Sand			2085	2182	Gas	1580	
					Oil	2153	
					Oil	2159	
					Oil	2168	
Total Depth				2197			

SHOT RECORD.

Date

Dec. 11-1910 820 ft.

May 7, 1910 4' 3"

May 12, 1910 4' 3"

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

Form No. MAR-457

Consolidation Coal Co.

Fairmont, W. Va.

SOUTH PENN OIL COMPANY,

411 Seventh Avenue,
Pittsburgh, Pa.

August 29, 1939.
WELL AND LOCATION

Clay District

Harrison County

Well No. 1

N. A. Rector Farm

E. W. Thompson,
R.D. #8, Shinnston, W. Va.

ATTENTION TO BE MADE IN PREPARING THIS AFFIDAVIT TO BE FILED IN THE DEPARTMENT. THE COST TO BE RETURNED BY THE WELL OPERATOR AND THE FILING COSTS AND EXTRA COSTS TO BE PAID BY THE WELL OPERATOR TO EACH LOCAL OPERATOR ABOVE NAMED AT THE RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA

COUNTY OF Harrison

J. F. Bloomer

and

being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by South Penn Oil Company, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 29th day of April, 1939, and that the well was plugged and filled in the following manner:

Manner in which said well was plugged:

Filled with non-porous material 2196' to 2055', - 20' above Fifty Foot Sand. Set wood plug 2065'-22362'. Set cement plug 2068'-2052', - sealing Fifty Foot Sand. Puled 1814' - 5-3/16" casing. Set bridge at 1720', - 30' below Big Injun Sand. Filled with non-porous material to 1547'. Puled 1449'-6-5/8" gas pipe leaving in 1000'. Set wood plug 1547'- 1547'. Set cement plug 1544'-1534', - sealing Big Injun Sand. Set bridge 1190', -30' below Salt Sand. Filled with non-porous material to 1030', - 20' above Salt Sand. Set wood plug 1030' - 10277'. Set cement plug 1027'- 1010', - sealing Salt Sand. Filled with non-porous material to 785'. Set wood plug 785' - 782'. Set cement plug 782' - 762'. Filled with non-porous material to 480'. Set cement plug 480' - 477'. Set cement plug 477'- 457', - sealing Big Dunkard and Little Dunkard Sands. Filled with non-porous material to 306'. Set cement plug 306' to 266'. Hole left open to surface.

Description of measurement

THE STATE OF WEST VIRGINIA DEPARTMENT OF MINES AND GEOLOGICAL SURVEY HAS THE HONOR TO REPLY TO ANY CORRECTIONS TO THIS AFFIDAVIT IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 10, CHAPTER 22 OF THE CODE.

and that the work of plugging and filling said well was completed on the 29th day of May