



0.885  
 3.12 W  
 3.08 - W

LOC. 1.2 M. W. OF HEREFORD  
 New Location X  
 Drill Deeper   
 Abandonment

Company COLUMBIAN CARBON CO.  
 Address BOX 1240 CHARLESTON W.VA.  
 Farm R. A. SHINN ET AL  
 Tract \_\_\_\_\_ Acres 269.5 Lease No. WU-62  
 Well (Farm) No. TWO Serial No. \_\_\_\_\_  
 Elevation (Spirit Level) 649.6  
 Quadrangle RIPLEY S.W. 508-  
 County JACKSON District RIPLEY  
 Engineer J. Sell  
 Engineer's Registration No. 772  
 File No. \_\_\_\_\_ Drawing No. 63  
 Date APRIL 6, '42 Scale 1" = 660'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. Jac-333

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

6-6-1942

WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Permit No. Jac 333

Company

Address

Farm

Location

Well No

District

Surface

Mineral

Commenced

Completed

Not Shot

Volume

Rock Pressure

Fresh Water

Salt Water

Columbian Carbon Co.

Box 1240, Charleston, W.Va.

R.A. Shinn et al Acres 269.5

Stationcamp Run

2 ( GW-661) Elev. 655.0 D.F.

Ripley Jackson County

J.B. Elliott et ux, Ripley, W.Va.

4-17-42

6-24-42

6,166 M CF

1700 lbs. 1 day

58° 4-15" blrs. pr. hr.

445° 2 blrs. /hr.

1625° Hole Full

Gas Well

CASING & TUBING

16 221'1 85'

13 3/8 643'2 0

10 1126'10 0

8 5/8 1954'10 0

7 4895'8 4895'8

2 3/8 5029'6 5029'6

No Packer

Soil	0	15	Sand	1390	1410
Red Rock	15	23	White Slate	1410	1445
Slate	23	35	Black Limo	1445	1470
Red Rock	35	41	Black Slate	1470	1540
White Slate	41	48	Slate & Shells	1540	1560
Sand	48	65	Grey Sand	1560	1700
Slate	65	72	Blue Slate	1700	1710
Sand	72	86	Black Slate	1710	1715
Blue Slate	86	102	Big Limo	1715	1805
Red Rock	102	125	Big Injun Sand	1805	1917
Slate	125	140	Slate & Sand	1917	1948 SLM
Sand	140	200	Black Limo	1948 SLM	1982
White Slate	200	215	Blue Limo	1982	2138
Sand	215	245	Black Slate	2138	2325
Red Rock	245	255	Berea Grit	2325	2345
Limo	255	275	Slate Shells	2345	3415
White Slate	275	285	Limo	3415	3460
Red Rock	285	325	Slate & Shells	3460	3580
White Slate	325	335	Brown Shale - 441	3580	3650
Red Rock	335	365	Slate & Shells	3650	3835
White Limo	365	385	Brown Shale	3835	3985
White Slate	385	400	White Slate	3985	4025
Red Rock	400	425	Brown Shale	4025	4175
Sand	425	450	White Slate	4175	4575
White Slate	450	463	Brown Shale	4575	4849 SLM
Coal	463	469	Gorniferous Limo - 463	4849 SLM	4960 SLM
White Slate	469	595	Oriskany Sand	4960 SLM	5005
Red Rock	595	645	Limo - Held.	5005	5008-S
Sand Shell	645	648			L
White Slate	648	652	TOTAL DEPTH <u>485</u>		SLM 5008 M
Red Rock	652	657			
White Slate	657	680	PAYS: 4969-SLM-73; 4989-90; 500L-04;		
Red Rock	680	760	5007-07½		
Blue Slate	760	775	Show gas 3385; Show gas 3910		
Dark Shale	775	800			
Red Rock	800	825	CEMENT RECORD:		
Limo	825	850	4-20-42 Aquagelled 13 3/8" casing.		
Red Rock	850	865	Mixed 18 sacks 6% aquagel with 1 sack		
White Slate	865	925	Fibrotex.		
Red Rock	925	940			
Limo	940	980	5-4-42 Aquagelled 10 3/4" casing. Mixed		
White Slate	980	1040	18 sacks 6% aquagel with 1 sack fibro-		
Sand	1040	1095	tex.		
White Slate	1095	1112			
Limo Shell	1112	1120	5-17-42 Aquagelled 8 5/8" casing.		
White Slate	1120	1150	Mixed 24 sacks aquagel with 1 sack		
Sand	1150	1200	fibrotex.		
Black Slate	1200	1235			
Sand	1235	1265	6-15-42 Cemented 7" casing. Ran 12		
White Slate	1265	1290	sacks superior cement. Picked pipe up		
Sand	1290	1300	and ran 50 sacks aquagel mixed with		
Slate	1300	1390	2 sacks Fibrotex.		