



New Location
 Drill Deeper
 Abandonment

ABD
 9/54

No. 1
 2.90 - 5
~~2.94~~
 0.68 W

Company United Carbon Company
 Address Charleston, W. Va.
 Farm Rondus Winter et al
 Tract _____ Acres 160 Lease No. 2450
 Well (Farm) No. 1 Serial No. 1068
 Elevation (Spirit Level) 846
 Quadrangle Kenna N.W.
 County Jackson District Ripley
 Engineer C. M. Withrow
 Engineer's Registration No. _____
 File No. _____ Drawing No. _____
 Date June 18, 1942 Scale 1" = 660'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. JAC-373

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
 - Denotes one inch spaces on border line of original tracing.

6-6-1942

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Jac 373
Kenna Quad. N.W.

Gas Well
CASING & TUBING

Company	United Carbon Company		
Address	Box 1913, Charleston, W.Va.	16	16
Farm	Rondus Winters et al Acres 160	13 3/8	796 0
Location	Grasslick Creek	10 1/4	1160 0
Well No	1 Elev. 846'	85/8	2196 2196
District	Ripley Jackson County	7	5039 5039
Surface	Rondus Winters, Fairplain, W.Va.		
Mineral	Same		
Commenced	July 20, 1942	Casing cemented:	
Completed	Oct. 15, 1942	8 5/8 700'	8-30-42
Date shot	10-15-42 Depth 5128 to 5146	7	215'
Flow	26/10ths M in 7" 24#		
Volume	7,959,000 C.F.		
Rock Pressure	1765 lbs. 24 hrs.		
Salt Water	1500' 1 blr. pr. hr.; 1730' H.F.		

Red Rock	16	160
Lime	160	200
Sand	200	220
Red Rock	220	275
Lime	275	300
Slate & Shells	300	500
Red Rock	500	650
Slate & Shells	650	670
Red Rock	670	748
Sand	748	765
Red Rock	765	800
Slate & Shells	800	885
Sand	885	920
Slate	920	930
Red Rock	930	970
Slate & Shells	970	1020
Red Rock	1020	1050
Lime	1050	1120
Sand	1120	1220
Slate & Shells	1220	1310
Sand	1310	1360
Slate & Shells	1360	1455
Sand	1455	1505
Slate	1505	1520
Sand	1520	1540
Slate & Shells	1540	1680
Salt Sand	1680	2075
Big Lime	2075	2080
Injun Sand	2080	2115
Slate & Shells	2115	2523
Berea Sandy Lime	2523	2535
Slate & Shells	2535	3000
Slate	3000	3780
Shale Brown	3780	3920
Slate	3920	4022
Shale Brown	4022	4480
Slate	4480	4575
Shale Brown	4575	4600
Slate	4600	4845
Shale Brown	4845	5027
Corn. Lime - 463	5027	5121
Oriskany Sand	5121	5160
Lime - 463	5160	5160
TOTAL DEPTH		5165

PAYS:

5129	7/10W7" O.D. 22#	1,142 MCF
5131	20/10 W "	1,929 MCF
5133	40/10 " "	2,728 MCF
5135	66/10 " "	3,504 MCF
5141	57/10 " "	3,256 MCF
5145	45/10 " "	2,893 MCF
5156	7/10 " "	1,142 MCF
5158	4/10 " "	862 MCF
5165	4/10 " "	862 MCF

RECORD OF SHOT:

Test before shot 4/10 W 7" O.D. 24#
846 MCF

Shot with 60 qts. glycerine from
5128- 5146 with 2 - 4 1/2" shells on 18'
Anchor

Oil & Water 1180' show

Test After shot:

		8,832 MCF
First 10 Mins	32/10 M 7" OD 24#	
" 15 Mins.	32/10 M "	8,832 MCF
" 20 "	28/10 " "	8,260 MCF
" 25 "	28/10 " "	8,260 MCF
" 30 "	28/10 " "	8,260 MCF
" 35 "	27/10 " "	8,112 MCF
" 40 "	26/10 " "	7,959 MCF
" 45 "	26/10 " "	7,959 MCF
" 50 "	26/10 " "	7,959 MCF
" 55 "	26/10 " "	7,959 MCF
" 60 "	26/10 " "	7,959 MCF

Oil & Water show 1180'
Show oil 1310'
Gas show 2525'
Gas show 4580'
Gas 5128' Show no test

5027 5121
846 846
4181 4275

485