



Company	Guy B. Ray
Address	213 Kanawha Banking & Trust Bldg. Charleston, W. Va.
Farm	Emmett Thaxton
Tract	8 Acres 25.5 Lease No.
Well (Farm) No.	1 Serial No. 2
Elevation (Spirit Level)	845 (Stadia)
Quadrangle	Charleston
County	Kanawha District Pocahontas
Engineer	Robert S. Hyde
Engineer's Registration No.	646
File No.	Drawing No.
Date	June 26, 1937 Scale 1"=300'

STATE OF WEST VIRGINIA
 Department of Mines
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 File No. KAN-417

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

— Denotes one inch spaces on border line of original tracing.

6-6 192

WEST VIRGINIA DEPARTMENT OF MINES

OIL & GAS DIVISION

WELL RECORD

Permit No. Kan-417

Gas Well

Kenna Quad.

CASING & TUBING

Company	Guy B. Ray	13	22
Address	Charleston, W. Va.	10	622
Farm	Ermott Thaxton ACRES 25	8-1/4	1863
Location	Tuppers Creek	6-5/8	4856
Well No.	One ELEV. 845		
District	Poca Kanawha County	6-5/8	cemented
Surface & Mineral	-		
Drilling commenced	April 7, 1938		No Coal
Drilling completed	July 2, 1938		
Date shot	7-3-38 - Depth 4951-4991		
Open Flow	4/10ths Water in 2-inch		
Volume	95,000 c.f.		
Rock Pressure	1600 lbs. approx.		
Water	-		

Formation Color ^{MAX} TOP Base Result Formation Color ^{MAX} TOP Base Result

Surface	red		0	50							
Slate	blue		50	80							
Sand			80	140							
Rock	red		140	210							
Sand			210	260							
Rock	red		260	305							
Slate	blk		305	475							
Sand			475	530							
Slate			530	620							
Sand			620	710							
Slate			710	785							
Sand			785	840							
Slate	blk		840	940							
Sand			940	1085							
Slate			1085	1100							
Salt Sand			1100	1455							
Slate			1455	1465							
Sand			1465	1550							
Slate			1550	1580							
L. Lime			1580	1610							
P. Cave			1610	1617							
Big Lime			1617	1785							
Injun Sand			1785	1830							
Slate Shells			1830	1950							
Slate	wh.		1950	2230							
Shale	brn		2230	2238							
Berea Sand			2238	2248							
Slate & Shells			2248	2625							
Slate	wh.		2625	3212							
Lime Shell			3212	3230							
Slate			3230	3490							
Shale	brn.		3490	3510							
Slate			3510	3750							
Shale	brn.		3750	3770							
Slate	wh.		3770	3880							
Shale	brn.		3880	4040							
Slate	wh.		4040	4570							
Shale	brn.		4570	4846							
Corniferous Lime			4846	4951							
Oriskany Sand			4951	4991							
Lime	blk.		4991	5002							
Total Depth				5002							