



Revised Location

ABD  
4/42

3.81 W  
2.34 R

Company	Guy B. Ray
Address	213 Kanawha Banking & Trust Bldg. Charleston, W. Va.
Farm	Harry Thaxton et al
Tract	5 & 6 Acres 44.6 Lease No.
Well (Farm) No.	1 Serial No. 3
Elevation (Spirit Level)	833.8 (Stadia)
Quadrangle	Charleston
County	Kanawha District Poca
Engineer	Robert S. Hyde
Engineer's Registration No.	646
File No.	Drawing No.
Date	July 27, 1937 Scale 1"=300'

STATE OF WEST VIRGINIA  
Department of Mines  
OIL AND GAS DIVISION  
CHARLESTON

WELL LOCATION MAP  
File No. KAN-421 Rev

Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

Denotes one inch spaces on border line of original tracing.

6-4-192

WEST VIRGINIA DEPARTMENT OF MINES  
OIL AND GAS DIVISION

W E L L R E C O R D

Permit No. Kan-421

Gas Well

Charleston Quad .

CASING & TUBING

Company	Guy B. Ray	10	603	603
Address	213 Kanawha Banking & Trust Bldg., Charleston, W. Va.	8 1/4	1854	1854
Farm	Harry Thaxton, et al	6 5/8 O.D.		4849
Location	Tuppers Creek	CASING CEMENTED: 6 5/8"		
Well No.	1- Serial #3	Elev. 833.8	12/6/37.- 50 Bags behind	
District	Poca	County Kanawha casing.		
Surface	Harry Thaxton & G.F. Dueley, Charleston, W. Va.			
Mineral	Same			
Drilling	Commenced Aug. 29, 1937			
	Completed Dec. 23, 1937			
Date Shot	12/23/37	Depth 4937-4961	-60 quarts.	
Open Flow	90/10ths W. 6 5/8" O.D.			
Volume	3962 M. Cu. Ft.			

Formation	Color	Hor	Top	Base	Result	Formation	Color	Hor	Top	Base	Result
Surface			0	50							
Red Rock			50	60							
Sand			60	170							
Red Rock			170	180							
Slate			180	200							
Red Rock			200	220							
Slate			220	280							
Red Rock			280	380							
Sand			380	405							
Slate			405	455							
Sand			455	560							
Slate			560	970							
Gas Sand			970	1070							
Slate			1070	1100							
Sc. It Sand			1100	1402	Sh. Gas						
Slate & Lime Shells			1402	1455	1115						
Maxon Sand			1455	1573							
Slate			1573	1575							
Little Lime			1575	1597							
Pencil Cave			1597	1601							
Big Lime			1601	1772							
Big Injun			1772	1802							
Slate			1802	1829							
Lime Shell			1857	1870							
Slate & Shells			1870	3430							
Shale	Brown		3430	3470							
Lime Shell			3470	3510							
Shale			3510	3710							
Shale	Brown		3710	3750							
Slate & Shells			3750	3785							
Shale	Brown		3785	4005							
Lime			4005	4050							
Slate	Grey		4050	4500							
Shale	Brown		4500	4831							
Corniferous Lime			4831	4931	S.L.M.						
Oriskany Sand		H	4931	4961	4849'						
					Gas						
TOTAL DEPTH				4961	4956						
					Gas						
					4953						
					60/10W						
					6 5/8"						
					Gas						
					4955						
ELEVATION: RIG FLOOR-			835.18'		90/10W-						
					6 5/8"						

4831  
834  
4931  
834  
3997