



New Location X  
 Drill Deeper .....  
 Abandonment .....

Company WEST VIRGINIA GAS CORPORATION  
 Address 401 UNION BLDG, CHARLESTON, W.VA.  
 Farm L.H.HARRISON ET AL  
 Tract \_\_\_\_\_ Acres 52.5 Lease No. OV 365  
 Well (Farm) No. ONE Serial No. 0-48  
 Elevation (Spirit Level) 686.9  
 Quadrangle KENNA SW  
 County KANAWHA District POCA  
 Engineer Robert S. Dryde  
 Engineer's Registration No. 646  
 File No. 150 Drawing No. W.O. 352  
 Date NOVEMBER 8, 1940 Scale 1 INCH = 400 FEET

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

**WELL LOCATION MAP**  
 FILE NO. KAN-763

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 - Denotes one inch spaces on border line of original tracing.

W-1  
 S-2

*ROAD*  
*1/47*

WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Permit No. Kan-763  
Kenna S. W. Quad.

Gas Well

Company	West Virginia Gas Corp.	CASING & TUBING		
Address	401 Union Bldg., Charleston, W. Va.	16	59-11	59-11
Farm	Lloyd H. Harrison ACRES 52.5a &	13-3/8	473-9	
Location	Trace Fork of Allen Fork	10-3/4	697-1	
Well No.	1 - Serial 0-48 ELEV. 692.5	8-5/8	1920-5	1920-5
District	Poca - Kanawha County	7	4887-9	4887-9
Surface	Lloyd H. Harrison, Sissonville, W.Va.	2	4963	4963
Mineral	Harrison & O. Dean, Kenna, W. Va.	Perf. top -	4937	
Commenced	Dec. 2, 1940	" bot.-	4942	
Completed	Feb. 16, 1941	CASING CEMENTED:		
Shot	2/17/41 - dophth 4945-4980	Size	Feet	Date
Open Flow	4/10ths Merc. in 7" OD 22#	8-5/8 -	25 bags	
Volume	3,181,000 c.f.	20 bags cement behind		
Rock Pressure	1180 lbs. - final	7" OD		
Salt Water	1350			

Gravel	0	20
Red Rock	20	39
Slate	39	56
Red Rock	56	170
Sand	170	180
Blue Slate	180	285
Red Rock	285	370
White Slate	370	393
Red Rock	393	475
Sand	475	500
Black Slate	500	515
Sand	515	548
Slate	548	580
Sand	580	640
Red Rock	640	655
White Slate	655	700
Sand	700	765
Slate	765	930
Sand	930	985
Black Slate	985	1265
Limo	1265	1308
-Salt Sand	1308	1710
-Big Lime	1710	1825
-Injun Sand	1825	1855
Slate	1855	1965
Limo Shells	1965	2020
Shells, Slate	2020	2280
-Brown Shahe	2280	2290
-Berea Sand	2290	2298
Slate&Shells	2298	3505
Brown Shale	3505	3540
Lime & Slate	3540	3890
Brown Shale	3890	4100
White Slate	4100	4575
Brown Shale	4575	4838
-Corniferous Limo	4838	4945
-Oriskany Sand	4945	4987
Lime -	4987	4992
Total Depth		4992

Water at 1350

Gas pay 4947-4961 best test 12/10 W 7" O.D. (22#)	1494M
Gas pay 4970-4977 " " 25/10 W 7"	2157M
Shot 2/17/41 from 4945 to 4980 with 80 qts. glycerine	
Test 30 minutes after shot 8/10 Merc. 7"	4500M
Test 17 hours after shot 4/10 Merc. 7"	3181M