



New Location X
 Drill Deeper
 Abandonment

LOC. 2.6 M. SOUTH OF ADVENT

Company COLUMBIAN CARBON CO.
 Address BOX 1240 - CHARLESTON - W.VA.
 Farm L.D. WICKLINE ET AL
 Tract _____ Acres 187 Lease No. 1903
 Well (Farm) No. ONE Serial No. _____
 Elevation (Spirit Level) 715.1
 Quadrangle KENNA S.E. (7)
 County KANAWHA District POCA
 Engineer J. M. Bell
 Engineer's Registration No. 772
 File No. _____ Drawing No. _____
 Date APRIL 14, 1941 Scale 1" = 600'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. KAN-809

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

Deep Well

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Kan-809

Gas Well

Kenna Quad.	Columbian Carbon Company	Casing & Tubing	
Company	Box 1240, Charleston, W. Va.	16	50' 8" 50' 8"
Address	Lawrence D. Wickline Acres 187	13-3/8	174' 7" Pulled
Farm	Hicumbottom Creek of Poca River	10 1/2	587' 2" 397' 10"
Location	1 (GW-485) Elev. 723.0DF	8-5/8	1822' 2" 1822' 2"
Well No.	Poca Kanawha County	7	4948' 10" 4948' 10"
District	Lawrence Wickline et al	2-3/8	5119' 10" 5119' 10"
Surface	4-27-41	Liners Used	
Commenced	7-21-41	3" 8.7#	92' 5" 92' 5"
Completed	7-13-41 Depth 5034'; 5074' SLM		
Shot	1550 lbs. 25 days		
Rock Pressure	1192' Small show	492 mcf - vol x VJ	
Oil	30' Hole Full 125' Hole Full		
Fresh Water	1234' Hole Full		
Salt Water			

Surface	0	5
Gravel	5	49FW 30'HF
Slate	49	60
Red Rock	60	75
Slate	75	138FW 125HF
Sand	138	158
Slate	158	163
Red Rock	163	178
Slate	178	195
S and	195	210
Slate	210	237
Red Rock	237	345
Slate & Shells	345	360
Red Rock	360	410
Slate & Shells	410	460
Shale	460	500
Sand	500	574
Slate	574	585
Shale	585	640
Sand	640	745
Slate & Shells	745	765
Sand	765	820
Slate	820	933
Sand	933	1020
Slate & Shells	1020	1123
S and	1123	1155
Slate	1155	1185
✓ Salt Sand	1185	15450/S1192'
✓ Little Lime	1545	1570/S1192'
✓ Big Lime	1570	1716
✓ Big Injun Sand	1716	1769
Slate	1769	1776
Black Lime	1776	1900
Grey Shale	1900	1910
Slate Shells	1910	2176G/S1213'
✓ Brown Shale	2176	2186S/W1234HF
→ Berea Sand	2186	2191
Slate Shells	2191	3890
Shale	3890	3963
Slate & Shells	3963	4578G/S4585'
✓ Brown Shale	4578	4840
✓ Black Shale	4840	4892SLM
✓ Corniferous Lime	4892	5009 Per sample
✓ Oriskany Sand	5009	5046 Per sample
✓ Lime Break	5046	5071 Per sample Oil Smell 5050*
✓ Oriskany Sand	5071	5089 Per sample
✓ Lime	5089	5098SLM
Total Depth		5098SLM
Pays:	5034-38; 5065-71	

Cement Record:
5-24-41 Cemented 8-5/8" casing. Ran 95 sacks Universal cement mixed with 2 sacks Aquagel. Picked up pipe 20' & pumped up & down. 45' cement in hole.
6-30-41 Cemented 7" casing. Ran 12 sacks cement mixed and dumped with dump bailer. No cavings. Set pipe back on bottom. 44' cement in hole.

4892	5009	5089
723	723	723
4169	4286	4366