



New Location
 Drill Deeper
 Abandonment

AGD
 10/52

W- 2.45
 S- 4.5

Company GODFREY L. CABOT INC.
 Address 600 UNION BLDG. CHARLESTON W.VA.
 Farm J. L. McLEAN HRS
 Tract _____ Acres 65 3/4 Lease No. 3-463
 Well (Farm) No. 10 Serial No. 983
 Elevation (Spirit Level) 848.07 "Ground"
 Quadrangle KENNA SW.
 County KANAWHA District POCA
 Engineer _____
 Engineer's Registration No. 975
 File No. _____ Drawing No. _____
 Date April 23, 1941 Scale 1" = 1320'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. KAN-818

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

✓ Deepwell

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Kan-818
Kenna S W Quad
Company
Address
Farm
Well No.
District
Commenced
Completed
Shot
Flow
Volume

Godfrey L. Gabot, Inc.,
Charleston, W. Va.
J. L. McLean Heirs.
10 Serial No. 988 Elev. 848.07
Poca Kanawha County
May 19, 1941
August 12, 1941
8-14-41 Depth 5044'
40 mins. After shot.
1,543 M.C.F.

Gas Well

Casing & Tubing
13-3/8 156 156
10 793 793
8-5/8 2088 --
7 4938 4938
2-3/8 5127 5090
Tubed & Shut in 8-16-41
Perf. top 5041
Perf. bot. 5049
Perf. top 5086
Perf. bot 5092

Soil	16	16	Slate	1420	1460
Shale	16	35	Lime	1460	1495
Red Rock	35	52	Slate	1495	1497
Red Rock	60	75	Lime	1497	1568
Lime	75	79	✓ Sand Salt?	1568	1873
Red Rock	79	89	✓ Lime Big Lime?	1873	1998
Shale	89	93	Shale	1998	2002
Red Rock	93	105 S.L.	✓ Sand Iron?	2002	2045
Slate	105	121	Slate & Shells	2045	2058
Red Rock	121	135	Lime	2058	2063
Lime	135	144	Slate & Shells	2063	2413
Shale	144	160	✓ Sand Salt?	2413	2435
Lime	160	165	Shale	2435	2460
Red Rock	165	225	Shale	2460	2469
Shale	225	240	Lime	2469	2498
Red Rock	240	260	Shale & Shells	2498	3745
Shale	260	272	Shale	3745	3785
Lime	272	290	Shale	3785	3991
Red Rock	290	320 S.L.	Shale	3991	4034
Slate	320	340	Shale	4034	4094
Red Rock	340	360 S.L.	Shale	4094	4270
Shale	360	387	Shale	4270	4675
Slate	387	406	Shale	4675	4888
Red Rock	406	410	Shale	4888	4926
Lime	410	424	✓ Corniferous	4926	5023
Slate	424	457	✓ Oriskany	5023	5090
Lime	457	490	✓ Big Lime - H	5090	5093
Red Rock	490	552	Total Depth	5093	
Lime	552	600	Gauges in Oriskany Sand Before Shot		
Red Rock	600	630	8-10 5028	100M	
Slate	630	660	5029	100M	
Red Rock	660	668	5031	100M	
Slate	668	730	8-11 5046	445M	
Red Rock	730	750	5049	268M	
Lime	750	761	5055	300M	
Red Rock	761	773	8-12 5059	328M	
Lime	773	777	5063	300M	
Sand	777	860	5068	300M	
Slate	860	890	5072	300M	
Sand	890	935	5074	300M	
Lime	935	955	5081	300M	
Slate	955	965	8-13 5087	300M	
Sand	965	970	5089	300M	
Slate	970	1080	8-14 5093	212M	
Lime	1080	1095	Gauges in Oriskany After Shot		
Slate	1095	1113	8-14 5093	212M Before Shot	
Sand	1113	1172	8-14 5Min.	2,040M	
Lime	1172	1187	10Min.	1,809M	
Slate	1187	1213	15Min.	1,724M	
Lime	1213	1232	20 Min	1,687M	
Sand	1232	1273	40Min.	1,543M	
Slate	1273	1295			
Sand	1295	1320			
Slate	1320	1360			
Lime	1360	1384			
Slate & Shells	1384	1400			
Lime	1400	1420			

4926 5023 5090
848 848 848

4078 4175 4242