

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Kan-858

Company	Godfrey L. Cabot, Inc.	Gas Well	
Address	Charleston, W. Va.	CASING & TUBING	
Farm	Putnam County	10 $\frac{1}{2}$ "	854 854 Cas. Sh
Location	Acres-- 7.5 ⁺	8-5/8	2093
Well No	27	864 7	4995 4995
District	Ser. 999	2-3/8	5082 5082 Bot. Wld.
Surface	Poca Kanawha County		
Mineral		1-8 5/8 W x10x16" B.H.P.	
Commenced	Oct. 3, 1941	and 25 sacks aquagol	
Completed	Jan. 25, 1942	1-7" O.D. Sp. Oriskany	
Shot	1-27-42	Packer and 40 sacks	
Volume	Depth 5066-5086-30 qts. aquagol. Perf. top 5066		
Rock Pressure	Depth 5095-5102-10 qts. Perf. bot 5086		
Salt Water	B.S. 146 MCF A.S. (20 Min) 622 MCF Tubed and shut in		
	1225' 31 hrs. Oriskany	2-14-42	
	1610-15 Holo Full		

Soil	0	20	Slate	1105	1140
Sand	20	100	Sand	1140	1215
Red Rock	100	140	Slate Gr	1215	1300
Lime	140	156	Sand	1300	1337
Sand	156	160	Slate & Shells	1337	1404
Blue Shale	160	225	Sand	1404	1460
Red Rock	225	255	Lime	1460	1525
Lime	255	260	Salt Sand	1525	1800
Slate	260	320	Dark Shale	1800	1803
Red Rock	320	372	Limo	1803	1840
Sand	372	380	Grey Sand - Blue	1840	1872
Blue Slate	380	395	Lime	1872	2033
Sand	395	400	Shale	2033	2036
Slate	400	451	Injun Sand	2036	2088
Lime Break	451	495	Lime	2088	2113
Shale	495	528	Slate & Shells	2113	2510
Red Rock	528	566	Sand	2510	2525
Shale	566	584	Slate & Shells	2525	2533
Shells	584	594	Berea Shells	2533	2700
Slate	594	604	Gr. Slate & Shells	2700	3366
Grey Lime	604	634	Lime Slate	3366	3459
Shells	634	649	Grey Slate	3459	3725
Red Rock	649	679	Brown Shale	3725	3762
Shells	679	721	Shells & Slate	3762	4742
White Sand	721	749	Brown Shale	4742	4935
Blue Slate	749	793	Black Shale	4935	4989
Limo	793	808	Corniferous	4989	5063
Red Rock	808	820	Oriskany	5063	5138
White Slate	820	825	Limo	5138	5148
Grey Sand	825	856	TOTAL DEPTH		SIM 5148
Slate Shells	856	950 S.W.			
Grey Sand	950	980	975' Show Gas 2500'		
Grey Slate	980	1023	Producing Sand-Oriskany 5067-5099-		
Sand	1023	1035	622 MCF-Init. Prod.		
Slate & Shells	1035	1075	Gauges in Oriskany B.S. A.S. (B.S. 146M)		
Sand & Lime	1075	1105	5067 211 M 5 min A.S. 696 M		
			5070 146 M 10 " A.S. 641 M		
			S.D. testing casing 15 " A.S. 622 M		
			5071 146M 20 " " 622 M		
			5977 174 M		
			5081 146 M		
			5082 140 M		
			5083-5097 219 M		
			5099 260M		
			5103-5148 189 M		