



New Location X  
 Drill Deeper  
 Abandonment

LOC. 0.6 M. N.E. OF ISLAND BRANCH

Company COLUMBIAN CARBON CO.  
 Address BOX 1240 CHARLESTON W.VA.  
 Farm ALONZO PAINTER ET AL  
 Tract \_\_\_\_\_ Acres 56.67 Lease No. CT-74  
 Well (Farm) No. ONE Serial No. \_\_\_\_\_  
 Elevation (Spirit Level) 883.7  
 Quadrangle KENNA S.E. -5-  
 County KANAWHA District POCA  
 Engineer J. M. Sell  
 Engineer's Registration No. 772  
 File No. \_\_\_\_\_ Drawing No. 374  
 Date OCT. 29, 1941 Scale 1" = 660'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. KAN-887

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 - Denotes one inch spaces on border line of original tracing.

*Handwritten note:*  
 0625 75'  
 38° 31' 30" 2.365  
 81° 30' 1.24W  
 15'  
 5.245  
 1.24W  
 ok

*Handwritten note:*  
 5.475  
 129 W



WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Permit No. Kan. 887

Company                   Columbian Carbon Co.  
Address                   Box 1240, Charleston, W.Va.  
Farm                      Alonzo Painter et al Acres 56.67  
Location                 Allen Creek  
Well No.                 1 ( GW- 629)   Elev. 888.0 D.F.  
District                 Poca             Kanawha County  
Surface                 Alonzo Painter et al, (contact  
                          Columbian Carbon Co. for addresses)

Dry Hole  
CASING & TUBING  
14       40"  
10 $\frac{1}{2}$    751'8 Pulled  
85/8 1780'3  
7       5126'6"

Mineral  
Commenced             2-6-42  
Completed             5-27-42

Not shot  
Volume                 Dry Hole  
Fresh Water           850' 1-10" blr. pr. hr.  
Salt Water            1380' Hole Full

Clay	0	5
Sand	5	35
Red Rock	35	40
Sand	40	145
Slate	145	220
Sand	220	275
Slate	275	285
Red Rock	285	300
Sand	300	360
Slate	360	362
Red Rock	362	470
Slate	470	500
Red Rock	500	548
Sand	548	575
Red Rock	575	630
Sand	630	650
Red Rock	650	665
Slate	665	680
Sand	680	715
Slate	715	739
Sand	739	870
Slate	870	955
Sand	955	1030
Slate	1030	1050
Sand	1050	1130
Slate	1130	1235
Sand	1235	1365
Slate	1365	1372
✓ Salt Sand	1372	1635
✓ Little Lime	1635	1710
✓ Slate	1710	1715
✓ Lime Shells	1715	1730
✓ Slate	1730	1735
✓ Big Lime	1735	1900
✓ Big Injun Sand	1900	1955
Slate & Shells	1955	2300
Slate	2300	2315
Lime Shells	2315	2320
White Slate	2320	2900
Slate & Shells	2900	3990
Brown Shale	3990	4220
White Slate	4220	4665
Brown Shale	4665	4935
White Slate	4935	5021
Brown Shale	5021	5066
✓ Corniferous Lime	5066	5207
✓ Oriskany Sand	5207	SLM5285
✓ Lime	5285	5297
TOTAL DEPTH		5297

CEMENT RECORD:

2-23-42 Aquagelled 10 $\frac{1}{2}$ " casing. Ran 12 sacks aquagel and 1 sack Fibrotex, mixed 6% solution.

3-20-42 Cemented 8 5/8" casing. Ran 75 sacks Alpha cement. Ran plug on bottom and top of cement. 15' hard cement in hole.

5-9-42 Cemented 7" casing. Ran 10 sacks cement in dump bailer. 37' hard cement in hole.

Small show of Gas 1820

SLM