



New Location... X
 Drill Deeper...
 Abandonment...

LOC. IS 1.4 MILES N.E. OF BLUNDON

Company COLUMBIAN CARBON CO.
 Address BOX 1240 CHARLESTON W.VA.
 Farm LORA JACKSON
 Tract _____ Acres 72 Lease No. C-1948
 Well (Farm) No. ONE Serial No. _____
 Elevation (Spirit Level) 834.3
 Quadrangle KENNA S.E. -7-
 County KANAWHA District POCA
 Engineer [Signature]
 Engineer's Registration No. 772
 File No. _____ Drawing No. 384
 Date NOV. 6, 1941 Scale 1" = 660'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. KAN888

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

2.14 S
 0.44 W

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Kan 888

Company
Address
Farm
Location
Well No
District
Surface
Mineral
Commenced
Completed
Shot

Volume
Rock Pressure
Fresh Water
Salt Water

Columbian Carbon Co.
Box 1240, Charleston, W.Va.
Lora Jackson Acres 72
Goose Creek
1 (GW-531) Elev. 836.0DF
Poca Kanawha County
~~I.E. Fields, Elkview, W.Va.~~
Same
2-8-42
5-14-42
5-14-42 Depth 5161' SLM-5191' SLM
200# 80% Gelatin
1,929 MCF
870# 5 days
50' Hole Full
1282-1300 Hole Full

Gas Well
CASING & TUBING
14 61' 61'
10 1/2 496' Pulled
8 5/8 1647'5 1647'5
7" 5068'10 5068'10
2 3/8 5249'5 5249'5
3 1/2 89'10 89'10

Surface	0	30	CEMENT RECORD:
Sand	30	70	2-14-42 Cemented 14" casing. Dumped
Slate	70	80	10 sacks Alpha cement in hole. Set pipe
Red Rock	80	275	down in cement. Water failed to shut off.
Sand	275	305	
Red Rock	305	325	2-18-42 Ran 25 sacks Alpha cement.
Sand	325	355	Pumped plug to bottom of pipe. Drilled
Rock-Pink	355	380	out cement- water still coming in.
Sand	380	425	
Red Rock	425	485	2-22-42 Hole filled solid with stone
Sand	485	690	back to 70'. Ran 100 Sacks Alpha cement
Slate	690	725	with 2 sacks aquagel. Pumped plug to
Sand	725	740	58'. Ran 12' spacer.
Slate	740	830	
Sand	830	860	3-1-42 Aquagelled 10 1/2" casing. Ran 14
Slate	860	885	sacks 6% aquagel with 50# Fibrotex.
Sand	885	900	
Slate & Shells	900	1100	3-23-42 Cemented 8 5/8" casing. Ran 100
Lime	1100	1160	sacks Alpha cement. Ran 10' spacer. 8'
Slate	1160	1175	cement in hole.
✓ Salt Sand	1175	1340	
Black Lime	1340	1360	5-3-42 Cemented 7" casing. ran 10 sacks
✓ 2nd Salt Sand	1360	1410	Alpha cement. 37' cement in hole.
Slate	1410	1460	
✓ Maxon Sand	1460	1585	
✓ Little Lime	1585	1611	
✓ Slate - P. Cave	1611	1625	
✓ Big Lime	1625	1693	
✓ Sand - Keener Sa	1693	1712	
Lime - Big Lime	1712	1782	
Big Injun Sand	1782	1815	
Slate & Shells	1815	2265	
Berea Grit	2265	2270	
Slate & Shells	2270	3410	
Brown Shale	3410	3520	
White Slate	3520	3690	
Brown Shale	3690	4120	
White Slate	4120	4560	
Brown Shale	4560	4890	
White Slate	4890	4915	
Shale	4915	5023	SLM
✓ Corniferous Lime	5023	5155	SLM
Oriskany Sand	5155	5190	SLM
Lime Break	5190	5198	
✓ Oriskany Sand	5198	5225	
Lime - H	5225	5229	SLM
TOTAL DEPTH		5229	SLM Pay 5161-71