



New Location
 Drill Deeper
 Abandonment

Company GODFREY L CABOT INC.
 Address 900 UNION BLDG. CHARLESTON W.VA.
 Farm D Holmes Morton
 Tract _____ Acres 200 Lease No. 3-467
 Well (Farm) No. 9 Serial No. S.998
 Elevation (Spirit Level) 950.36 888.75
 Quadrangle KENNA
 County KANAWHA District POCA
 Engineer Roy Boston
 Engineer's Registration No. _____
 File No. _____ Drawing No. _____
 Date 2-16-42 Scale 1" = 1320'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. KAN-920

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
 - Denotes one inch spaces on border line of original tracing.

ASD
 4/4/46

1.95
 2.24 W

Deep Well

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Kan 920		Gas Well
Kenna Quad.		CASING & TUBING
Company	Godfrey L. Cabot, Inc.	10 $\frac{1}{2}$ 892 892
Address	Charleston, W.Va.	85/8 2017 2017
Farm	D. Holmes Morton Acres ---	7" 4940 4940
Location	--	2 3/8 5079 5079
Well No	9 Ser 998 Elev. 817.75	10 $\frac{1}{2}$ Half Collar shoe
District	Poca Kanawha County	28 bags aquagel. 1 8 5/8
Surface	---	x 10 $\frac{1}{2}$
Mineral	--	D.H. Spang Packer #20138
Commenced	March 28, 1942	7" D.H. Spang Packer
Completed	June 22, 1942	# 20476; 40 bags aquagel;
Date shot	6-24-42 Depth 5013 to 5033 with 40 qts. 4 fibertex.	
Volume	B.S. 484 MCF 1 hrs. A.S. 1,279 MCF	
Rock Pressure	Oriskany 1575 in 16 hrs.	2 3/8 bottom joint welded.
Fresh Water	--	Tubed under line pressure.
Salt Water	1426; H.F. 1452'	Tubed and shut in 7-7-42
		Perf. top 5022 5030 Bot
		" " 5073 5079 Bot

Red Rock	0	10	Slate & Shells	2046	2425
Lime	10	42	Sand <i>Blue</i>	2425	2450
No record	42	70	Shale	2450	2484
Shale	70	156	Shale & Shell	2484	2610
Lime	156	178	Shale	2610	2671
Shale	178	200	Lime Shells	2671	2707
Lime	200	278	Lime	2707	2738
Shale	278	285	Shale	2738	2775
Red Rock	285	320	Slate " Lime Shells	2775	2924
White Slate	320	335	Shale	2924	2951
Red Rock	335	360	Slate & Shells	2951	3160
Lime	360	372	Shale	3160	3185
Red Rock	372	388	Slate & Shells	3185	3228
Shale	388	392	Shale	3228	3267
Red Rock	392	410	Slate & Shells	3267	3391
Lime	410	430	Shells	3391	3428
White Slate	430	440	Slate & Lime Shells	3428	3558
Lime	440	528	Shale	3558	3585
Shale, gray	528	550	Slate & Shells	3585	3636
Lime, White	550	575	Shale	3636	3643
Slate	575	581	Gritty Lime, Black	3643	3675
Lime	581	625	Brown Shale & Shells	3675	3705
Shale, Gray	625	640	Shale, & Slate, Dark	3705	3755
Lime, Gray	640	656	Shale & Shells, White	3755	3770
Red Rock	656	670	Lime	3770	3779
Slate, White	670	707	Shale & Shells, White	3779	3871
Lime	707	728	Shale, Dark	3871	3938
Shale	728	740	Shale & Shells, White	3938	3974
Lime	740	759	Shale, Dark Brown	3974	4212
Sand	759	795	Shale, White	4212	4226
Shale	795	815	Shale, Brown	4226	4795
Gritty Lime	815	870	Shale, White	4795	4845
Slate & Shells	870	954	Shale	4845	4899
Shale, Gray	954	950	Slate, Black	4899	4919
Lime, Blue	960	985	Lime <i>Oriskany</i>	4919	5012
Slate, Black	985	996	Sand <i>Oriskany</i>	5012	5053
Gritty Lime	996	1060	Lime	5053	5063
Slate, Black	1060	1095	Sand	5063	5085
Slate & Lime Gray	1095	1137	Lime	5085	5087 SL
Sand	1137	1203	TOTAL DEPTH		5087
Slate	1203	1280	Show oil 1285-90; Gas 3065-70; 3646		
Sand, White	1280	1357	Shale gas 95 M		
Slate, Black	1357	1375	GAUGES IN ORISKANY R.S.		
Sand, White <i>gas</i>	1375	1795	5014-Show	5045-50	553M
Big Lime, White	1795	1973	5018 189M	5059	520M
Sand, White <i>gas</i>	1973	1980	5022 280 M	5080-87	465M
Black Shale	1980	1983	5024 327 M	GAUGES IN ORISKANY A.S.	
Sand, White <i>gas</i>	1983	2004	5026 270 M	Gauge B.S. 484 M	
Shale	2004	2020	5027 310 M	5 Mins. A.S. 1767 M	
Lime	2020	2046	5028 315 M	10 " " 1590M	
			5032-5036 561M 15	" " 1443 M	
			5040 561 M	20 " " 1390 M	
			60 " " 1279 M		

Producing Sand Record - Best gauge
Oriskany Sand 5014-5032 561 MCF