



0625 75' loc 15'  
 38° 35' 2.145 2.145  
 81° 27' 30" 2.07W 4.25W

2.195  
 4.22W

- New Location
- Drill Deeper
- Abandonment

SKL  
 P. 415  
 9 WC (I-6)

Company COLUMBIAN CARBON CO.  
 Address BOX 873 CHARLESTON W.VA.  
 Farm J.A. DODD ET AL  
 Tract \_\_\_\_\_ Acres 320 1/4 Lease No. CT-103  
 Well (Farm) No. 1 Serial No. G.W.-682  
 Elevation (857) BAR.  
 Quadrangle WALTON S.W. -9-  
 County KANAWHA District POCA  
 Engineer J. M. [Signature]  
 Engineer's Registration No. 772  
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
 Date 7-21-42 Scale 1" = 660'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. KAN-953

- + Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
- Denotes one inch spaces on border line of original tracing.

✓  
 Deepwell

WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Permit No. Kan 953  
Walton Quad S.W.

Dry Hole  
CASING & TUBING

Company	Columbian Carbon Company	14	35'
Address	Box 873, Charleston, W.Va.	10 $\frac{1}{2}$ "	542' 11" Pulled
Farm	John A. Dodd et al Acres 320 $\frac{1}{2}$	8 5/8	1683' 8" "
Location	Hunt Fork of Green Creek	7	5111' 6"
Well No	1 (GW-685) Elev. 866.5 DF		
District	Poca Kanawha County		
Surface	Eva J. & Sigel Moore (81A) & Delbert Dodd (9A)		
Mineral			
Commenced	8-15-42		
Completed	11-10-42		
Not shot			
Volume	Dry Hole		
Fresh Water	70' 5 -13" blrs. pr.hr.		
Salt Water	1295' H.F.		

Sand	0	85	Slate & Shells	2505	3440
Slate	85	115	Brown Shale	3440	3470
Red Rock	115	125	Lime Shells & Slate	3470	3940
Blue Sand	125	132	Brown Shale	3940	4130
Red Rock	132	170	White Slate	4130	4610
Slate	170	190	Lime Shells	4610	4625
Red Rock	190	250	White Slate	4625	4685
Sand	250	270	Brown Shale	4685	4725
Slate	270	310	White Slate	4725	4790
Sand	310	335	Brown Shale	4790	4970
Red Rock	335	345	White Slate	4970	5005
Blue Rock	345	370	Brown Shale	5005	* 5073
Sand	370	390	Corriferous Lime	5068	SLM 5202
Shale	390	405	Oriskany Sand	SLM 5202	SLM 5242
Red Rock	405	425	Lime Break	5242	5257
Sand	425	440	Oriskany Sand	5257	5276
White Slate	440	510	Black Lime	5276	DLM 5284
Sand	510	680	TOTAL DEPTH		5284
Slate	680	750			
Sand	750	800	SLM 5073 -5068 *		
Slate	800	860			
Sand	860	935	CEMENT RECORD:		
Slate	935	945	8-22-42 Aquagelled 10 $\frac{1}{2}$ " casing.		
Sand	945	980	Ran 15 sacks aquagel and 1 bale		
Slate	980	1030	Fibrotex. Returns 360'. Pumped plug		
Lime Sand	1030	1066	to 475'		
Slate	1066	1128			
Sand	1128	1180	9-13-42 Aquagelled 8 5/8" casing.		
Slate	1180	1200	Ran 20 sacks aquagel and 1 bale Fibrotex		
Sand	1200	1260	Show gas 1290) Returns 1250'		
Salt Sand	1260	1530			
Maxon Sand	1530	1615	10-25-42 Cemented 7" casing. Ran 50		
Slate	1615	1620	sacks aquagel and 2 bales Fibrotex.		
Little Lime	1620	1645	Picked pipe up 45' and ran 20 sacks		
Pencil Cave	1645	1658	Alpha cement on bottom with dump bailer.		
Big Lime	1658	SLM 1810	Show gas 1777 Pipe went back to bottom.		
Big Injun Sand	1810	1840	Show gas 1797		
Slate	1840	1850			
Limsy Sand	1850	1885			
Slate & Shells	1885	2485			
Lime Shell	2485	2505			

5068	5202	5276
867	867	867
<hr/>	<hr/>	<hr/>
4201	4335	4409