



New Location
 Drill Deeper
 Abandonment

12-23-68

Company MORGANIC CHEMICALS CO., INC. CORP.
WESTVACO CHLORINE PROD. CORP.
 Address SOUTH CHARLESTON, W.VA.
 Farm WESTVACO CHLORINE PROD. CORP.
 Tract _____ Acres _____ Lease No. _____
 Well (Farm) No. _____ Serial No. _____
 Elevation (Spirit Level) 583.18'
 Quadrangle CHARLESTON WV
 County KANAWHA District UNION
 Engineer C. R. Smith
 Engineer's Registration No. 941
 File No. _____ Drawing No. _____
 Date 9-19-42 Scale 1"=100'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. KAN-973-P

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
WELL RECORD

Permit No. Kan 973		Salt Brine Well
Charleston Quad.		CASING & TUBING
Company	Westvaco Chlorine Products Corp.	
Address	South Charleston, W.Va.	16 44'
Farm	100' East of Dunbar on Kanawha River Bank	
Location	Kanawha Acres --	13 3/8 218'
Well No	27 Elev. --	110-3/4" 809'
District	Union Kanawha County	
Surface	Westvaco Chlorine Products Corp.	Bottom Hole Packer
	So. Charleston, W.Va.	Size 10"
Mineral	Same	Depth 812'
Commenced	Oct. 12, 1942	
Completed	Dec. 12, 1942	
Date shot	12/13/42 (see remarks)	Casing not cemented
		Coal 148' 24"

Surface		0	34	
Sand & Gravel		34	44	
Slate	Blue	44	60	
Slate	White	60	90	
Sand, Fresh Water		90	118	
Slate	White	118	148	
Coal		148	150	
Sand	Gray	150	202	
Slate	Black	202	212	<i>Not black here</i>
Sand	Red	212	268	
Slate	Gray	268	295	
Sand	White	295	325	
Slate & Shale		325	360	
Sand	White	360	395	
Slate	Dark	395	425	
Sand	Gray	425	460	
Slate	Dark	460	550	
Sand	Gray	550	558	
Slate		558	679	
Sand	White	679	697	
Slate	Blue	697	720	
Sand	Gray	720	775	
Slate	Blue	775	795	
Salt Sand		795	960	Pay at 900'
Slate		960	965	
Salt Sand Pay		965	1015	
Slate		1015	1023	
Salt Sand Dry		1023	1050	
Salt Sand Pay		1050	1195	
Slate & Sand		1195	1220	
Sand		1220	1315	
Slate		1315	1320	
Salt Sand Pay		1320	1416	
Little Lime		1416	1418	

Drilled in 12-12-42 standing level of water 325'. Shot 900'-1015' 120 qts. Nitro glycerine. Shot 1050' -1195' 140 qts. Nitro. Shot 1220' 1416-190 qts. Nitro glycerine.

WESTVACO CHLORINE PRODUCTS CORP. NO. 27 SALT WELL.

.....District, Kanawha County, W. Va.
 By Westvaco Chlorine Products Corp., South Charleston, W. Va.
 Elevation, 583.18'.

Drilled 100' east of Dunbar on Kanawha River bank.
 13-3/8" casing, 218'; 16" drive pipe, 44'; 10 3/4" casing, 809'.
 Drilled in Dec. 12, 1942. Standing level of water, 325'.
 Shooting record: 900-1015', 120 qts.; 1050-1195', 140 qts.;
 1220-1416', 190 qts.; total, 450 qts.

Drilled by Tom Ray of Huntington.
 Shot by E. I. du Pont, American Glycerin Division, Winchester, Ky.
 Record from Martens Sept. 16, 1944. Old File No. 1054.

	Top.	Bottom.
Surface	0	34
Sand and gravel	34	44
Blue slate	44	60
White slate	60	90
Sand (fresh water)	90	118
White slate	118	148
Coal	148	150
Gray sand	150	202
Black slate	202	212
Red sand	212	268
Gray slate	268	295
White sand	295	325
Slate and shale	325	360
White sand	360	395
Dark slate	395	425
Gray sand	425	460
Dark slate	460	550
Gray sand	550	558
Slate	558	679
White sand	679	697
Blue slate	697	720
Gray sand	720	775
Blue slate	775	795
Salt Sand (pay at 900')	795	960
Slate	960	965
Salt Sand (pay)	965	1015
Slate	1015	1023
Salt Sand (pay)	1023	1050
Salt Sand (pay)	1050	1195
Slate and sand	1195	1220
Sand	1220	1315
Slate	1315	1320
Salt Sand (pay)	1320	1416
Little lime	1416	1418
Total depth		1418