



New Location:    
 Drill Deeper:    
 Abandonment:

Company Godfrey L. Cabot Inc   
 Address 900 Union Bldg Charleston Wva   
 Farm J.L. McLean Hrs   
 Tract \_\_\_\_\_ Acres 160 Lease No. 3-463   
 Well (Farm) No. 24 Serial No. 1081   
 Elevation (Spirit Level) 779.76   
 Quadrangle Kenna   
 County HANAWHA District Union   
 Engineer Ray Bostow   
 Engineer's Registration No. \_\_\_\_\_   
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_   
 Date 10-26-42 Scale 1" = 1320'

STATE OF WEST VIRGINIA   
 DEPARTMENT OF MINES   
 OIL AND GAS DIVISION   
 CHARLESTON

WELL LOCATION MAP   
 FILE NO. KAN-979

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.   
 - Denotes one inch spaces on border line of original tracing.

*Deep Well*

WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Permit No. Kan 979

Dry Hole  
CASING & TUBING

Kenna Quad.				
Company	Godfrey L. Cabot, Inc.			
Address	Charleston, W.Va.	13 3/8	233	
Farm	J. L. McLean Hrs. Acres 160	10	724	
Location		8 5/8	1986	
Well No	#24-Ser 1081 Elev. 779.76	7	4818	
District	Union Kanawha County			
Surface		10 1/2	coupling shoe	
Mineral		8 5/8	Spang B.H. Packer	
Commenced	Jan. 4, 1943	7 OD	Spec. Orisk. B.H.	
Completed	April 7, 1943	Packer	28 bags aquagel	
Volume	49 MCF A. Shot			
Rock Pressure	None		Not tubed	
Date shot	April 8, 1943 4900-4915' with 30 qts.			
	B.S. 21 MCF 1 hrs. A.S. 49 MCF			
Fresh Water				
Salt Water	980-95 5 blrs. pr. hr.; 1425-30 6 blrs. pr. hr.			
	S.W. 1430-40 H.F.			

Soil	0	10	Slate & Shells	1990	2370
Red Rock	10	30	Brown Shale	2370	2393
Sand	30	40	Berea Grit	2393	2425
Blue Mud	40	60	Slate & Shells	2423	3590
Red Rock	60	69	Brown Shale	3590	3665
White Sand	69	79	Slate & Shells	3665	3846
Red Rock	79	89	Dark Shale	3846	3956
Slate	89	100	White Shale	3956	4006
Red Rock	100	120	Brown Shale	4006	4124
Slate	120	190	White Shale	4124	4540
White Sand	190	210	Brown Shale	4540	4768
Slate & Shells	210	350	Black Lime	4768	4798
Red Rock	350	400	Corniferous Lime	4798	4898
Slate & Shells	400	434	Oriskany Sand	4898	4960
Red Rock	434	452	Lime	4960	
Slate & Shells	452	478	TOTAL DEPTH		SLM 4960
Red Rock	478	498			
Slate & Shells	498	595	Show gas 1940-44'		
Red Rock	595	612	Show gas 3722'		
Lime	612	629			
Red Rock	629	656			
Sand	656	695	4902	103 M	
Slate, Dark	695	705	4904	84 M	
Red Rock	705	720	4812	84 M	
Slate & Shells	720	750	4919	60 M	
Sand	750	800	4926	60 M	
Slate & Shells	800	805	4930	33 M	
Lime	805	855	4960	33 M	
Slate & Shells	855	860			
Sand	860	900			
Dark Shale	900	905			
Sand	905	920			
Slate	920	925	Gauge before shot	24 M	
Sand	925	942	5' A.S.	146 M	
Slate & Shells	942	970	10 "	103 M	
White Sand	970	1020	15 "	84 M	
Slate	1020	1027	20 "	53 M	
Sand	1027	1048	60"	49 M	
Slate	1048	1051			
Sand	1051	1115			
Slate	1115	1180			
Sand	1180	1330			
Slate & Shells	1330	1385			
Salt Sand	1385	1722			
Little Lime	1722	1748			
Black Slate	1748	1750			
Big Lime	1750	1905			
Injun Sand	1905	1961			
Black Slate	1961	1963			
Gray Lime	1963	1990			

4798 4898 4960  
 780  


---

 4018 4118 4180