

STATE OF WEST VIRGINIA
DEPARTMENT OF ENVIRONMENTAL PROTECTION
OFFICE OF OIL AND GAS



ORIGINAL

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE IN TRIPLICATE, one copy mailed to the Department, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Farm name: Dickinson, Sallie J Operator Well No.: 809083

LOCATION: Elevation: 1502.94' Quadrangle: Mammoth
District: Elk County: Kanawha
Latitude: 42 Feet South of 39 Deg. 324 Min. 2 Sec.
Longitude: 46 Feet West of 81 Deg. 87 Min. 53 Sec.

Well Type: OIL _____ GAS X

Company	<u>Diversified Producon, LLC</u>	Coal Operator	<u>HC Dickinson, LLC C/O MC Hager Inc</u>
	<u>PO Box 6070</u>	or Owner	<u>PO Box 14744</u>
	<u>Charleston, WV 25362</u>		<u>Richmond, Va 23221</u>
Agent	<u>Jeff Mast</u>	Coal Operator	<u>Kanawha Energy Company</u>
Permit Issued Date	<u>5-25-21</u>	or Owner	<u>PO Box 11174</u>
			<u>Charleston, WV 25311</u>

AFFIDAVIT

STATE OF ~~WEST VIRGINIA~~, KY
County of Floyd ss:

Rodney Osborne and Estill Johnson being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by the above named well operator, and participated in the work of plugging and filling the above well say that said work was commenced on the 15 day of July, 2021, and the well was plugged and filled in the following manner:

TYPE	FROM	TO	PIPE REMOVED	LEFT
See Attachment A			2033' 3 1/2" plus packer	32' of 10"
				651' of 8 1/4"
				1977' of 7"

Description of monument: 7" casing w/ API # 36" above ground and that the work of plugging and filling said well was completed on the 21 day of July, 2021.

And further deponents saith not. [Signature]
Estill Johnson

Sworn and subscribe before me this 22 day of July, 2021

My commission expires: 02/04/2022

Stella M. Slove
Notary Public



Affidavit reviewed by the Office of Oil and Gas: [Signature] Title: Inspector Decker

09/17/2021

Attachment A

809083

47-039-01765

Dickinson, Sallie J.



Bottom	Top	Actual TOC	Sks of Cement
2028'	1950'	1869'	30
1496'	1390'	1376'	35
1109'	1000'	992'	32
850'	611'	591'	78
498'	392'		50
303'	197'		50
102'	Surface	303'	114
296'	Surface		95

Perforated 7" casing with 2 holes each @ 1490', 1440', 1400', 1100', 1050', 1000', 840', 790', 750', 711', 661', 620', 492', 452', 412', 297', 247', 207', 100', 50'

Arny W. Miller - Inspector Odegas
7-22-21

09/17/2021