

Cabin Creek District, Kanawha County, W. Va.
 By Virginian Gasoline & Oil Co., Charleston, W. Va.
 On 8000 acres, surface and mineral rights owned by David Ward Heirs,
 Benj. B. Brown, Atty. in fact, Kanawha Valley Bank Bldg.,
 Charleston, W. Va.

Well drilled previous to June 1, 1929.

No elevation given.

13" conductor, 16'; 10", 400'; 8 $\frac{1}{4}$ ", 1310'; 6-5/8", 1614'; 5-3/16", 1703'.

Coal was encountered at 280-285 and 350-357'.

Abandonment reported to Dept. of Mines June 30, 1931.

Producing hole.

	Top.	Bottom.	Thickness.
Soil	0	- 20	20
Slate	20	- 80	60
Sand	80	- 115	35
Slate	115	- 180	65
Sand	180	- 225	45
Slate	225	- 280	55
Coal	280	- 285	5
Slate	285	- 320	35
Sand	320	- 350	30
Coal	350	- 357	7
Slate and shells	357	- 425	68
Sand	425	- 480	55
Slate	480	- 552	72
Sand	552	- 600	48
Slate	600	- 625	25
Sand	625	- 700	75
Lime	700	- 730	30
1st Salt Sand	730	- 865	135
Slate and shells	865	- 930	65
2nd Salt Sand	930	- 1106	176
Slate	1106	- 1140	34
3rd Salt Sand	1140	- 1225	85
Slate	1225	- 1280	55
Red rock	1280	- 1310	30
Sand	1310	- 1400	90
Slate	1400	- 1520	120
Red rock	1520	- 1550	30
Sand	1550	- 1580	30
Pencil Cave	1580	- 1600	20
Little Lime	1600	- 1630	30
Pencil Cave	1630	- 1640	10
Black lime	1640	- 1663	23
Big Lime	1663	- 1853	190
Big Injun Sand	1853	- 1893	40
Slate	1893	- 1910	17
Weir Sand (gas, 1930, 1940') (oil, 2077, 2086)	1910	- 2096	186
Total depth		2100	