

Elk District, Kanawha County, W. Va.

By W. Va. Gas Corp., Charleston, W. Va.

On 85 $\frac{1}{2}$ acres, on Silken Branch; surface and mineral rights owned by
W. H. Vickers, Frame, W. Va.

Well was completed Sept. 21, 1925.

Elevation, 900' O.T.B.

10" conductor, 15' (left in); 8 $\frac{1}{2}$ "¹/₂, 490 $\frac{1}{2}$ ' (left in); 6-5/8", 1729'
(left in); 3" tubing, 1859' 11".Heater packer, set at 1757 $\frac{1}{2}$ ' (no record of size).

No coal was encountered.

Abandonment reported to Dept. of Mines Sept. 22, 1931.

No record of shot.

	Top.	Bottom.	Thickness.
Clay	0	- 36	36
Sand	36	- 40	4
Red rock	40	- 195	150
Sand	195	- 225	30
Slate	225	- 275	50
Sand	275	- 295	20
Slate	295	- 320	25
Lime sand	320	- 360	40
Slate and shells	360	- 475	115
Dunkard Sand	475	- 575	100
Slate	575	- 600	25
Sand	600	- 660	60
Slate	660	- 740	80
Lime shells	740	- 820	80
Sand	820	- 890	70
Slate	890	- 965	75
Lime shells	965	- 1045	80
Sand	1045	- 1090	45
Slate and shells	1090	- 1180	90
Salt Sand	1180	- 1620	440
Maxton Sand	1620	- 1668	48
Break	1668	- 1675	7
Little Lime	1675	- 1685	10
Pencil Cave	1685	- 1690	5
Big Lime (gas, 1814')	1690	- 1844 $\frac{1}{2}$ '	154 $\frac{1}{2}$ '
Big Injun Sand (gas, 1844 $\frac{1}{2}$ '-1858 $\frac{1}{2}$ ')	1844 $\frac{1}{2}$ '	- 1859 $\frac{1}{2}$ '	15
Total depth		1859 $\frac{1}{2}$ '	