

Elk District, Kanawha County, W. Va.  
 By Virginian Gasoline & Oil Co., Charleston, W. Va.  
 On 60 acres, surface and mineral rights owned by Mrs. Carrie  
 Jeffers et al., 211 Spring St., Charleston, W. Va.  
 Drilled previous to June 1, 1929.  
 Elevation, 738.6' L.  
 13" conductor, 16'; 6-5/8" casing, 1559'.  
 Callanan packer, 6-5/8 x 8.  
 Coal was encountered at 320-322, 400-405, and 490-492'.  
 Abandonment reported to Dept. of Mines June 4, 1934.  
 Well was shot at 1804-1811 $\frac{1}{2}$ ' and 1810 $\frac{1}{2}$ -1818'.  
 No record of water.  
 Producing hole.

	Top.	Bottom.	Thickness.
Clay and shale	0	- 320	320
Coal	320	- 322	2
Shale	322	- 400	78
Coal	400	- 405	5
Shale	405	- 490	85
Coal	490	- 492	2
Slate and shale	492	- 860	368
Salt Sand	860	- 1360	500
Pink rock	1360	- 1370	10
Limy sand	1370	- 1430	60
Maxton Sand	1430	- 1470	40
Sand and lime	1470	- 1500	30
Slate	1500	- 1505	5
Lime	1505	- 1531	26
Slate	1531	- 1536	5
Lime	1536	- 1542	6
Slate	1542	- 1544	2
Big Lime	1544	- 1726	182
Red rock	1726	- 1746	20
Shelly slate	1746	- 1782	36
Lime and shells	1782	- 1802	20
Squaw Sand (oil, 1810-1818')	1802	- 1818	16
Total depth			1818