

KAN-136-A

Cabin Creek District, Kanawha County, W. Va.

By Virginian Gasoline &amp; Oil Co., Charleston, W. Va.

On lot; mineral rights owned by Virginian Gasoline & Oil Co.,  
Charleston, W. Va.

Drilled previous to June 1, 1929.

Elevation, 760' B.

13" conductor, 25'; 10" casing, 250'; 8 $\frac{1}{2}$ ", 1196'; 6-5/8", 1525'.

Coal was encountered at 225-230'.

Abandonment reported to Dept. of Mines June 15, 1934.

No record of shot. No record of water.

Producing hole.

	Top.	Bottom.	Thickness.
Gravel	0	25	25
Lime shell	25	35	10
Slate shells	35	130	95
Lime, gritty	130	175	45
Slate, black	175	225	50
Coal	225	230	5
Slate shells	230	250	20
Lime	250	310	60
Slate shells	310	400	90
Slate	400	440	40
Lime	440	485	45
Slate	485	515	30
Sand, white	515	575	60
Shells	575	600	25
Salt Sand	600	730	130
Break	730	790	60
Salt Sand	790	930	140
Slate break	930	970	40
Salt Sand	970	1065	95
Sand, white	1065	1070	5
Lime, white	1070	1100	30
Slate, black	1100	1120	20
Lime, hard	1120	1160	40
Slate shells, blue	1160	1180	20
Sand, Gas	1180	1196	16
Sand, Gas	1196	1255	59
Rock, hard	1255	1270	15
Slate, black	1270	1280	10
Maxton Sand	1280	1320	40
Slate shells	1320	1415	95
Little Lime	1415	1480	65
Slate, black	1480	1490	10
Lime shell, white	1490	1500	10
Pencil Cave	1500	1505	5
Big Lime	1505	1705	200
Big Injun Sand	1705	1730	25
Slate shells	1730	1751	21
Weir Sand (gas, 1766'; oil, 1898 and 1934')	1751	1944	193
Black line, to bottom	1944	1946	2