



New Location   
 Drill Deeper   
 Abandonment

JUN - 9 1941

# 1 (2831)	2.102 W
	4.4 Q
# 2 (2835)	1.89 W
	4.53 Q

Company VIRGINIAN GASOLINE & OIL CO.  
 Address CHARLESTON, W.VA.  
 Farm JOHN MITCHELL  
 Tract Acres 72 Lease No. 774  
 Well (Farm) No. 1 & 2 Serial No. 2835  
 Elevation (Spirit Level) 2831-825 2835-810  
 Quadrangle CLENDENIN  
 County KANAWHA District ELK  
 Engineer's Registration No. 659  
 File No. 70-65 Drawing No. \_\_\_\_\_  
 Date MAY 28, 1941 Scale 1"=660'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. KAN-320A & 321A  
2831 2835

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 - Denotes one inch spaces on border line of original tracing.

JOHN MITCHELL VIRGINIAN GASOLINE & OIL CO. KAN-320A-205, 1 (2831) and 2 (2835) - & OIL Co. - KAN-321A-6-6-217

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

893

Ab 300-A

WELL RECORD

Permit No. \_\_\_\_\_ Oil or Gas Well \_\_\_\_\_ (KIND) Oil

Company Virginian Gasoline & Oil Co.  
Address Box 1626, Charleston, West Virginia  
Farm John Mitchell #1 Acres 72  
Location (waters) Blue Creek  
Well No. 2831 Elev. 825.0  
District Elk County Kanawha  
The surface of tract is owned in fee by H. S. Naylor, et al.  
Address Three Mile, W. Va.  
Mineral rights are owned by Same  
Address \_\_\_\_\_  
Drilling commenced January 28, 1912  
Drilling completed March 14, 1912  
Date shot \_\_\_\_\_ Depth of shot 1829  
Open Flow \_\_\_\_\_ /10ths Water in \_\_\_\_\_ Inch  
\_\_\_\_\_ /10ths Merc. in \_\_\_\_\_ Inch  
Volume \_\_\_\_\_ Cu. Ft.  
Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
Oil 720 bbls., 1st 24 hrs.  
Fresh water No Record feet \_\_\_\_\_ feet  
Salt water " " feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16			Kind of Packer
13			
10	48	48	Size of
8 1/4	540	Pulled	
6 5/8	1596	1596	Depth set
5 3/16			
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_  
COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Shale			500	520			
Lime			520	545			
Black Shale			545	590			
Sand			590	625			
Shale & Lime			625	880			
Salt Sand			880	1370			
Lime			1370	1390			
Red Rock			1390	1400			
Shale			1400	1431			
Lime			1431	1436			
Shale			1436	1530			
Lime & Shale			1530	1554			
Slate			1554	1558			
Lime			1558	1560			
Shale			1560	1563			
Lime			1563	1578			
Shale			1578	1590			
Big Lime			1590	1760			
Shale			1760	1764			
Red Rock			1764	1768			
Shale & Shells			1768	1812			
Dark Lime			1812	1828			
Oil Sand			1828	1850			
Total Depth			1850			1828	Flowing



