



COAL NOT OPERATED

S 1.66  
W 3.21

New Location   
 Drill Deeper   
 Abandonment

Company KREBS OIL CO., INC.  
 Address CHARLESTON NAT. BANK BLDG.  
CHAS. W. VA.  
 Farm NUMA BLOCK COAL CO.  
 Tract \_\_\_\_\_ Acres 1025 Lease No. \_\_\_\_\_  
 Well (Farm) No. 3 Serial No. 712  
 Elevation (Spirit Level) 775  
 Quadrangle CLENDENIN  
 County KANAWHA District ELK  
 Engineer E. J. Krebs  
 Engineer's Registration No. 773  
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
 Date 9-7-50 Scale 1" - 1320'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

**WELL LOCATION MAP**  
 FILE NO. KAN-775-A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.



NUMA BLOCK COAL CO. NO. 3 WELL.

775A

Elk District, Kanawha County, W. Va.  
 By Krebs Oil Co., Inc., Box 213, Charleston, W. Va.  
 Abandoned under permit Kan-.....-A?  
 On 1025 acres, on Blue Creek.  
 Elevation, 775' L.  
 Drilling commenced Aug. 14, 1915; completed Oct. 4, 1915.  
 8 $\frac{1}{4}$ " casing, 440' (pulled); 6 $\frac{5}{8}$ ", 1470'.  
 Salt water, 775'.  
 Well shot 10-5-15, with 80 qts., at 1760-1780'.  
 1st gas, 1758'. Oil, 1766-1776'.  
 Oil well. Record to Dept. of Mines not dated or stamped.  
 Record to RCT from Mrs. Griffith June 24, 1951. Old File No. 1546.

|                               | Top. | Bottom. |
|-------------------------------|------|---------|
| Conductor                     | 0    | 16      |
| Sand                          | 16   | 160     |
| Slate                         | 160  | 200     |
| Sand                          | 200  | 240     |
| Slate                         | 240  | 300     |
| Sand                          | 300  | 380     |
| Slate                         | 380  | 405     |
| Stray lime                    | 405  | 440     |
| Slate                         | 440  | 525     |
| Sand                          | 525  | 645     |
| Slate                         | 645  | 655     |
| Sand                          | 655  | 680     |
| Slate and shells              | 680  | 770     |
| Salt Sand (break, 1000-1015') | 770  | 1210    |
| Sand and lime shells          | 1210 | 1315    |
| Red rock                      | 1315 | 1335    |
| Lime                          | 1335 | 1355    |
| Slate                         | 1355 | 1360    |
| Maxton Sand                   | 1360 | 1390    |
| Slate                         | 1390 | 1396    |
| Little Lime                   | 1396 | 1428    |
| Slate                         | 1428 | 1433    |
| Gray lime                     | 1433 | 1445    |
| Pencil Cave                   | 1445 | 1449    |
| Big Lime                      | 1449 | 1600    |
| Big Injun Sand                | 1600 | 1620    |
| Slate and shells              | 1620 | 1690    |
| Squaw Sand                    | 1690 | 1705    |
| Slate                         | 1705 | 1713    |
| Weir Sand                     | 1713 | 1855    |
| Total depth                   |      | 1858    |





1546

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

WELL RECORD

Permit No. Ab 775-A Oil or Gas Well  (KIND)

Company Krebs Oil Company, Inc.  
 Address Box 213 - Charleston, W. Va.  
 Farm Nuna Block Coal Co. Acres 1025  
 Location (waters) Blue Creek  
 Well No. 3 Elev. 775.'  
 District Elk County Kanawha  
 The surface of tract is owned in fee by \_\_\_\_\_  
 Address \_\_\_\_\_  
 Mineral rights are owned by \_\_\_\_\_  
 Address \_\_\_\_\_  
 Drilling commenced August 14, 1915  
 Drilling completed October 4, 1915  
 Date Shot \_\_\_\_\_ From \_\_\_\_\_ To \_\_\_\_\_  
 With \_\_\_\_\_  
 Open Flow /10ths Water in \_\_\_\_\_ Inch  
 /10ths Merc. in \_\_\_\_\_ Inch  
 Volume \_\_\_\_\_ Cu. Ft.  
 Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
 Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
 Fresh water \_\_\_\_\_ feet \_\_\_\_\_ feet  
 Salt water \_\_\_\_\_ feet \_\_\_\_\_ feet

| Casing and Tubing | Used in Drilling | Left in Well | Packers        |
|-------------------|------------------|--------------|----------------|
| Size              |                  |              | Kind of Packer |
| 16                |                  |              |                |
| 13                |                  |              |                |
| 10                |                  |              | Size of        |
| 8 1/4             | 440'             |              |                |
| 6 5/8             | 1470'            | 1470'        | Depth set      |
| 5 3/16            |                  |              |                |
| 3                 |                  |              | Perf. top      |
| 2                 |                  |              | Perf. bottom   |
| Liners Used       |                  |              | Perf. top      |
|                   |                  |              | Perf. bottom   |

CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_  
 COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES

| Formation          | Color | Hard or Soft | Top  | Bottom | Oil, Gas or Water | Depth Found | Remarks                        |
|--------------------|-------|--------------|------|--------|-------------------|-------------|--------------------------------|
| Conductor          |       |              |      | 16     |                   |             |                                |
| Sand               |       |              | 16   | 160    |                   |             |                                |
| Slate              |       |              | 160  | 200    |                   |             |                                |
| Sand               |       |              | 200  | 240    |                   |             |                                |
| Slate              |       |              | 240  | 300    |                   |             |                                |
| Sand               |       |              | 300  | 380    |                   |             |                                |
| Slate              |       |              | 380  | 405    |                   |             |                                |
| Stray Lime         |       |              | 405  | 440    |                   |             |                                |
| Slate              |       |              | 440  | 525    |                   |             |                                |
| Sand               |       |              | 525  | 645    |                   |             |                                |
| Slate              |       |              | 645  | 655    |                   |             |                                |
| Sand               |       |              | 655  | 680    |                   |             |                                |
| Slate & shells     |       |              | 680  | 770    |                   |             |                                |
| Salt Sand          |       |              | 770  | 1210   |                   |             | Salt water 775'                |
| Sand & Lime Shells |       |              | 1210 | 1315   |                   |             | Break in Salt Sand 1000'-1015' |
| Red Rock           |       |              | 1315 | 1335   |                   |             |                                |
| Lime               |       |              | 1335 | 1355   |                   |             |                                |
| Slate              |       |              | 1355 | 1360   |                   |             |                                |
| Maxon Sand         |       |              | 1360 | 1390   |                   |             |                                |
| Slate              |       |              | 1390 | 1396   |                   |             |                                |
| Little Line        |       |              | 1396 | 1428   |                   |             | Well shot - 10/5/15            |
| Slate              |       |              | 1428 | 1433   |                   |             | with 80 qts.                   |
| Grey Lime          |       |              | 1433 | 1445   |                   |             | Do                             |
| Pencil Cave        |       |              | 1445 | 1449   |                   |             |                                |
| Big Lime           |       |              | 1449 | 1600   |                   |             |                                |
| Injun Sand         |       |              | 1600 | 1620   |                   |             |                                |
| Slate & shells     |       |              | 1620 | 1690   |                   |             |                                |
| Squaw Sand         |       |              | 1690 | 1705   |                   |             |                                |
| Slate              |       |              | 1705 | 1713   |                   |             |                                |
| Weir Sand          |       |              | 1713 | 1855   |                   |             | 1st gas 1758                   |
|                    |       |              |      |        |                   |             | Oil 1760'-1776'                |
|                    |       |              |      |        |                   |             | top of shot 1760'              |
|                    |       |              |      |        |                   |             | bottom of shot 1780'           |
| Total Depth        |       |              |      | 1855'  |                   |             |                                |