

*no flat*



2023

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

WELL RECORD

Quadrangle \_\_\_\_\_

Permit No. KAN 1261 A

Oil or Gas Well (KIND)

Company Gas, Coal Oil Company  
 Address c/o Mr. H. M. Brawley, Charleston, W. Va.  
 Farm Susan S. Brawley Heirs Acres \_\_\_\_\_  
 Location (waters) \_\_\_\_\_  
 Well No. 2 Elev. \_\_\_\_\_  
 District Big Sandy County Kanawha  
 The surface of tract is owned in fee by \_\_\_\_\_  
 Address \_\_\_\_\_  
 Mineral rights are owned by \_\_\_\_\_  
 Address \_\_\_\_\_  
 Drilling commenced July 6, 1915  
 Drilling completed August 30, 1915  
 Date Shot \_\_\_\_\_ From \_\_\_\_\_ To \_\_\_\_\_  
 With \_\_\_\_\_  
 Open Flow \_\_\_\_\_ /10ths Water in \_\_\_\_\_ Inch  
 \_\_\_\_\_ /10ths Merc. in \_\_\_\_\_ Inch  
 Volume \_\_\_\_\_ Cu. Ft.  
 Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
 Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
 Fresh water \_\_\_\_\_ feet \_\_\_\_\_ feet  
 Salt water \_\_\_\_\_ feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16 Conductor - left in hole			Kind of Packer _____
18			
10	107'	107'	Size of _____
8 1/4	567'	Pulled	
6 5/8	1267'	1267'	Depth set <u>1338'</u>
5 3/16			
3			Perf. top _____
2			Perf. bottom _____
Liners Used			Perf. top _____
			Perf. bottom _____

CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_

COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Drift				18			
Sand			18	20			
Coal			20	22			
Sand			22	62			
Slate			62	72			
Sand			72	140			
Slate and shells			140	403			
Sand			403	438			
Slate			438	535			
Sand			535	570			
Salt sand			570	1202	Little oil and gas	615'	
Break in salt sand	1000' - 2'						
Little lime			1202	1231			
Slate			1231	1237			
Shells			1237	1242			
Pencil Cave			1242	1255			
Big lime			1255	1375			
Injun sand			1375	1421			
Red rock			1421	1455			
Black slate							
Total Depth				1461			
					Gas	1349-1356'	
					Gas	1382-1392'	
					Gas	1412-1418'	
					Packer set at 1338'		
					Anchor below perforation 40'		
					62' from perforation to packer.		
					Perforation 20'		
					(Later changes in cleaning out)		
					Moved perforation one joint in		

DEC 6 1957