



BENCH MARK DESCRIPTION

U.E. "D" in The Bride Abutment
 Over Cabin Crk. East Side Of Creek
 South End Of Abutment On Side Road
 Off Main State Route Near Mouth Of
 Paint Br.

DEGREE OF ACCURACY

One Part in 200

- New Location
- Drill Deeper
- Abandonment

oil
 Seybert R. Jewell

Company THE PRESTON OIL CO.
 Address CHARLESTON, W. VA.
 Farm J. D. KITTINGER
 Tract _____ Acres 39 Lease No. 27189
 Well (Farm) No. 6 Serial No. 3313
 Elevation (Spirit Level) 1294.98'
 Quadrangle MONTGOMERY - WC
 County KANAWHA District CABIN CRK.
 Engineer Seybert R. Jewell
 Engineer's Registration No. 2529
 File No. 72-45 Drawing No. _____
 Date SEPT. 25, 1964 Scale 1" = 400'

STATE OF KENTUCKY
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 LEXINGTON

WELL LOCATION MAP
 FILE NO. KAN-1354-A
 Was 70060

+ Denotes location of well on United States
 Topographic Maps, scale 1 to 62,500, lat-
 itude and longitude lines being represented
 by border lines as shown.

- Denotes one inch spaces on border line
 of original tracing.

Cabin Creek District, Kanawha County, W. Va.
 By The Ohio Fuel Oil Co. (Virginian Gasoline & Oil Co.)
 On lease No. 1986; 39 acres.
 Drilling contractor, D. M. Close, Charleston, W. Va.
 Commenced June 29, 1917; completed Nov. 3, 1917.
 Drillers: Harry Sheff, R. L. Jayne.
 Conductor, 12"; 10" casing, 823'; 8 $\frac{1}{2}$ ", 1767'; 6 $\frac{5}{8}$ ", 2404'; all left in.
 Shot Nov. 3, 1917, with 120 qts.
 Oil well.

	Top.	Bottom.	Thickness.
Sand slate	0 -	80	80
Coal	80 -	82	2
Sandy lime	82 -	142	60
Sand	190 -	240	50
Lime sand	240 -	247	7
Slate and sand shells	247 -	340	93
Sand	340 -	370	30
Slate	370 -	385	15
Sand and slate	385 -	659	274
Coal	659 -	663	4
Slate	663 -	669	6
Lime and sand	669 -	950	281
Big Dunkard Sand	950 -	1005	55
Slate	1005 -	1025	20
Sandy lime	1025 -	1206	181
Gramphis Sand	1206 -	1320	114
Slate	1320 -	1410	90
Salt Sand (hole full of water at 1510')	1410	1670	260
White slate	1670 -	1690	20
Lime	1690 -	1735	45
Black slate	1735 -	1742	7
Lime	1742 -	1858	116
Red rock	1868 -	1893	35
Slate and lime shells	1893 -	2075	182
Lime	2075 -	2150	75
Maxton Sand (3 bailers of water an hour at 2170')	2150 -	2240	90
Little Lime	2240 -	2375	135
Big Lime	2375 -	2550	175
Big Injun Sand	2550 -	2590	40
Slate and shells	2590 -	2720	130
Weir Sand	2720 -	2750	30
Slate and shell	2750 -	2974	224
Berea Grit Sand (first oil, 2994'; second pay, 3005')	2974 -	3014	40
Total depth		3017	