

LATITUDE

LONGITUDE

7'5 OGIS topo location

7.5' loc \_\_\_\_\_ 15' loc \_\_\_\_\_  
\_\_\_\_\_ (calc.) \_\_\_\_\_

Company \_\_\_\_\_

Farm Kelley Axe Co #1

Quad \_\_\_\_\_

County \_\_\_\_\_

District \_\_\_\_\_

WELL LOCATION MAP

File No. 039-70054

70054

Kan?

KELLY ABE CO. WELL #1 - Completed March 15, 1935

Gravel	0	55
Sand	55	90
Slate	90	150
Coal	150	152
Sand	152	270
Slate	270	315
Coal	315	317
Sand	317	360
Slate & Shells	360	525
Lime	525	570
Slate	570	612
Coal	612	614
Lime	614	640
Slate & Shells	640	700
Lime	700	740
Slate & Shells	740	780
Salt Sand	780	1140
Slate & Shells	1140	1200
Maxon Sand	1200	1280
Slate	1280	1300
Lime	1300	1530
Slate	1330	1535
Sandy Lime	1335	1575
<del>Lime</del> Lime	1575	1417
Pencil Cave	1417	1427
Big Lime	1427	1602
Slate	1602	1615
Big Injun	1615	1645
Slate & Shells	1645	2055
Hard Shell	2055	2060
Brown Shale	2060	2075
Berea	2075	2090
Slate & Shells	2090	2110
Hard Lime	2110	2125
Slate & Shells	2125	2365
Sand	2365	2380
Slate & Shells	2380	2455
Sand Shell	2455	2470
Slate & Shells	2470	2915
Hard Shell	2915	2925
Slate & Shells	2925	3275
Lime	3275	3286
Brown Shale	3286	3330
Slate & Shells	3330	3380
Lime	3380	3450
Slate & Shells	3450	3570
Sandy Shale	3570	3610

Sand Shell	3610	3615
Slate & Shells	3615	3645
Brown Shale	3645	3850
Black Slate	3850	4000
TOTAL DEPTH		4000

	<u>Casing</u> <u>Used</u>	<u>Left</u> <u>In Well</u>
13"	59	59
10"	278	110
8 1/2"	1435	1435
6-5/8"	2055	None

Shot with 100 qts. in Brown Sandy Shale at 3585 ft. Gas increased from 2/10 Water 1" to 10/10 W. 1"

Tubed with 686 ft. of 3" anchor and 151 ft. 3" above Packer Balance 2" to top of hole

Packer set at 2915 ft.

Perforation 42 ft. from bottom

Hole filled to 3605

21 ft. pocket below bottom of shot

8 sacks Cement on top Packer

*Filed*