


LATITUDE

38° 30'

LONGITUDE 81° 25'


 5.37 S
 3.68 W
 15' location

7.5 OGIS topo location

7.5' loc _____ 15' loc _____
 _____ (calc.) _____

Company Ohio Fuel

Farm J F Thumm 1

Quad Clendenin 15'

County Kanawha

District EIK

WELL LOCATION MAP

File No. 40132 70188

#99 in 1914 WVGES
Kanawha County Report

Walter Morris No. 1 Well Record (784).

Located in Elk district, on Turkey Fork of Indian Creek. Completed Dec. 25, 1912. Authority, United Fuel Gas Company. Elevation, 900' A. T. B.

| | Thickness Feet. | Total Feet. |
|-------------------------------|--------------------|----------------|
| Unrecorded | | |
| Slate | 16 | 16 |
| Sand | 64 | 80 |
| Slate | 40 | 120 |
| Sand | 40 | 160 |
| Coal, Stockton-Lewiston | 90 | 250 |
| Slate | 4 | 254 |
| Sand | 21 | 275 |
| Slate | 25 | 300 |
| Sand | 40 | 340 |
| Slate | 60 | 400 |
| Sand | 50 | 450 |
| Slate | 50 | 500 |
| Sand | 125 | 625 |
| Lime and shells | 50 | 675 |
| Salt sand | 25 | 700 |
| Slate | 240 | 940 |
| Coal | 5 | 945 |
| Slate | 4 | 949 |
| Second Salt sand | 4 | 953 |
| Slate | 267 | 1220 |
| Sand | 10 | 1230 |
| Slate | 90 | 1320 |
| Red rock | 8 | 1328 |
| Slate | 12 | 1340 |
| Sand, Maxton | 8 | 1348 |
| Little Lime | 32 | 1380 |
| Slate break | 45 | 1425 |
| Lime | 8 | 1433 |
| Pencil cave | 10 | 1443 |
| Big Lime | 4 | 1447 |
| Slate | 158 | 1605 |
| Sand, Squaw | 90 | 1695 |
| Slate | 7 | 1702 |
| Sand, Weir | 15 | 1717 |
| Slate to bottom | 25 | 1742 |
| | 70 | 1812 |

"Oil well; gas 1504', 1569', 1700; oil 1767'-1795'; water at 280', 750' 820'."

Thumm Heirs No. 6 Well Record (99).

Located in Elk district on Pinch Creek, one-half mile east of Pinchton. Completed July 10, 1912. Authority, Ohio Fuel Oil Company. Elevation, 688' L.

| | Thickness Feet. | Total Feet. |
|-----------------|--------------------|----------------|
| Conductor | | |
| Sand | 16 | 16 |
| | 180 | 196 |

| | Thickness Feet. | Total Feet. |
|-------------------------|--------------------|----------------|
| Coal, Stockton | 3 | 199 |
| Black lime | 24 | 223 |
| Sand | 47 | 270 |
| Slate | 15 | 285 |
| Slate | 3 | 288 |
| Coal, Winifrede ? | 12 | 300 |
| Lime | 20 | 320 |
| Slate and shells | 40 | 360 |
| Sand | 25 | 385 |
| Slate and lime | 40 | 425 |
| Sand | 5 | 430 |
| Limestone | 3 | 433 |
| Coal, No. 2 Gas ? | 12 | 445 |
| Slate | 70 | 515 |
| Sand | 20 | 535 |
| Slate | 45 | 580 |
| Sand | 20 | 600 |
| Slate | 40 | 640 |
| Sand | 22 | 662 |
| Slate and shells | 48 | 710 |
| Sand | 30 | 740 |
| Slate | 50 | 790 |
| Black lime | 20 | 810 |
| Slate | 505 | 1315 |
| Salt sand..... | 8 | 1323 |
| Slate | 5 | 1328 |
| Red rock | 62 | 1390 |
| Limestone | 5 | 1395 |
| Soft slate | 63 | 1458 |
| Sand, Maxton | 25 | 1483 |
| Little Lime | 2 | 1485 |
| Slate | 3 | 1488 |
| Lime | 3 | 1491 |
| Slate | 21 | 1512 |
| Lime | 7 | 1519 |
| Pencil cave..... | 146 | 1665 |
| Big Lime | 10 | 1675 |
| Black lime | 10 | 1685 |
| Red rock | 70 | 1755 |
| Slate and shells | 13 | 1768 |
| Oil sand | 3 | 1771 |
| Shale to bottom | | |

"Oil well; hole full of water at 950 feet."

Jane O. Moles No. 1 Well Record (155).

Located in Elk district, 1¼ miles southwest of Blue Creek P. O.
Completed April 27, 1912. Authority, South Penn Oil Company. Ele-
vation, 1007' L.

| | Thickness Feet. | Total Feet. |
|------------------|--------------------|----------------|
| Unrecorded | 1129 | 1129 |
| Salt sand | 472 | 1601 |
| Unrecorded | 36 | 1637 |