


LATITUDE 39° 5' 00"

00, 02, 08 LONGITUDE



7'5 OGIS topo location

7.5' loc 277S 15' loc _____
' 2.06 W (calc.) _____

Company _____

Farm _____

Quad CAMDEN 7 1/2'

County LEWIS

District FREEMANS CREEK

WELL LOCATION MAP

File No. 041-17A

Freemans Creek District, Lewis County, W. Va. 77A
 Reserve Gas Co., 445 W. Main St., Clarksburg, W. Va.
 On 150 acres, surface and mineral rights owned by George H.
 Jarvis, R.F.D., Weston, W. Va.
 Drilled prior to June 1, 1929.
 Elevation, 1196' L.
 10" casing, 158'; 8 $\frac{1}{2}$ " casing, 870'.
 Coal was encountered at 470-475'.
 Abandonment reported to Dept. of Mines Dec. 10, 1930.

	Top.	Bottom.
No record of formations overlying the coal seam.		
Little Dunkard Sand	525	- 575
Big Dunkard Sand	590	- 625
First Salt Sand	700	- 790
Lime	863	- 1000

10" casing set at 158'.
 8 $\frac{1}{2}$ " casing set at 870'.

No oil or gas encountered between the coal seam
 and the point where 8 $\frac{1}{2}$ " casing is set.

(RECORD INCOMPLETE)

AFFIDAVIT IN TRIPPLICATE TO TIME AND MANNER OF PLUGGING AND FILLING WELL

(REQUIRED BY SECTION 8, CHAPTER 22, ACTS 1929)

WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS SECTION

Jan 17A

No Coal Operations.

Reserve Gas Company

COAL OPERATOR

NAME OF WELL OPERATOR

445 West Main St.
Clarksburg, W. Va

COMPLETE ADDRESS

Coal Owner;
George H. Jarvis,
COAL OPERATOR
Weston, W. Va. R. F. D.

January, 10, 1931. 19

WELL AND LOCATION

Freemans Creek District
Lewis County

COAL OPERATOR

Well No. 816

ADDRESS

James Jarvis Farm

AFFIDAVIT TO BE MADE IN TRIPPLICATE; ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA.

COUNTY OF LEWIS

vs:

D. J. WHITE and CECIL KITTLE.

being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by RESERVE GAS COMPANY, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 2nd day of DECEMBER, 19 30, and that the well was plugged and filled in the following manner:

Manner in which sand was plugged: FILLED FROM 1229 TO 1186 WITH CLAY. SET ONE 8 1/2" WOOD BRY HOLE PLUG AT 1186. FILLED SOLID WITH CLAY TO 896. SET ONE 8 1/2" WOOD BRY HOLE PLUG AT 896. SET ONE 8 1/2" X 5 FOOT WOOD BRY HOLE PLUG AT 890. PUT IN 200 POUNDS OF LEAD WOOL FROM 890 TO 886. FILLED SOLID WITH CLAY TO 680. SET ONE 10" X 5 FOOT CEMENT PLUG FROM 680 TO 686. FILLED SOLID WITH CLAY TO 600. SET ONE 10" X 5 FOOT CEMENT PLUG AT 600 TO 597. FILLED SOLID WITH CLAY TO 506. FILLED WITH CEMENT FROM 506 TO 440. FILLED SOLID WITH CLAY TO 168. SET ONE 10" X 5 FOOT CEMENT PLUG FROM 168 TO 166. HOLES FILLED SOLID WITH CLAY FROM 168 TO SURFACE.
Manner in which coal was plugged:
FILLED WITH CEMENT FROM 506 TO 440.

Description of monument:

SET ONE CONCRETE MARKER IN A BLOCK OF CEMENT 3' X 3' X 3' SQUARE EXTENDING 30" ABOVE THE SURFACE OF THE GROUND. MARKER SUPPORTED BY 18 FEET OF 2" PIPE FOR VENT WITH ONE 2" INTEGRATED JULL-PLUG IN-TOE OF PIPE. (SECTION 10, OIL AND GAS ACT OF 1929)

and that the work of plugging and filling said well was completed on the 10th day of JANUARY, 19 31 (WELL WOULD NOT TEST OR LIGHT THROUGH 1/2" OPENING AFTER STANDING 48 HOURS FLOW METER TEST)

And further deponents saith not.

[Handwritten signature]