


LATITUDE 39° 05' 00"



LONGITUDE 80° 32' 30"

T'S OGIS topo location

7.5' 10c 0.445 15' 10c _____
 1.28W (calc.) _____

Company _____

Farm _____

Quad CAMDEN 7 1/2

County LEWIS

District FREEMAN'S CREEK

WELL LOCATION MAP

File No. 041-75A

75A

Freemans Creek District, Lewis County, W. Va.

Reserve Gas Co., 145 W. Main St., Clarksburg, W. Va.

On 359 acres, surface and mineral rights owned by Stark A. White,

R. F. D. No. 1, Weston, W. Va.

Elevation, 1436' L.

10" casing, 207'; 8", 1025'; 6-5/8", 1790'.

Abandonment reported to Dept. of Mines April 8, 1935.

Starts below coal.

No record of shot. No water recorded.

Gas well.

	Top.	Bottom.
Little Dunkard Sand	680	- 720
Big Dunkard Sand	780	- 825
Gas Sand	960	- 1030
First Salt Sand	1050	- 1100
Second Salt Sand	1280	- 1325
Maxton Sand	1716	- 1725
Little Lime	1725	- 1730
Big Injun Sand	1800	- 2020
30-Ft. Sand	2335	- 2345
Gordon Sand (gas, 2406, 2426 and 2437')	2404	- 2481
Fifth Sand (gas, 2630')	2628	- 2639
Total depth		2674

**AFFIDAVIT IN TRIPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL**

(REQUIRED BY SECTION 9, ARTICLE 4, CHAPTER 22 OF THE CODE)

**WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION**

WV-75A

Well does not penetrate coal. <small>COAL OPERATOR OR OWNER</small>	Reserve Gas Company <small>NAME OF WELL OPERATOR</small>
ADDRESS	Clarksburg, W. Va., <small>COMPLETE ADDRESS</small>
COAL OPERATOR OR OWNER	April 16th, 1935. 19
ADDRESS	Freemans Creek District
Stark A. White, <small>COAL OPERATOR OR OWNER</small>	Lewis County
Weston, W. Va., RFD #1. <small>ADDRESS</small>	Well No. 923
	Stark A. White Farm

AFFIDAVIT TO BE MADE IN TRIPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT. ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA,
COUNTY OF Lewis } ss:

Wesley S. Carder and Cecil L. Kittle
being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Reserve Gas Company, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 16th day of April, 1935, and that the well was plugged and filled in the following manner:

Manner in which sand was plugged:
Filled hole with clay and cavings to 2340'; Run 6" M. & F. Wood plug at 2340'. Installed bridge and placed one 6" M & F Wood plug and one cement plug at 1610'. Attempted to pull 6-5/8" casing which was set at 1790', would not pull, shot casing off and pulled out 1875', leaving 217' in hole. Installed permanent bridge and filled with clay and cavings to 1085'. Set cement plug at 1085'. Found no 8 1/2" casing in well. Hole then caved and filled up to 217', was unable to place plugs at 800 feet and 660 feet account of hole caving. Bridged hole and set 10" M & F wood plug and a cement plug at 217', Pulled 207' 10" casing and filled solid to surface with clay and cavings.

(Well does not penetrate coal)

Description of monument:
Concrete monument with the inscription well # 923, Reserve Gas Co., thereon. Monument extends 32" above surface of ground.

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 4, CHAPTER 22 OF THE CODE)

and that the work of plugging and filling said well was completed on the 16th day of April