


LATITUDE 39° 05' 00"



LONGITUDE 80° 37' 30"

7'5 OGIS topo location

7.5' loc 0.49 S 15' loc _____
 0.12 W (calc.) _____

Company WNB Co

Farm M. F. McLeighlin #345

Quad VA01S 7 1/2

County LEWIS

District FREEMANS CREEK

WELL LOCATION MAP

File No. 041-85A

**AFFIDAVIT IN TRIPLICATE TO THE AND MANNER OF
PLUGGING AND FILLING WELL**

(REQUIRED BY SECTION 9, ARTICLE 4, CHAPTER 22 OF THE CODE)

**WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION**

none
COAL OPERATOR OR OWNER

T. C. Zinn
NAME OF WELL OPERATOR

4035 1/2 Market St, Parkersburg, W. Va.
COMPLETE ADDRESS

October 25th 19 35
WELL AND LOCATION

Freeman's Creek District

Lewis County

Well No. 34 5 Hope Natural Gas Co
L. P. McLaughlin Farm

AFFIDAVIT TO BE MADE IN TRIPLICATE ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT ONE COPY TO BE RETURNED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES

AFFIDAVIT

STATE OF WEST VIRGINIA,
COUNTY OF _____

J. B. Adams and Lellis Snyder
being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by T. C. Zinn, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 0th day of July, 19 35, and that the well was plugged and filled in the following manner:

Manner in which sand was plugged: filled with red clay from bottom 1343' to 20' above the Injuin Sand, drove wood plug from 1703' to 1710', sealed from 1700' to 1690', sealing then Big Injuin Sand, pulled 6-5/8", set a permanent bridge at 1590' 30' below Laxon sand, filled with clay from 1590' to 1493' 20' above Laxon Sand, drove wood plug from 1490' to 1490', filled with red clay from 1490' to 1345' 20' above salt drove wood plug from 1345' to 1342", cemented from 1342' 1352', set permanent bridge at 1039' 10' below 8-1/4 casing, pulled 8-1/4 casing

Manner in which coal was plugged:
filled with red clay from 1029' to 992", drove wood plug from 992' to 740' 20' above Dunkard Sand, filled with red clay from 740' to 737", filled with red clay from 737' to 737'

OK
Directed Barker according to Rule 18, 1931 Regulations
Description of monument: Cement and 5-3/16 casing

THESE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 4, CHAPTER 22 OF THE CODE
that the work of plugging and filling said well was completed on the 23rd day of August, 19 35.

And further deponents saith not.
T. C. Zinn