



Company PITTSBURGH E. W. VA. GAS CO.
 Address CLARKSBURG, W. VA.
 Farm PETER SWEENEY
 Tract _____ Acres 300 Lease No. 4431
 Well (Farm) No. TWO Serial No. 7039
 Elevation (Spirit Level) 1260' V.A.
 Quadrangle BURNSVILLE N.E. 33
 County LEWIS District COLLINS SETLMT
 Engineer Kenneth B. Moore
 Approved By [Signature]
 Engineer's Registration No. 764
 File No. VOL 161 P. 57 Drawing No. _____
 Date SEPT. 23, 1949 Scale 1" = 500'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. LEW-525-A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
 - Denotes one inch spaces on border line of original tracing.



613

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

WELL RECORD

Permit No. 5754 Oil or Gas Well "GAS"
(KIND)

Company Pittsburgh & West Va Gas Company
 Address Clarksburg, West Va.
 Farm Peter Sweeney Acres 200
 Location (waters) Burnsville H/B. 2-3
 Well No. 7039 Elev. 2260' VA
 District Court House County Lewis
 The surface of tract is owned in fee by Peter Sweeney
 Address Orlando, West Va.
 Mineral rights are owned by Peter Sweeney
 Address Orlando, West Va.
 Drilling commenced September 15, 1915
 Drilling completed October 27, 1915
 Date Shot From To
 With
 Open Flow /10ths Water in Inch
 /10ths Merc. in Inch
 Volume Cu. Ft.
 Rock Pressure lbs. hrs.
 Oil bbls., 1st 24 hrs.
 Fresh water feet feet
 Salt water feet feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10	140'	140'	Size of
8 1/4	056'	056'	
6 5/8	2006'	2006'	Depth set
5 3/16	2473'	None.	
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED SIZE No. Ft. Date
 COAL WAS ENCOUNTERED AT FEET INCHES
 FEET INCHES FEET INCHES
 FEET INCHES FEET INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Red Rock	Red	Soft	0	65			
Lime	White	Hard	65	85			
Slate	"	Soft	85	145			
Red Rock	Red	"	145	225			
Sand	White	Hard	225	245			
Slate	Dark	Soft	245	285			
Red Rock	Red	"	285	435			
Lime	White	Hard	435	460			
Slate	"	Soft	460	500			
Lime	"	Hard	500	530			
Slate	Dark	Soft	530	550			
Red Rock	Red	"	550	610			
Slate	White	"	610	635			
Lime	"	Hard	635	655			
Red Rock	Red	Soft	655	705			
Slate	White	"	705	790			
Sand	"	Hard	790	840			
Slate	Dark	Soft	840	865			
Sand	White	Hard	865	920			
Slate	Dark	Soft	920	925			
Sand	"	Hard	925	1000			
Slate	Black	Soft	1000	1035			
Lime	White	Hard	1035	1065			
Slate	Dark	Soft	1065	1135			
Sand	White	Hard	1135	1230			
Slate	Dark	Soft	1230	1235			
Sand	"	Hard	1235	1295			
Slate	White	Soft	1295	1325			
Sand	Dark	Hard	1325	1360			
Slate	Dark	Soft	1360	1390			
Lime	White	Hard	1390	1405			
Slate	"	Soft	1405	1440			
Sand	Dark	Hard	1440	1470			
Slate	Black	Soft	1470	1560			
Lime	White	Hard	1560	1500			
Slate	Dark	Soft	1500	1620			
Sand	"	Hard	1620	1660			
Slate	Black	Soft	1660	1675			



Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Sand	Dark	Hard	1675	1730			
Slate	"	Soft	1730	1815			
Sand	White	Hard	1815	1875			
Red Rock	Red	Hard	1875	1925			
Sand	Dark	Hard	1925	1935			
Slate	Black	Soft	1935	1960			
Lime	White	Hard	1960	1990			
Pencil Cave	"	Soft	1990	1994			
Big Lime	"	Hard	1994	2000			
Big Injun	"	"	2000	2140	Sh. Gas	2090'	
Slate	Dark	Soft	2140	2144			
Squaw Sand	"	Hard	2144	2260			
Slate	"	Soft	2260	2340			
Sand	"	Hard	2340	2350			
Slate	Black	Soft	2350	2365			
Lime	Dark	Hard	2365	2380			
Slate&Shells	White	Hard/Soft	2380	2460			
30 Ft. Sand	"	Hard	2460	2473	Gas	2465-2470'	
Un-recorded			2473	2851			
Total Depth.....				2851			

September 21, 1949

Date _____, 19____

PITTSBURGH & WEST VA GAS COMPANY

APPROVED _____

Owner

By _____

(Title)

The Philadelphia Company of West Virginia

7039

Sweeney

Record of Well No. 7039 Located on Peter Stormy Farm Aug 12 1910

Court House District Lewis County W. Va State

Division K District No. 10 Drilled under Well Order

Rig built by John Craig Began Sept 5 1910 Completed Sept 10 1910

Well drilled by C. W. McCall Began Sept 15 1910 Completed Oct 23 1910

Depth of Well ~~2475~~ 2851 feet, slate Size of Hole 6 7/8" Producing Gas

Elev: 1260

CASED WITH

REMARKS

AMOUNT	SIZE	KIND	REMARKS
15	1 1/2"	Wood	
140	10"	Casing	Pulled 91' Left on 41' of 10"
856	8 1/2"	"	Pulled 754' Left on 102' of 8 1/2"
2006	6 7/8"	"	8 1/4 x 6 7/8" Bad Hole Packed with 1300' of 6 7/8"
2493	5 1/2"	"	6 1/2 x 5 1/2" packed Packed with 1000' of 6 7/8"
2494	2"	Subg	6 7/8 x 2" NW packer
2496	2"	Subg	Packed with 100' of 2" 16'

COAL VEINS

FORMATIONS

NAME	TOP	BOTTOM	OIL	GAS	WATER	REMARKS
Big Linn	1994	2010				com. time 4 hrs 19. 1910
Big Logan	2010	2140	2090	2090		2 shows
Squeak sand	2144	2265				
20 feet sand	2340	2350				
30 "	2460	2473		34.65		17/10 water 6 7/8" of 1570 McS
Sand	2574	2600				
Sandstone	2612	2620				3 1/2 hrs. Well drilled down by Peter Stormy Co. from 2473 to 2851
Sandstone	2640	2649				
Sand	2662	2666				
5th sand	2827	2831				

Plugged 10-3-19 to 10-10-19:

Casing	2851-2852
Agua	2852-2855
Cement	2450-2440
Agua	2440-2030
Bridel	2030
Cement	2030-2020
Agua	2020-875
Bridel	875
Cement	875-865
Agua	865-165
Bridel	165
Cement	165-155
Agua	155-5
Cement	5-Surface

FIRST PRESSURE TEST IN 6 1/4 CASING REMARKS

30 Sec.	26	lbs.
1 Min.	52	"
2 "	85	11 2/4 1/2
5 "	175	"
10 "	300	"
25 "	495	"
30 "		"

Rock Pressure 600 " in 30 Min ^{and crumped at that}
 Taken Oct 23 1915
 By F. W. Lumber

WELL TUBED AND PACKED Oct 27 1915

1139 to 2473' 5 3/16" Cas
 6 1/8" x 5 3/16" line Perforated
 139 to 243' of liner
 Perforated to 2454'

9 1/2" 3
 4 1/2" 2 1/2
 6 1/8" x 5 3/16"
 Packed 10-49

FIRST PRESSURE TEST IN 5 3/16 TUBING REMARKS

30 Sec.	30	lbs.
1 Min.	67	"
2 "	115	15 2/4 1/2
5 "	227	"
10 "	385	"
25 "	557	"
30 "		"

Rock Pressure 875 " in 14 hrs
 Taken Oct 27 1915
 By F. W. Lumber

MATERIAL FOR THIS WELL RECEIVED FROM FOLLOWING SOURCES:

1 old Rig and Lumber from E. C. Bond #4009
 4806 7th Rig Lumber 1. McP. July @ 28 #10

Petro Survey FORMATIONS #7039

NAME	TOP	BOTTOM	OIL	GAS	WATER	REMARKS
Red Rock	0	65				
Lime	65	85				
slate	85	145				
Red Rock	145	225				
sand	225	245				
slate	245	285				
Red Rock	285	435				
Lime	435	460				
slate	460	500				
Lime	500	530				
slate	530	550				
Red Rock	550	610				
slate	610	635				
Lime	635	655				
Red Rock	655	705				
slate	705	790				
sand	790	840				
slate	840	865				
sand	865	920				
slate	920	925				
sand	925	1000				
slate	1000	1035				
Lime	1035	1065				
slate	1065	1135				
sand	1135	1730				
slate	1730	1735				
sand	1735	1795				
slate	1795	1875				
sand	1875	1890				
slate	1890	1390				
Lime	1390	1405				
slate	1405	1440				
sand	1440	1470				
slate	1470	1560				
Lime	1560	1580				
slate	1580	1670				
sand	1670	1685				
slate	1685	1695				
sand	1695	1730				
slate	1730	1815				
sand	1815	1875				
Red Rock	1875	1925				
sand	1925	1935				
slate	1935	1960				
Lime	1960	1990				
slate	1990	1994				
Big Lime	1994	2080				
in Argun	2080	2140	2090	2090		
slate	2140	2144				
Dyke	2144	2760				
slate	2760	7340				
50' sand	7340	7355				
slate	7355	7365				
Lime	7365	7380				
slate	7380	2460				
30' sand	2460	2473				
slate		2473				

2465
2470
Total Depth