

New Location...   
 Drill Deeper.....   
 Abandonment.....  2453


Company Pittsburgh & W.Va. Gas Co.  
 Address Clarksburg, W.Va.  
 Farm T. J. WHITE  
 Tract \_\_\_\_\_ Acres 373 1/2 Lease No. 4426  
 Well (Farm) No. 1 E 4 Serial No. 2453  
 Elevation (Spirit Level) 974' V.A. & 1113' L  
 Quadrangle Vadis S.E. 33  
 County Lewis District Court House  
 Engineer Kenneth B. Moore  
 Engineer's Registration No. \_\_\_\_\_  
 File No. V-153, P-44 Drawing No. \_\_\_\_\_  
 Date June 2, 1947 Scale 1" = 1000'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. LEW-395-A-#2453  
LEW-616-A-#1983

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 --- Denotes one inch spaces on border line of original tracing.

LATITUDE 39° 00' 00"



LONGITUDE 90° 58' 00"

7.5 OGIS topo location

7.5' loc 0.25 S 15' loc \_\_\_\_\_  
                  0.92 W (calc.) \_\_\_\_\_

Company \_\_\_\_\_

Farm \_\_\_\_\_

Quad PETERSON 7 1/2'

County LEWIS

District COURT HOUSE

WELL LOCATION MAP

File No. 041-616A



STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

711

WELL RECORD

"GAS"

Oil or Gas Well (KIND)

Permit No. 616-A

Company Equitable Gas Company-West Va Div.  
Address Clarksburg, West Va.  
Farm Thomas J. White Acres 373  
Location (waters) Valley S/S. 3-3  
Well No. 1983 Elev. 974' VA  
District Court House County Summit Lewis  
The surface of tract is owned in fee by Thomas H. White  
Camden, W. Va.  
Address Thomas H. White  
Mineral rights are owned by Thomas H. White  
Camden, W. Va.  
Address \_\_\_\_\_  
Drilling commenced August 16, 1909  
Drilling completed September 27, 1909  
Date Shot \_\_\_\_\_ From \_\_\_\_\_ To \_\_\_\_\_  
With \_\_\_\_\_  
Open Flow \_\_\_\_\_ /10ths Water in \_\_\_\_\_ Inch  
\_\_\_\_\_ /10ths Merc. in \_\_\_\_\_ Inch  
Volume \_\_\_\_\_ Cu. Ft.  
Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
Fresh water \_\_\_\_\_ feet \_\_\_\_\_ feet  
Salt water \_\_\_\_\_ feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10	180'	160'	Size of <u>162</u>
8 1/4	932'	932'	<u>331</u>
6 3/4	1928'	1928'	Depth set <u>584</u>
5 3/16			
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom


CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_

COAL WAS ENCOUNTERED AT 232 FEET 60 INCHES

\_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES

\_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
1st Sand	White	Soft	0	16	Water	25'	
2nd Sand	Red	Hard	16	26			
3rd Sand	Red	Soft	26	76			
4th Sand	White	Hard	76	176			
5th Sand	Light	Soft	176	202			
6th Sand	Black	Soft	202	232			
7th Sand	Black	Soft	232	237			
8th Sand	"	Soft	237	308			
9th Sand	White	"	308	320			
10th Sand	"	Hard	320	330			
11th Sand	"	Soft	330	390			
12th Sand	White	"	390	470			
13th Sand	"	Hard	470	495			
14th Sand	"	Soft	495	496			
15th Sand	"	Hard	496	514			
16th Sand	Light	Soft	514	519			
17th Sand	Red	"	519	525			
18th Sand	Black	"	525	580			
19th Sand	White	Close	580	630			
20th Sand	Black	Soft	630	700			
21st Sand	White	Hard	700	712			
22nd Sand	"	"	712	742			
23rd Sand	"	Soft	742	772			
24th Sand	Red	"	772	775			
25th Sand	Light	Open	775	778			
26th Sand	"	Hard	778	852			
27th Sand	"	Soft	852	856			
28th Sand	"	Hard	856	859			
29th Sand	"	Soft	859	900			
30th Sand	Gray	Hard	900	935			
31st Sand	White	Open	935	1005			
32nd Sand	Black	Soft	1005	1015			
33rd Sand	White	Open	1015	1055			
34th Sand	Black	Soft	1055	1070			
35th Sand	Light	Open	1070	1115			
36th Sand	Black	"	1115	1150			
37th Sand	White	"	1150	1215			
38th Sand	Black	Soft	1215	1310			
39th Sand	Light	Hard	1310	1430			



1953

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Slate	Light	Soft	1430	1515			
7th. Salt Sand	White	Hard	1515	1545			
Slate	Black	Soft	1545	1600			
8th. Salt Sand	White	Hard	1600	1640			
Slate&Shells	"	"	1640	1660			
Red Rock	Red	Soft	1660	1750			
Huron Sand	White	Hard	1750	1770			
Red Rock	Red	Soft	1770	1805			
Little Lime	White	Hard	1805	1820			
Pencil Cave	Black	Soft	1820	1845			
Big Lime	White	Hard	1845	1905			
Big Injun	"	"	1905	2070	Gas	2020'	
Slate	Light	Soft	2070	2080			
Squaw Sand	White	Hard	2080	2115			
Slate&Shells	Light	Soft	2115	2225			
Ganta Sand	Gray	Hard	2225	2270			
Slate&Shells	Light	Soft	2270	2400			
50 Ft. Sand	White	Hard	2400	2430			
Slate	Light	Soft	2430	2430			
30 Ft. Sand	Gray	Hard	2430	2444			
Slate	Light	Soft	2444	2478			
Gordon Stray	White	Open	2478	2498	Gas	2483'	
Slate	Light	Soft	2498	2506			
Gordon Sand	"	Hard	2506	2530			
Un-Recorded			2530	2536			
Total depth.....				2536			

April 29, 1953

Date \_\_\_\_\_, 19\_\_\_\_

EQUITABLE GAS COMPANY-WEST VA DIV.

APPROVED \_\_\_\_\_

Owner

By W. J. [Signature]  
(Title)