

E. W. (G. W.) STOWERS NO. 36 WELL. (88)
(LINCOLN LAND ASSN. NO. 36).

601
No. 243-34 O.F.-Lincoln
No. L-601 CWL p. 330

No 1842 a May
08 1913 G. E. L.

Duval District, Lincoln County, W. Va.
Columbia G. & E. Co. (CWL)
Elevation, 755' L.
Lincoln Well No. 36, Lincoln Land Association.
On land of G. W. (E. W.) STOWERS, on Merrick Creek.
Copied from record books of Columbia Elec. & Gas Co., by
C. E. Krebs, Feb. 24, 1912.
Well completed Dec. 2, 1909.
1,500,000 cu. ft. gas.

	Top.	Bottom.
Coal	150	- 155
Gas Sand	745	- 765
Salt Sand	790	- 1380
Little Lime	1410	- 1445
Pencil Cave	1445	- 1452
Big Lime	1452	- 1635
Big Injun Sand	1640	- 1665
Berea Sand (gas, 2134-2163'; 1500 M.)	2134	- 2163
Total depth		2165

Sheridan.....District, Lincoln County, W. Va.
 Copied from record books of Columbia Elec. & Gas Co.,
 by C. E. Krebs, Feb. 24, 1912.

	Top.	Bottom.	Thickness.
Surface, green and red	0	- 25	25
Slate, lime, and shells	25	- 100	75
Sand	100	- 150	50
Coal	150	- 155	5
Sand	155	- 300	145
Slate	300	- 330	30
Sand	330	- 390	60
Slate	390	- 470	80
Sand	470	- 500	30
Slate	500	- 540	40
Sand	540	- 565	15
Slate	565	- 575	10
Sand	575	- 740	65
Slate	740	- 745	5
Sand	745	- 765	20
Slate	765	- 790	15
Salt Sand	790	- 1230	440
Slate	1230	- 1270	40
Lime	1270	- 1285	15
Slate	1285	- 1300	15
Sand	1300	- 1380	80
Maxton Sand	1380	- 1410	30
Little Lime	1410	- 1445	35
Pencil Cave	1445	- 1452	7
Big Lime	1452	- 1635	182
Slate	1635	- 1640	5
Big Injun Sand	1640	- 1665	25
Slate	1665	- 1685	20
Black sand	1685	- 1740	55
Slate	1740	- 1780	40
Hard shells	1780	- 1900	120
Slate	1900	- 2134	234
Berea Sand	2134	- 2163	29
Total depth		2165	